



EMERGENCY LIGHTING SYSTEM

Reliable lighting for safety during emergencies

Honeywell

EMERGENCY LIGHTING SYSTEM

| Ensuring safe movement, evacuation and life safety

In modern premises, emergency situations can occur anytime. And it's human nature to panic when faced with such a situation – whether it's a fire, and earthquake or any other kind of crisis. To mitigate the effects of the crisis, it's critical to evacuate people quickly and get them to safety. But if they cannot see where they're going, they will panic and evacuation will slow down. Honeywell's best-in-class Emergency Lighting Systems are engineered to respond instantly to crisis situations and provide sufficient lighting to help people evacuate. These systems will work even in case of a power failure, ensuring that you can get your people out and keep them safe as you deal with the crisis.



PRODUCT SEGMENT



138057	138087	138126	138009
UniLED Combi ST LED 230V including Pict 1h/3h/8h	ExiLED M ST LED 25m 230V including Pict 1h/3h/8h	ExiLED M ST LED 40m 230V including Pict 1h/3h/8h	MaxLED M ST LED 26m 230V including pict 1h/3h/8h
Reading distance, exit sign: One-side 27 m / Two-side 23 m	Reading distance, exit sign: Two-sided 25m	Reading distance, exit sign: Two-sided 40m	Reading distance, exit sign: Two-sided 26m
Lumen output, mains: 350 lm	Lumen output, mains: 150 lm	Lumen output, mains: 180 lm	Lumen output, mains: 280 lm
IP rating: IP20	IP rating: IP40	IP rating: IP40	IP rating: IP40
Materials: PC/ABS (housing) and PC (diffuser)	Materials: Aluminum, Acrylic Plate	Materials: N/A	Materials: Aluminum, Plexiglass, PC/ABS
Pictograms: 4 Pictograms (Left, Right, Down, Up) are included in the ordering part code of 138057	Pictograms: 4 Pictograms (Left, Right, Down, Up) are included in the ordering part code of 138087	Pictograms: 4 Pictograms (Left, Right, Down, Up) are included in the ordering part code of 138126	Pictograms: 4 Pictograms (Left, Right, Down, Up) are included in the ordering part code of 138009
Maintained/Non-Maintained: Maintained	Maintained/Non-Maintained: Maintained	Maintained/Non-Maintained: Maintained	Maintained/Non-Maintained: Maintained
Self Testing/Manual Testing: SelfTesting	Self Testing/Manual Testing: SelfTesting	Self Testing/Manual Testing: SelfTesting	Self Testing/Manual Testing: SelfTesting
Battery: 4.8V/ 1.2Ah Ni-MH	Battery: 3.6V/ 1.2Ah Ni-MH	Battery: 3.6V/ 1.2Ah Ni-MH	Battery: 3.6V/ 1.2Ah Ni-MH



138254
MaxLED M ST LED 65m 230V including pict 1h/3h/8h
Reading distance, exit sign: Two-sided 65m
Lumen output, mains: 900 lm
IP rating: IP40
Materials: Aluminum, Plexiglass, PC/ABS
Pictograms: 4 Pictograms (Left, Right, Down, Up) are included in the ordering part code of 138254
Maintained/Non-Maintained: Maintained
Self Testing/Manual Testing: Self Testing
Battery: 4.8V/ 1.2Ah Ni-MH

138255
MaxLED M ST LED 47m 230V including pict 1h/3h/8h
Reading distance, exit sign: Two-sided 47m
Lumen output, mains: 550lm
IP rating: IP40
Materials: Aluminum, Plexiglass, PC/ABS
Pictograms: 4 Pictograms (Left, Right, Down, Up) are included in the ordering part code of 138255
Maintained/Non-Maintained: Maintained
Self Testing/Manual Testing: Self Testing
Battery: 4.8V/ 1.2Ah Ni-MH

138172
AgoraLED NM LED IP42 230V 2X6W 1h/3h/8h
Reading distance, exit sign: N/A
Lumen output, mains: N/A
IP rating: IP42
Materials: PC/ABS, PC, Aluminium
Pictograms: N/A
Maintained/Non-Maintained: Non - Maintained
Self Testing/Manual Testing: Self Testing
Battery: 12V / 7Ah Pb

138173
AgoraLED NM LED IP65 230V 2X6W 1h/3h/8h
Reading distance, exit sign: N/A
Lumen output, mains: N/A
IP rating: IP65
Materials: PC/ABS, PC, Aluminium
Pictograms: N/A
Maintained/Non-Maintained: Non - Maintained
Self Testing/Manual Testing: Self Testing
Battery: 12V / 7Ah Pb



138073
AeriLED AP NM ST LED 230V 1h/3h/8h
Reading distance, exit sign: N/A
Lumen output, mains: N/A
IP rating: IP20
Materials: PC/ABS
Pictograms: N/A
Maintained/Non-Maintained: Non - Maintained
Self Testing/Manual Testing: Self Testing
Battery: 4.8V/ 1.2Ah Ni-MH

138008
MultiLED Combi ST LED 230V including pict 1h3h/8h
Reading distance, exit sign: Two-sided 20m
Lumen output, mains: 275 lm
IP rating: IP44
Materials: PC, ABS/PC
Pictograms: 4 Pictograms (Left, Right, Down, Up) are included in the ordering part code of 138008
Maintained/Non-Maintained: Maintained
Self Testing/Manual Testing: Self Testing
Battery: 4.8V/ 1.2Ah Ni-MH

138002
ImPerLED Combi ST LED 230V including pict 1h/3h/8h
Reading distance, exit sign: 30m
Lumen output, mains: 250 lm
IP rating: IP65
Materials: ABS/PC, PC
Pictograms: 4 Pictograms (Left, Right, Down, Up) are included in the ordering part code of 138002
Maintained/Non-Maintained: Maintained
Self Testing/Manual Testing: Self Testing
Battery: 3.6V/ 2Ah Ni-MH

138406
ImPerLED Combi EST LED 230V including pict 1h/3h/8h
Reading distance, exit sign: 30m
Lumen output, mains: 250 lm
IP rating: IP65
Materials: ABS/PC, PC
Pictograms: 4 Pictograms (Left, Right, Down, Up) are included in the ordering part code of 138406
Maintained/Non-Maintained: Maintained
Self Testing/Manual Testing: Self Testing
Battery: 4.8V/ 2Ah Li ₄ Ti ₅ O ₁₂



138006
Ova-OmniLED Square ER/AP NM ST LED 230V 1h/3h/8h
Reading distance, exit sign: N/A
Lumen output, mains: N/A
IP rating: IP20
Materials: PC/ABS
Pictograms: N/A
Maintained/Non-Maintained: Non - Maintained
Self Testing/Manual Testing: Self Testing
Battery: 4.8V/ 1.2Ah Ni-MH

138007
Ova-OmniLED R Spot ER/AP NM ST LED 230V 1h/3h/8h
Reading distance, exit sign: N/A
Lumen output, mains: N/A
IP rating: N/A
Materials: N/A
Pictograms: N/A
Maintained/Non-Maintained: Non - Maintained
Self Testing/Manual Testing: Self Testing
Battery: 4.8V/ 1.2Ah Ni-MH

138004
Cube M ST LED 50m 230V w/pict 1h/3h/8h
Reading distance, exit sign: 50m
Lumen output, mains: 370 lm
IP rating: IP40
Materials: Aluminum, ABS/PC, PC, Acrylic Plate
Pictograms: 4 Pictograms (Left, Right, Down, Up) are included in the ordering part code of 138004
Maintained/Non-Maintained: Non - Maintained
Self Testing/Manual Testing: Self Testing
Battery: 4.8V/ 1.2Ah Ni-MH

138005
SeqLED E NM ST LED 230V 1h/3h/8h
Reading distance, exit sign: N/A
Lumen output, mains: N/A
IP rating: IP65
Materials: ABS/PC, PC
Pictograms: N/A
Maintained/Non-Maintained: Non - Maintained
Self Testing/Manual Testing: Self Testing
Battery: 4.8V/ 2Ah Li ₄ Ti ₅ O ₁₂



138410
SeqLED ER NM ST LED 230V 1h/3h/8h
Reading distance, exit sign: N/A
Lumen output, mains: N/A
IP rating: IP65
Materials: ABS/PC, PC
Pictograms: N/A
Maintained/Non-Maintained: Non - Maintained
Self Testing/Manual Testing: Self Testing
Battery: 4.8V/ 2Ah Li ₄ Ti ₅ O ₁₂

502531
AlphaLED 26m 230V including Pict 3h
Reading distance, exit sign: 26m
Lumen output, mains: 90 lm
IP rating: IP44
Materials: Fire retardant ABS, Acrylic plate
Pictograms: One Pictogram price is included (as per the image). For more pictograms, separate order is to be placed
Maintained/Non-Maintained: Maintained
Self Testing/Manual Testing: Manual Testing
Battery: 3.6V/1,5Ah Ni-MH

007004
EcoLED 14m 230V including Pict 1h
Reading distance, exit sign: 14m
Lumen output, mains: 75 lm
IP rating: IP20
Materials: PC/ABS (housing) and PC (diffuser)
Pictograms: 3 Pictograms (Left, Right, Down) are included in the price
Maintained/Non-Maintained: Non - Maintained
Self Testing/Manual Testing: Manual Testing
Battery: 3.6V/0,6Ah Ni-Cd

800051
EcoLED 15m 230V including Pict 1.5h
Reading distance, exit sign: 15m
Lumen output, mains: 40 lm
IP rating: IP42
Materials: PC/ABS (housing) and PC (diffuser)
Pictograms: 3 Pictograms (Left, Right, Down) are included in the price
Maintained/Non-Maintained: Maintained
Self Testing/Manual Testing: Manual Testing
Battery: 3.6V/0,6Ah Ni-Cd



210004
Slim-Classic LED 22m 230V including Pict 1.5h
Reading distance, exit sign: 22m
Lumen output, mains: 40 lm
IP rating: IP30
Materials: PC/ABS, PC
Pictograms: 3 Pictograms (Left, Right, Down) are included in the price
Maintained/Non-Maintained: Maintained
Self Testing/Manual Testing: Manual Testing
Battery: 3.6V/0,6Ah Ni-Cd

270006
Spot Light ER LED 230V 1.5h
Reading distance, exit sign: N/A
Lumen output, mains: N/A
IP rating: IP40
Materials: PC/ABS, PC
Pictograms: N/A
Maintained/Non-Maintained: Non - Maintained
Self Testing/Manual Testing: Manual Testing
Battery: 3.6V/1,5Ah Ni-MH

271004
Spot Light AP LED 230V 1.5h
Reading distance, exit sign: N/A
Lumen output, mains: N/A
IP rating: IP40
Materials: PC/ABS, PC
Pictograms: N/A
Maintained/Non-Maintained: Non - Maintained
Self Testing/Manual Testing: Manual Testing
Battery: 3.6V/1,5Ah Ni-MH

502009
EcoLED 20m 230V including Pict 3h
Reading distance, exit sign: 20m
Lumen output, mains: 75 lm
IP rating: IP54
Materials: PC, Acrylic plate
Pictograms: 3 Pictograms (Left, Right, Down) are included in the price
Maintained/Non-Maintained: Maintained
Self Testing/Manual Testing: Manual Testing
Battery: 3.6V/0,6Ah Ni-Cd



193504
Waterproof LED 22m 230V including Pict 1.5h
Reading distance, exit sign: 22m
Lumen output, mains: 40 lm
IP rating: IP65
Materials: ABS/PC, PC
Pictograms: 3 Pictograms (Left, Right, Down) are included in the price
Maintained/Non-Maintained: Non - Maintained
Self Testing/Manual Testing: Manual Testing
Battery: 3.6V/0,6Ah Ni-Cd

502827
BetaLED 16m 230V including Pict 3h
Reading distance, exit sign: 16m
Lumen output, mains: 85 lm
IP rating: IP40
Materials: ABS/PC, PVC, Acrylic plate
Pictograms: One Pictogram price is included (as per the image). For more pictograms, separate order is to be placed
Maintained/Non-Maintained: Maintained
Self Testing/Manual Testing: Manual Testing
Battery: 3.6V/1Ah Ni-Cd

503437
BetaLED 30m 230V including Pict 3h
Reading distance, exit sign: 30m
Lumen output, mains: 105 lm
IP rating: IP40
Materials: ABS/PC, PVC, Acrylic plate
Pictograms: One Pictogram price is included (as per the image). For more pictograms, separate order is to be placed
Maintained/Non-Maintained: Maintained
Self Testing/Manual Testing: Manual Testing
Battery: 3.6V/0,6Ah Ni-Cd

310009
WhiteLED 26m 230V including Pict 1.5h
Reading distance, exit sign: 26m
Lumen output, mains: 40 lm
IP rating: IP40
Materials: ABS/PC, PC
Pictograms: 3 Pictograms (Left, Right, Down) are included in the price
Maintained/Non-Maintained: Maintained
Self Testing/Manual Testing: Manual Testing
Battery: 3.6V/0,6Ah Ni-Cd



502211
EcoLED 22m 230V including Pict 3h
Reading distance, exit sign: 22m
Lumen output, mains: 75 lm
IP rating: IP54
Materials: PC, Acrylic plate
Pictograms: 3 Pictograms (Left, Right, Down) are included in the price
Maintained/Non-Maintained: Maintained
Self Testing/Manual Testing: Manual Testing
Battery: 3.6V/1Ah Ni-Cd

503017
EcoLED 30m 230V including Pict 3h
Reading distance, exit sign: 30m
Lumen output, mains: 75 lm
IP rating: IP54
Materials: PC, Acrylic plate
Pictograms: Pictograms (L,R,D) included in the price
Maintained/Non-Maintained: Maintained
Self Testing/Manual Testing: Manual Testing
Battery: 3.6V/1Ah Ni-Cd

470001
Escape Route ER LED 230V 1.5h
Reading distance, exit sign: N/A
Lumen output, mains: N/A
IP rating: IP42
Materials: ABS/PC, PC
Pictograms: N/A
Maintained/Non-Maintained: Non - Maintained
Self Testing/Manual Testing: Manual Testing
Battery: 3.6V/1Ah Ni-Cd

471000
Escape Route AP LED 230V 1.5h
Reading distance, exit sign: N/A
Lumen output, mains: N/A
IP rating: IP42
Materials: ABS/PC, PC
Pictograms: N/A
Maintained/Non-Maintained: Non - Maintained
Self Testing/Manual Testing: Manual Testing
Battery: 3.6V/1Ah Ni-Cd



408004
Comfort Light LED 16m 230V including pict 1.5h
Reading distance, exit sign: 16m
Lumen output, mains: N/A
IP rating: IP42
Materials: ABS/PC, PC
Pictograms: 3 Pictograms (Left, Right, Down) are included in the price
Maintained/Non-Maintained: Non - Maintained
Self Testing/Manual Testing: Manual Testing
Battery: 3.6V/1Ah Ni-Cd

For more information,

www.honeywellbuildings.in

Call: 1800 103 4761

Email: HBT-IndiaBuildings@Honeywell.com

Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43,

Block C, Sushant Lok Phase - I,

Gurgaon - 122 002.

**THE
FUTURE
IS
WHAT
WE
MAKE IT**

