1 💀 🏹

COMPLETE LED LIGHTING SOLUTIONS TECHNICAL CATALOGUE | 2021-22





<u>Global Headquarters</u> Net Zero Energy Building spread over 48,000 sq. mtrs.



Conceived back in 1960, the Jaquar Group has been built on the platform of the highest quality standards, aesthetics and the intent of providing world-class products. Today, the Jaquar Group caters to luxury, premium and value bathroom segments with Artize, Jaquar & Essco brands, respectively, for residential and commercial sectors across the globe. The group's lighting division, Jaquar Lighting too, has been setting new parameters of excellence while witnessing unprecedented success.

# Ärtize

It pays a tribute to the fine traditions of exquisite craftsmanship and precision where design, technology and talent combine to deliver a masterpiece. Artize products are crafted for luxurious bath spaces. Perfect harmony is the very essence of Artize- together as coordinates or even as individual pieces. Artize's exquisite craftsmanship is so stunning that it can inspire the design principles of not just your bath spaces but of your entire living spaces.

### ) Jaquar

A leading global super brand known for its excellence in innovation and technology. The highest build standards combine with the most beautifully designed aesthetics to provide world-class products for tough conditions. With a superb blend of ergonomic shapes, contemporary styles and meticulous finish, Jaquar continues to enthrall millions of hearts across the world with Its wide range of concepts and products.

#### ESSCO Bath fittings since 1960

For over five decades now, Essco, the bath fittings brand, has been supporting affordable and sustainable housing in India. Essco is a value for money bath brand from the Jaquar Group, which is the leader in Complete Bathing Solutions. Essco, a Pan India brand, added a whole new chapter in the bath fittings industry by ushering in the era of

the organised bath market. Essco set out with an obsession for good quality products at affordable pricing, one that was unheard of in the corridors of bath fittings manufacturers then. With its 10 years of warranty and impeccable customer service, Essco is standing tall in the Indian bath fittings Industry since 1960 and touching more hearts every year.











# JAQUAR LIGHTING The torchbearer for innovation in lighting

Innovative, energy efficient lighting solutions, for an array of places and purposes. From home to office, decorative to landscaping, from gorgeous chandeliers to unique LEDs, you name it, we have it. All, illuminating with the highest quality, fascinating designs and immaculate perfection.

### What Makes Jaquar Lighting stand apart:

- Complete LED Lighting Solutions
- Futuristic manufacturing facility
- Global certifications
- Unique customization option for Chandeliers
- Best in the world lighting, best for the Indian conditions
- Smart New Products
- Trusted for Prestigious projects
- Jaquar Lighting Orientation Centres
- Pro-active Customer Care



# Complete LED Lighting Solutions

Jaquar Lighting gives you complete LED lighting solutions – for residential, commercial and outdoor use. Choose for varied budgets without compromising on quality and reliability.

They are designed to complement and co-ordinate the most exclusive interior and exterior lifestyles and decors, from classic to contemporary.

In fact, Jaquar Lighting carries forward the legacy of Jaquar Group where the thrust has always been on creating new parameters of design, quality and customer satisfaction.



# Futuristic manufacturing facility

Jaquar Lighting's state-of-the-art manufacturing plant is a fully automated facility having in-house ROHS compliant LED Driver.

Its LED Module manufacturing unit is equipped with high-precision optical inspection besides the capacity to make 87,000 components everyhour.

Jaquar Lighting also has the only NABL accredited lab in India, with an in-house facility for CCT testing upto 100,000 K.

With so many firsts to its credit and with sustained investment in enhancing the capabilities, Jaquar has been setting new benchmarks for the lighting industry.

One of the flag-bearers of the Government's 'Make in India' initiative, Jaquar Lighting now has an ultra-modern manufacturing facility that sprawls over 250,000 sq. ft. of covered area.

This fully automated plant, with a capacity to make 2,400 bulbs/ hour, produces a wide range of world-class LED lighting products under one roof - for residential as well as commercial/ industrial usage, including LED Bulbs, Battens, Recessed lights, Panels, LED Streetlights, Floodlights, Smart lights and Highbay lights.







### **ISO Certificate**



ZERTIFIKAT + CERTIFICATE + 到註註書 + CEPTN中NKAT + CERTIFICADD + CERTIFICAT

### **BIS Certificate**



### **NABL** Certificate



# Global certifications

They say, excellence begets rewards and laurels. Jaquar Lighting's NABL Accredited Lab has enabled the company to come up with the best lighting products. Certifications followed along the way:

- System Certifications like ISO 9001:2015, BIS and BEE
- BIS Certification for its LED Lamps, Drivers, Panels, LED Streetlights, and LED Floodlights, as per the latest applicable Indian Standards



# Unique customization option for Chandeliers

Jaquar Lighting has the first chandelier manufacturing plant in India with in-house facilities for designing, fabrication, plating and assembly, to provide unique customized solutions.

As a chandelier manufacturer, Jaquar is also the first and only one in India to offer 24K gold plating-in Antique Gold, as well as Chrome plating with some of the World's best crystals.



# Best in the world lighting, best for the Indian conditions

Jaquar Lighting Products are built keeping in mind the tough, ever-changing Indian weather conditions. These products pass through a wide range of tests to ensure their endurance, reliability and durability.

Jaquar Lighting Products follow the philosophy of sustained development. Precisely why, all these products are eco-friendly and energy efficient.

Jaquar Lighting LED products:

- Save upto 90% of the energy required for similar levels of illumination by conventional, non-LED products
- Designed to be glare free and provide uniform illumination
- Built to be high efficiency products that provide approx.
   100 Lm/W-higher than most competing products

# Trusted for Prestigious projects

Jaquar Lighting has been entrusted to light up an array of prestigious premises for its expertise in coming up with the best lighting solutions. Have a look:

- Central Hall, Parliament of India
- Supreme Court, Delhi
- Jammu & Kashmir Assembly, Srinagar
- Governor House, Dehradun
- Air Force Headquarters, Delhi
- National Defence Academy (NDA), Pune
- ISRO
- Royal Orchid hotels in Bangalore, Hyderabad and Jaipur
- Hotel Mount View, Chandigarh
- Hotel Westin, Hyderabad
- Hotel India Awadh, Lucknow
- Amber Conventional Centre, Indore
- Hindustan Club, Kolkata
- Hotel Crown, Bhubaneswar

- IIM Shillong
- IIT Mandi & IIT Guwahati
- Bangur House, Kolkata
- Holiday Inn, Kolkata
- Mahagun, Noida
- Supertech, Noida
- MG Motors, Delhi
- Jeep Showroom, Haryana
- Hotel Hyatt, Gurgaon
- Hotel Marriott, Nasik
- HP (Hewlett Packard)

Jaquar Lighting also has corporate tie-ups with Sayaji Group, Lemontree, and Jaypee, among others.





# Jaquar Lighting Orientation Centres

Jaquar Orientation Centres are spread across the length & breadth of the nation and even abroad.

You can discover the whole gamut of Jaquar Lighting products under one roof. Offering a one-stop solution to the discovery and selection process, the Orientation Centre is manned by trained experts who can help you find the perfect match even for your most unique lighting requirements.

So drop in to a Jaquar Orientation Centre today. And bring home the glow of happiness!

For more information, visit any of our 21 Orientation Centres in following cities:

Ahmedabad, Bangalore, Bhopal, Bhubaneswar, Chandigarh, Chennai, Cochin, Guwahati, Hyderabad, Jaipur, Jammu, Kolkata, Lucknow, Ludhiana, Mumbai, Nagpur, New Delhi, Pune, Raipur, Siliguri and Surat







# Customer Care

Even the peers vouch for Jaquar Lighting's enviable customer care.

Backed by over 1,000 trained technicians and warranty on its products, Jaquar Lighting provides India's most reliable service to its customers with fully integrated service network across the country.

Toll free Customer Care No: 1800 212 6808 E-mail: ccare.lighting@jaquar.com

# **Category Content**




### Facade Lights

Jaquar carefully designed night lighting on the façades that respects the building's architecture, context



## Chandeliers

Discover a grand centrepiece for your indoor space in Jaquar's range of chandeliers



## Decorative

The best of global lighting designs and craftsmanship in a large range of designs and shapes




# Commercial

The latest options in LED lighting solutions for indoor spaces in offices, malls, and commercial areas




# Landscape

The most comprehensive range of high-quality products for landscape and outdoor lighting



# Smart Lights

The world is getting smarter and so are the Jaquar Lighting Products.



# Home Lights

Cutting-edge, energy-efficient LED lighting solutions for an array of home needs and requirements

# Façade Lighting

Façade lighting of our buildings is essential in creating aesthetically pleasing urban environments. It can be called architecture's fourth dimension. Buildings nowadays need to be iconic landmarks and distinct in the way they present themselves both in day and night. Carefully designed night lighting on the façades that respects the building's architecture, context while controlling light trespass are quite important in making an image that is enjoyed by all.

# Content

Wallwashers 02	26
Flood Lights 03	30
Linear Lights 03	38
Dot Lights 04	42
Linear Flex 04	46
Spot Projectors 05	50
Window Lights 05	54
Linear Inground Lights 00	60
Ground Burials 00	64
Flexi Wallwashers 00	68
Guardrail Lights 07	72
Trunking Lights 0	76
Under Water Lights 08	80



Warranty: 3 / 5 year

\*As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in detail from data given here.



# Wallwashers


Introducing a wide range of high performance Linear Wallwashers designed to highlight key architectural features of buildings or projects. Offering highly customizable optics and color temperatures, Jaquar provides best in class solutions for various types of applications, suited for both Wallwashing or Wall Grazing. These are fully compatible with advanced protocols such as DMX512, RDM & DALI.



### JQL-WWL024W

#### Features

- Unobtrusive appearance design
- Strong aviation aluminium housing
- Structured design with thermoelectric separation integrated
- Definitive and impact-resistant toughened glass
- · Seamless splicing of light, with optical dark-free zone design
- Varied options of visually comfortable and precise optical lens
- Meets international standards DMX512 protocol



#### SPECIFICATIONS

Power Consumption 24 W Luminous Flux 1920 Lm @4000 K Color Temperature 2700 K / 3000 K / 4000 K / 5000 K / 5700 K / 6500 K / RGB / RGBW Beam Angle (50% Imax) 17° / 23° / 33° / 46° / 15 x 27° / 21 x 53° / 25 x 80° Input Voltage DC24 V Protection Class IEC Ш Control DMX / RDM / DALI / Remote / On-Off Power Factor ≥0.95 Extruded aluminum 6063 Housing Cover Toughened glass W 1000 / W 28 x H 61 Dimensions IP66 / IP67 IP Rating IK Rating IK08 Mounting Adjustable bracket -35 °C ~ 60 °C (-31 °F ~ 140 °F) **Operating Temperature** THD <10% Lifespan >50,000 Hrs (Ta=35 °C @L70) BIS / CE / RoHS Certificate



### JQL-WWL036W

#### Features

- Unobtrusive appearance design
- Strong aviation aluminium housing
- Structured design with thermoelectric separation integrated
- Definitive and impact-resistant toughened glass
- Seamless splicing of light, with Optical dark-free zone design
- · Varied options of visually comfortable and precise optical lens
- Meets International standards DMX512 protocol

1000

### SPECIFICATIONS


Beam Angle (50% Imax) $12^{\circ} / 17^{\circ} / 30^{\circ} / 45^{\circ} / 60^{\circ} / 80^{\circ} / 12 \times 20^{\circ} / 12 \times 45^{\circ}$ Input VoltageAC220 V / DC24 VProtection Class IECIIIControlDMX / RDM / DALI / Remote / On-OffPower Factor $\geq 0.95$ HousingExtruded aluminum 6063CoverToughened glassDimensionsW 1000 / W 43 x H 62IP RatingIP66 / IP67IK RatingK08MountingAdjustable bracketOperating Temperature $-35 ^{\circ}$ C ~ 60 °C (-31 °F ~ 140 °F)THD<10%Lifespan>50,000 Hrs (Ta=35 °C @L70)CertificateBIS / CE / RoHS	Power Consumption Luminous Flux Color Temperature	36 W 2700 Lm @4000 K 2700 K / 3000 K / 4000 K / 5000 K / 5700 K / 6500 K / BGB / BGBW
ControlDMX / RDM / DALI / Remote / On-OffPower Factor $\geq 0.95$ HousingExtruded aluminum 6063CoverToughened glassDimensionsW 1000 / W 43 x H 62IP RatingIP66 / IP67IK RatingK08MountingAdjustable bracketOperating Temperature-35 °C ~ 60 °C (-31 °F ~ 140 °F)THD<10%	0 ( )	12° / 17° / 30° / 45° / 60° / 80° / 12 x 20° / 12 x 45°
Power Factor $\geq 0.95$ HousingExtruded aluminum 6063CoverToughened glassDimensionsW 1000 / W 43 x H 62IP RatingIP66 / IP67IK RatingIK08MountingAdjustable bracketOperating Temperature-35 °C ~ 60 °C (-31 °F ~ 140 °F)THD<10%	Protection Class IEC	III
HousingExtruded aluminum 6063CoverToughened glassDimensionsW 1000 / W 43 x H 62IP RatingIP66 / IP67IK RatingIK08MountingAdjustable bracketOperating Temperature-35 °C ~ 60 °C (-31 °F ~ 140 °F)THD<10%	Control	DMX / RDM / DALI / Remote / On-Off
CoverToughened glassDimensionsW 1000 / W 43 x H 62IP RatingIP66 / IP67IK RatingIK08MountingAdjustable bracketOperating Temperature-35 °C ~ 60 °C (-31 °F ~ 140 °F)THD<10%	Power Factor	≥0.95
DimensionsW 1000 / W 43 x H 62IP RatingIP66 / IP67IK RatingIK08MountingAdjustable bracketOperating Temperature-35 °C ~ 60 °C (-31 °F ~ 140 °F)THD<10%	Housing	Extruded aluminum 6063
IP RatingIP66 / IP67IK RatingIK08MountingAdjustable bracketOperating Temperature-35 °C ~ 60 °C (-31 °F ~ 140 °F)THD<10%	Cover	Toughened glass
IK RatingIK08MountingAdjustable bracketOperating Temperature-35 °C ~ 60 °C (-31 °F ~ 140 °F)THD<10%	Dimensions	W 1000 / W 43 x H 62
MountingAdjustable bracketOperating Temperature-35 °C ~ 60 °C (-31 °F ~ 140 °F)THD<10%	IP Rating	IP66 / IP67
Operating Temperature         -35 °C ~ 60 °C (-31 °F ~ 140 °F)           THD         <10%	IK Rating	IK08
THD         <10%	Mounting	Adjustable bracket
Lifespan >50,000 Hrs (Ta=35 °C @L70)	Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
	THD	<10%
Certificate BIS / CE / RoHS	Lifespan	>50,000 Hrs (Ta=35 °C @L70)
	Certificate	BIS / CE / RoHS



### JQL-WWL048W

#### Features

- Unobtrusive appearance design
- Strong aviation aluminium housing
- Structured design with thermoelectric separation integrated
- Definitive and impact-resistant toughened glass
- Seamless splicing of light, with Optical dark-free zone design
- Varied options of visually comfortable and precise optical lens
- Meets International standards DMX512 protocol



#### SPECIFICATIONS


Power Consumption Luminous Flux	48 W 3840 Lm @4000 K
Color Temperature	2700 K / 3000 K / 4000 K / 5000 K / 5700 K / 6500 K / RGB / RGBW
Beam Angle (50% Imax)	10° / 15° / 30° / 45° / 60° / 80° / 12 x 20° / 12 x 45°
Input Voltage	AC220 V / DC24 V
Protection Class IEC	
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Housing	Extruded aluminum 6063
Cover	Toughened glass
Dimensions	W 1000 / W 60 / W 50 x H 85
IP Rating	IP66 / IP67
IK Rating	IK08
Mounting	Adjustable bracket
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS



### JQL-WWL072W


#### Features

- Unobtrusive appearance design
- Strong aviation aluminium housing
- Structured design with thermoelectric separation integrated
- Definitive and impact-resistant toughened glass
- Seamless splicing of light, with Optical dark-free zone design
- Varied options of visually comfortable and precise optical lens
- Meets International standards DMX512 protocol



#### **SPECIFICATIONS**

Power Consumption Luminous Flux	72 W 5184 Lm @4000 K
Color Temperature	2700 K / 3000 K / 4000 K / 5000 K / 5700 K /
	6500 K / RGB / RGBW
Beam Angle (50% Imax)	10° / 15° / 30° / 45° / 60° / 80° / 12 x 20° / 12 x 45°
Input Voltage	AC100-240 V 50 / 60Hz
Protection Class IEC	1
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Housing	Extruded aluminum 6063
Cover	Toughened glass
Dimensions	W 1000 / W 60 / W 42 x H 56
IP Rating	IP66 / IP67
IK Rating	IK08
Mounting	Adjustable bracket
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS



Jaquar Flood Lights are perfect for creating varied effects such as flood lighting effect, grazing, decorative lighting and more. They deliver exceptionally high lumen output and color consistency. They provide the best solution in the industry to transform medium and large architectural structures into landmarks. Offering highly customizable optics from ultra narrow beam optics to ultra wide beam and variety of color temperatures, Jaquar flood lights set a new benchmark for the category. They are customised for various applications and can be controlled via either DMX, RDM or DALI depending on project requirements.



### JQL-FL003W

#### Features

- Unobtrusive appearance design
- Strong die cast aluminium housing
- Definitive and impact-resistant toughened glass
- Anti-glare optical design
- Varied options of comfortable and precise optical lens
- Performance oriented electronic design and dependable heat dissipation







#### SPECIFICATIONS

Power Consumption Luminous Flux Color Temperature Beam Angle (50% Imax) Input Voltage Protection Class IEC Control Power Factor Housing Cover Dimensions IP Rating IK Rating Mounting **Operating Temperature** THD Lifespan Certificate

3 W 210 Lm @4000 K 2700 K / 3000 K / 4000 K / 5000 K / 5700 K / 6500 K 8° / 15° / 30° / 40° / 60° / 80° / 30 x 60° DC24 V DMX / RDM / DALI / Remote / On-Off ≥0.95 Die cast aluminum ADC12 Toughened glass W 66 x H 44 / W 87.2 x H 51 IP66 / IP67 IK08 Adjustable bracket -35 °C ~ 60 °C (-31 °F ~ 140 °F) <10% >50,000 Hrs (Ta=35 °C @L70) BIS / CE / RoHS



### JQL-FL006W

#### Features

- Unobtrusive appearance design
- Strong die cast aluminium housing
- Definitive and impact-resistant toughened glass
- Anti-glare optical design
- Varied options of comfortable and precise optical lens
- Performance oriented electronic design and dependable heat dissipation
- Smart step-less dimming technology adopted

F			-	
4	00	5	h	4
4	S.	~	μ	ŭ





#### SPECIFICATIONS

Power Consumption	6 W
Luminous Flux	425 Lm @4000 K
Color Temperature	2700 K / 3000 K / 4000 K / 5000 K / 5700 K /
	6500 K / RGB / RGBW
Beam Angle (50% Imax)	8° / 15° / 30° / 40° / 60° / 80° / 30 x 60°
Input Voltage	DC24 V
Protection Class IEC	III
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Housing	Die cast aluminum ADC12
Cover	Toughened glass
Dimensions	W 90 x H 55.5 / W 111.6 x H 73.5
IP Rating	IP66 / IP67
IK Rating	IK08
Mounting	Surface mount with adjustable bracket
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS



### JQL-FL012W

#### Features

- Unobtrusive appearance design
- Strong die cast aluminium housing
- Definitive and impact-resistant toughened glass
- Anti-glare optical design
- Varied options of comfortable and precise optical lens
- Performance oriented electronic design and dependable heat dissipation
- Smart step-less dimming technology adopted

113 137



ŝ

#### SPECIFICATIONS

Power Consumption	12 W
Luminous Flux	870 Lm @4000 K
Color Temperature	2700 K / 3000 K / 4000 K / 5000 K / 5700 K /
	6500 K / RGB / RGBW
Beam Angle (50% Imax)	8° / 15° / 30° / 40° / 60° / 80° / 30 x 60°
Input Voltage	DC24 V
Protection Class IEC	
Control	DMX / RDM/DALI / Remote / On-Off
Power Factor	≥0.95
Housing	Die cast aluminum ADC12
Cover	Toughened glass
Dimensions	W 113 x H 70 / W 137 x H 85
IP Rating	IP66 / IP67
IK Rating	IK08
Mounting	Adjustable bracket
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS




### JQL-FL024W

#### Features

- Unobtrusive appearance design
- Strong die cast aluminium housing
- Definitive and impact-resistant toughened glass
- Anti-glare optical design
- Varied options of comfortable and precise optical lens
- Performance oriented electronic design and dependable heat dissipation
- Smart step-less dimming technology adopted

All dimensions are in mm









#### SPECIFICATIONS

Power Consumption	24 W
Luminous Flux	1800 Lm @4000 K
Color Temperature	2700 K / 3000 K / 4000 K / 5000 K / 5700 K /
	6500 K / RGB / RGBW
Beam Angle (50% Imax)	8° / 15° / 30° / 40° / 60° / 80° / 30 x 60°
Input Voltage	DC24 V
Protection Class IEC	III
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Housing	Die cast aluminum ADC12
Cover	Toughened glass
Dimensions	W 145 x H 90 / W 166.5 x H 109
IP Rating	IP66 / IP67
IK Rating	IK08
Mounting	Adjustable bracket
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS




### JQL-FL036W

#### Features

- Unobtrusive appearance design
- Strong die cast aluminium housing
- Definitive and impact-resistant toughened glass
- Anti-glare optical design
- Varied options of comfortable and precise optical lens
- Performance oriented electronic design and dependable heat dissipation
- · Smart step-less dimming technology adopted







#### **SPECIFICATIONS**

**Power Consumption** Luminous Flux Color Temperature

Input Voltage Protection Class IEC Control Power Factor Housing Cover Dimensions IP Rating IK Rating Mounting Operating Temperature THD Lifespan Certificate

36 W 2740 Lm @4000 K 2700 K / 3000 K / 4000 K / 5000 K / 5700 K / 6500 K / RGB / RGBW Beam Angle (50% Imax) 8° / 15° / 30° / 40° / 60° / 80° / 30 x 60° DC24 V / AC100-240 V 50 / 60 Hz 111 / 1 DMX / RDM / DALI / Remote / On-Off ≥0.95 Die cast aluminum ADC12 Toughened glass W 181.5 x H 110 / W 201 x H 124.7 IP66 / IP67 IK08 Surface mount with adjustable bracket -35 °C ~ 60 °C (-31 °F ~ 140 °F) <10% >50,000 Hrs (Ta=35 °C @L70) BIS / CE / RoHS



### JQL-FL048W

#### Features

- Unobtrusive appearance design
- Strong die cast aluminium housing
- Definitive and impact-resistant toughened glass
- Anti-glare optical design
- Varied options of comfortable and precise optical lens
- Performance oriented electronic design and dependable heat dissipation
- Smart step-less dimming technology adopted

			1
888888	. L.	2	
000000	- H I	(1)	1





#### SPECIFICATIONS

Power Consumption Luminous Flux Color Temperature	48 W 3600 Lm @4000 K 2700 K / 3000 K / 4000 K / 5000 K / 5700 K / 6500 K / RGB / RGBW
Beam Angle (50% Imax)	8° / 15° / 30° / 40° / 60° / 80° / 30 x 60°
Input Voltage	AC220 V / DC24 V / DC36 V / AC100-240 V 50 / 60 Hz
Protection Class IEC	III / I
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Housing	Die cast aluminum ADC12
Cover	Toughened glass
Dimensions	W 215 x H 130 / W 253.5 x H 143
IP Rating	IP66 / IP67
IK Rating	IK08
Mounting	Adjustable bracket
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS

All dimensions are in mm 034 COMPLETE LED LIGHTING SOLUTIONS



JQL-FL072W

#### Features

- Unobtrusive appearance design
- Strong aviation aluminium housing
- Structured design with thermoelectric separation integrated
- Definitive and impact-resistant toughened glass
- Anti-glare optical design
- Varied options of comfortable and precise optical lens
- Performance oriented electronic design and dependable heat dissipation
- Smart step-less dimming technology adopted
- High-precision vents for greater performance, increased durability, and higher reliability








#### SPECIFICATIONS

Power Consumption	72 W
Luminous Flux	5760 Lm @4000 K
Color Temperature	2700 K / 3000 K / 4000 K / 5000 K / 5700 K /
	6500 K / RGB / RGBW
Beam Angle (50% Imax)	8° / 15° / 30° / 40° / 60° / 80° / 30 x 60°
Input Voltage	AC100-240 V 50 / 60Hz
Protection Class IEC	1
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Housing	Extruded aluminum 6063
Cover	Toughened glass
Dimensions	W 274.7 x H 200 / W 311.6 x H 225
IP Rating	IP66 / IP67
IK Rating	IK08
Mounting	Adjustable bracket
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS



#### Features

- Unobtrusive appearance design
- Strong aviation aluminium housing
- Structured design with thermoelectric separation integrated
- Definitive and impact-resistant toughened glass
- Anti-glare optical design
- Varied options of comfortable and precise optical lens
- Performance oriented electronic design and dependable heat dissipation
- Smart step-less dimming technology adopted
- High-precision vents for greater performance, increased durability, and higher reliability



#### SPECIFICATIONS

Power Consumption Luminous Flux Color Temperature	144 W 11808 Lm @4000 K 2700 K / 3000 K / 4000 K / 5000 K / 5700 K /
Beam Angle (50% Imax)	6500 K / RGB / RGBW 8° / 15° / 30° / 40° / 60° / 80° / 30 x 60°
Input Voltage	AC100-240 V 50 / 60Hz
Protection Class IEC	
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Housing	Extruded aluminum 6063
Cover	Toughened glass
Dimensions	W 554.6 x H 225
IP Rating	IP66 / IP67
IK Rating	IK08
Mounting	Adjustable bracket
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS



JQL-FL216W

Unobtrusive appearance design

separation integrated

• Anti-glare optical design

dependable heat dissipation

optical lens

• Strong aviation aluminium housing

• Structured design with thermoelectric

· Definitive and impact-resistant toughened glass

• Varied options of comfortable and precise

• Performance oriented electronic design and

• Smart step-less dimming technology adopted

• High-precision vents for greater performance,

increased durability, and higher reliability

Features



#### SPECIFICATIONS

Power Consumption Luminous Flux Color Temperature

Beam Angle Input Voltage Protection Class IEC Control Power Factor Housing Cover Dimensions IP Rating IK Rating Mounting Operating Temperature THD Lifespan Certificate

216 W 17496 Lm @4000 K 2700 K / 3000 K / 4000 K / 5000 K / 5700 K / 6500 K / RGB / RGBW (50% Imax) 8° / 15° / 30° / 40° / 60° / 80° / 30 x 60° AC100-240 V 50 / 60 Hz DMX / RDM / DALI / Remote / On-Off ≥0.95 Extruded aluminum 6063 Toughened glass W 761 x H 200 / W 797.6 x H 225 IP66 / IP67 IK08 Adjustable bracket -35 °C ~ 60 °C (-31 °F ~ 140 °F) <10% >50,000 Hrs (Ta=35 °C @L70) BIS / CE / RoHS



### JQL-FL288W

#### Features

- Unobtrusive appearance design
- · Strong aviation aluminium housing
- Structured design with thermoelectric separation integrated
- Definitive and impact-resistant toughened glass
- Anti-glare optical design
- Varied options of comfortable and precise optical lens
- Performance oriented electronic design and dependable heat dissipation
- Smart step-less dimming technology adopted
- · High-precision vents for greater performance, increased durability, and higher reliability

554.6 518 109.5 365.8 29.5

#### SPECIFICATIONS

Power Consumption Luminous Flux	288 W 23616 Lm @4000 K
Color Temperature	2700 K / 3000 K / 4000 K / 5000 K / 5700 K /
	6500 K / RGB / RGBW
Beam Angle (50% Imax)	8° / 15° / 30° / 40° / 60° / 80° / 30 x 60°
Input Voltage	AC100-240 V 50 / 60 Hz
Protection Class IEC	I
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Housing	Extruded aluminum 6063
Cover	Toughened glass
Dimensions	W 518 x H 429.5 / W 554.6 x H 365.8
IP Rating	IP66 / IP67
IK Rating	IK08
Mounting	Adjustable bracket
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS


# Flood Lights



JQL-FL432W

#### Features

- Unobtrusive appearance design
- Strong aviation aluminium housing
- Structured design with thermoelectric separation integrated
- Definitive and impact-resistant toughened glass
- Anti-glare optical design
- Varied options of comfortable and precise optical lens
- Performance oriented electronic design and dependable heat dissipation
- Smart step-less dimming technology adopted
- High-precision vents for greater performance, increased durability, and higher reliability







# SPECIFICATIONS

Power Consumption	432 W
Luminous Flux	35424 Lm @4000 K
Color Temperature	2700 K / 3000 K / 4000 K / 5000 K / 5700 K /
	6500 K / RGB / RGBW
Beam Angle (50% Imax)	8° / 15° / 30° / 40° / 60° / 80° / 30 x 60°
Input Voltage	AC100-240 V 50 / 60Hz
Protection Class IEC	I
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Housing	Extruded aluminum 6063
Cover	Toughened glass
Dimensions	W 761 x H 429.5 / W 797.6 x H 365.8
IP Rating	IP66 / IP67
IK Rating	IK08
Mounting	Adjustable bracket
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS




# JQL-FL648W

#### Features

- Unobtrusive appearance design
- Strong aviation aluminium housing
- Structured design with thermoelectric separation integrated
- Definitive and impact-resistant toughened glass
- Anti-glare optical design
- Varied options of comfortable and precise optical lens
- Performance oriented electronic design and dependable heat dissipation
- Smart step-less dimming technology adopted
- High-precision vents for greater performance, increased durability, and higher reliability

11010400010



#### SPECIFICATIONS

Power Consumption	648 W
Luminous Flux	53784 Lm @4000 K
Color Temperature	2700 K / 3000 K / 4000 K / 5000 K / 5700 K /
	6500 K / RGB / RGBW
Beam Angle (50% Imax)	8° / 15° / 30° / 40° / 60° / 80° / 30 x 60°
Input Voltage	AC100-240 V 50 / 60 Hz
Protection Class IEC	1
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Housing	Extruded aluminum 6063
Cover	Toughened glass
Dimensions	W 761 x H 658.5 / W 797.6 x H 505.8
IP Rating	IP66 / IP67
IK Rating	IK08
Mounting	Adjustable bracket
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS



# Linear Lights

Linear Lights are especially designed direct view luminaires which come with anti-glare technology. These luminaires allow us to introduce a substantial wow factor within projects when effectively utilized through the application of Media Façade. They can help us create various dynamic effects, allowing us to bring a structure to life and help achieve the designer's or architect's vision for the project. They come in mono color, tunable white, RGB & RGBW solutions.



# JQL-LRLF012W

#### Features

- Unobtrusive appearance design
- Outside self-cleaning design ensures high reliability and performance
- Strong aviation aluminium housing
- PC diffuser for Weather and UV resistance
- Seamless splicing of light, with optical dark-free zone design
- Meets international standards DMX512 protocol

1000.0

# **SPECIFICATIONS**

Power Consumption	12 W
Luminous Flux	300 Lm @4000 K
Color Temperature	2700 K / 3000 K / 4000 K / 5000 K / 5700 K /
	6500 K / RGB / RGBW
Beam Angle (50% Imax)	130°
Input Voltage	DC24 V
Protection Class IEC	111
Control	DMX / RDM / DALI / Remote / On-Off
Pixel	8
Power Factor	≥0.95
Housing	Extruded aluminum 6063
Dimensions	W 1000 / W 18 x H 42
Diffuser	High strength optical PC
IP Rating	IP65 / IP66 / IP67 / IP68
IK Rating	IK06 / IK07
Mounting	Adjustable bracket
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS



# JQL-LRLR012W

#### Features

- Unobtrusive appearance design
- Outside self-cleaning design ensures high reliability and performance
- Strong aviation aluminium housing
- PC diffuser for Weather and UV resistance
- Seamless splicing of light, with optical dark-free zone design
- Meets international standards DMX512 protocol



# SPECIFICATIONS

Power Consumption	12 W
Luminous Flux	840 Lm @4000 K
Color Temperature	2700 K / 3000 K / 4000 K / 5000 K / 5700 K /
	6500 K / RGB / RGBW
Beam Angle (50% Imax)	150°
Input Voltage	DC24 V
Protection Class IEC	III
Control	DMX / RDM / DALI / Remote / On-Off
Pixel	8
Power Factor	≥0.95
Housing	Extruded aluminum 6063
Dimensions	W 1000 / W 25 x H 50.5 / W 28 x H 44.5
Diffuser	High strength optical PMMA
IP Rating	IP65 / IP66 / IP67 / IP68
IK Rating	IK06 / IK07
Mounting	Adjustable bracket
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS

All dimensions are in mm

# Linear Lights



# JQL-LRLC012W

#### Features

- Unobtrusive appearance design
- Outside self-cleaning design ensures high reliability and performance
- Strong aviation aluminium housing
- PC diffuser for Weather and UV resistance
- Seamless splicing of light, with optical dark-free zone design
- Meets international standards DMX512 protocol

1000 -14 [.\_\_\_\_\_\_\_]



#### **SPECIFICATIONS**

Luminous Flux Color Temperature Beam Angle (50% Imax) Input Voltage Protection Class IEC Control Pixel Power Factor Housing Dimensions Diffuser **IP** Rating IK Rating Mounting Operating Temperature THD Lifespan Certificate

**Power Consumption** 12 W 1020 Lm @4000 K 2700 K / 3000 K / 4000 K / 5000 K / 5700 K / 6500 K / RGB / RGBW 110° DC24 V Ш DMX / RDM / DALI / Remote / On-Off 8 ≥0.95 Extruded aluminum 6063 W 1000 / W 25 x H 39.3 / W 28 x H 33.3 High strength optical PMMA IP65 / IP66 / IP67 / IP68 IK06 / IK07 Adjustable bracket -35 °C ~ 60 °C (-31 °F ~ 140 °F) <10% >50,000 Hrs (Ta=35 °C @L70) BIS / CE / RoHS



# JQL-LRLFX12W

#### Features


- Unobtrusive appearance design
- Outside self-cleaning design ensures high reliability and performance
- · Strong aviation aluminium housing
- PC diffuser for Weather and UV resistance
- · Seamless splicing of light, with optical dark-free zone design
- Meets international standards DMX512 protocol



### **SPECIFICATIONS**

1000mm

Power Consumption	12 W
Luminous Flux	870 Lm @4000 K
Color Temperature	2700 K / 3000 K / 4000 K / 5000 K / 5700 K /
	6500 K / RGB / RGBW
Beam Angle (50% Imax)	150°
Input Voltage	DC24 V
Protection Class IEC	III
Control	DMX / RDM / DALI / Remote / On-Off
Pixel	8
Power Factor	≥0.95
Housing	Extruded aluminum 6063
Dimensions	W 1000 / W 28.5 x H 42.05
Diffuser	High strength optical PC
IP Rating	IP65 / IP66 / IP67 / IP68
IK Rating	IK06 / IK07
Mounting	Adjustable bracket
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS



# Dot Lights


Introducing the most unique and advanced direct-view luminaries which are highly flexible and can fulfill various applications - dynamic lighting, displaying messages and creating multiple advanced patterns and effects as desired to create a stunning LED light show. They are easy to use and install and maintenance free. They are fully compatible with advance control systems such as DMX512, RDM & DALI and are customised for the application.



# JQL-DTL03W

#### Features

- Unobtrusive appearance design
- Strong aviation aluminium housing
- Waterproof structure an integral element
- Optional milky or transparent diffuser
- PC diffuser for Weather and UV resistance
- Meets international standards DMX512 protocol







## SPECIFICATIONS


Power Consumption Luminous Flux Color Temperature	3 W 200 Lm @4000 K 2700 K / 3000 K / 4000 K / 5000 K / 5700 K / 6500 K / RGB / RGBW
Beam Angle (50% Imax)	110° / 160°
Input Voltage	DC24 V
Protection Class IEC	III
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Housing	Die cast aluminum ADC12
Dimensions	ø52 x H 90 / W 80 x H 50 / W 70 x H 50
Diffuser	High strength optical PC
IP Rating	IP65 / IP66 / IP67 / IP68
IK Rating	IK06 / IK07
Mounting	Side bracket
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS



# JQL-DTL05W

#### Features

- Unobtrusive appearance design
- Strong aviation aluminium housing
- Waterproof structure an integral element
- Optional milky or transparent diffuser
- PC diffuser for Weather and UV resistance
- Meets international standards DMX512 protocol




#### SPECIFICATIONS

Power Consumption	5 W
Luminous Flux	350 Lm @4000 K
Color Temperature	2700 K / 3000 K / 4000 K / 5000 K / 5700 K /
	6500 K / RGB / RGBW
Beam Angle (50% Imax)	110° / 160°
Input Voltage	DC24 V
Protection Class IEC	III
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Housing	Die cast aluminum ADC12
Dimensions	ø71.6 x H 112 / W 103 x H 73.2 / W 90 x H 73.2
Diffuser	High strength optical PC
IP Rating	IP65 / IP66 / IP67 / IP68
IK Rating	IK06 / IK07
Mounting	Side bracket
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS

All dimensions are in mm





# Linear Flex

Jaquar Linear Flex is a state-of-the-art luminaires solution that provides maximum flexibility. It is especially designed to overcome the challenges for the uneven surfaces of the building and is used for various lighting concepts such as Contouring and Media Façade. It provides a uniform dot-free and anti-glare direct view effect. The Linear flex solution is available in multiple CCT options like mono, tunable white, RGB and RGBW and can be controlled via DMX, DALI, Triac dimming or standard switching.





JQL-LFLXS008W

• High quality circuit design for stable and reliable

• With cut mark on the back to satisfy different

• IP67 perfect for indoor and outdoor use

• Excellent flexibility for side bending and easy shape

• Excellent weather resistance and corrosion resistance

Features

performance

requirements

• Dimmable

# Light Surface

2



# SPECIFICATIONS

Power Consumption Luminous Flux Color Temperature Beam Angle Input Voltage Control Dimensions Power Factor Housing IP Rating **IK Rating** Mounting **Operating Temperature** THD Lifespan Certificate

8 W 500 Lm / M at 4000 K 3000 K / 4000 K / 6500 K / RGB / RGBW 114° AC100-240 V / DC24 V DMX / RDM / DALI / Remote / On-Off W 16 x H 17 x L (Length can be customised) ≥0.95 Silicon IP68 IK07 Brackets / fixed profile / adjustable profile -30 °C ~ +45 °C <10% >50,000 Hrs (Ta=30 °C @L70) BIS / CE / RoHS



# JQL-LFLXE012W

#### Features

Color options: single color

- Design: superior design with exquisite craftsmanship ensure stable and reliable performance
- Flexibility: top bending, min. bend diameter 60 mm
- IP grade: silicone extrusion, injection molded cap, IP68 protection. Glue process end caps, IP67 protection
- Customisation: multiple spec options, can be customised upon requirements

10023[394.60] 10000[393.70] 50[1.96]


# SPECIFICATIONS

**Power Consumption** 12 W Luminous Flux 500 Lm / M at 4000 K 3000 K / 4000 K / 6500 K Color Temperature Beam Angle 110° Input Voltage DC24 V Control On-Off ≥0.95 Power Factor Housing Stainless steel body Cover Tempered glass W 12 x H 12 Dimensions Net Weight 0.6Kg IP Rating IP68 IK Rating IK06 Brackets / fixed profile / adjustable profile Mounting **Operating Temperature** -30 °C ~ +45 °C THD <10% >50,000 Hrs (Ta=30 °C @L70) Lifespan Certificate BIS / CE / RoHS





JQL-LFLEXS013W



## SPECIFICATIONS

#### Features

- · Color options: single color, tunable white and RGB
- Design: superior design with exquisite craftsmanship ensure stable and reliable performance
- Flexibility: top bending, min. bend diameter 60 mm
- IP grade: silicone extrusion, injection molded cap, IP68 protection. Glue process end caps, IP67 protection
- Customisation: multiple spec options, can be customised upon requirements


Power Consumption	13 W
Luminous Flux	500 Lm / M at 4000 K
Color Temperature	3000 K / 4000 K / 6500 K / RGB / RGBW
Beam Angle	113°
Input Voltage	DC24 V
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Housing	Silicon
Dimensions	W 12 x H 12
IP Rating	IP68
IK Rating	IK07
Mounting	Brackets / fixed profile / adjustable profile
Operating Temperature	-30 °C ~ +45 °C
THD	<10%
Lifespan	>50,000 Hrs (Ta=30 °C @L70)
Certificate	BIS / CE / RoHS



# JQL-LFLXHP018W

#### Features

- High quality circuit design for stable and reliable performance
- Excellent flexibility for side bending and easy shape
- With cut mark on the back to satisfy different requirements
- IP67 perfect for indoor and outdoor use
- Excellent weather resistance and corrosion resistance
- Dimmable




18 W

# **SPECIFICATIONS**

Power Consumption Luminous Flux Color Temperature Beam Angle Input Voltage Control Dimensions Power Factor Housing IP Rating IK Rating Mounting **Operating Temperature** THD Lifespan Certificate

1100 Lm / M at 4000 K 3000 K / 4000 K / 6500 K / RGB / RGBW 114° AC100-240 V / DC24 V DMX / RDM / DALI / Remote / On-Off W 16 x H 17 x L (Length can be customised) ≥0.95 Silicon IP68 IK07 Brackets / fixed profile / adjustable profile -30 °C ~ +45 °C <10% >50,000 Hrs (Ta=30 °C @L70) BIS / CE / RoHS



# Spot Projectors


Jaquar spot projectors provide best in class optics from ultra narrow beam to wide beam. They can be surface mounted or spike mounted to meet various applications. The heavy-duty die cast aluminium housing ensures high corrosion resistance. They are also fully compatible with advance protocols such as DMX512, RDM & DALI.



# JQL-SPLA012W

#### Features

- Structure: tough aluminium design, simple, elegant, optical UV resistance cover and lens, The color of the product housing can be customised according to requirements
- It's easy to install by fixing lamp base, 180° rotatable base and up and down 90° for all directions projection. It can be used in many kinds of outdoor engineering applications



# SPECIFICATIONS

Power Consumption Luminous Flux Color Temperature Beam Angle Input Voltage Control Power Factor Housing Cover Dimensions **IP** Rating IK Rating Mounting Operating Temperature THD Lifespan Certificate


12 W 60 Lm / W at 3000 K 2200 K / 3000 K / 4000 K / 5700 K / RGB / RGBW 6° / 10° / 15° / 25° / 30° / 45° / 60° / 90° DC24 V / AC100-277 V DMX / RDM / DALI / Remote / On-Off >0.95 Aluminium body PMMA Lens Ø94 x 100 x 177 IP65 IK07 Surface Mount / Spike -30 °C ~ +45 °C <10% >50,000 Hrs (Ta=30 °C @L70) BIS / CE / RoHS



# JQL-SPLA027W

#### Features

- Structure: tough aluminium design, simple, elegant, optical UV resistance cover and lens, The color of the product housing can be customised according to requirements
- It's easy to install by fixing lamp base, 180° rotatable base and up and down 90° for all directions projection. It can be used in many kinds of outdoor engineering applications



## SPECIFICATIONS

Power Consumption Luminous Flux Color Temperature Beam Angle Input Voltage Control Power Factor Housing Cover Dimensions IP Rating **IK Rating** Mounting Operating Temperature THD Lifespan Certificate

## 27 W 60 Lm / W at 3000 K 2200 K / 3000 K / 4000 K / 5700 K / RGB / RGBW 6° / 10° / 15° / 25° / 30° / 45° / 60° / 90° DC24 V / AC100-277 V DMX / RDM / DALI / Remote / On-Off ≥0.95 Aluminium body PMMA Lens Ø115 x 100 x 193 IP65 IK07 Surface Mount / Spike -30 °C ~ +45 °C <10% >50,000 Hrs (Ta=30 °C @L70) BIS / CE / RoHS






Jaquar introduces a specialized selection of window lights to meet various applications. They come with advance anti-glare technology which guarantees 0% light leakage inside the window and allows us to achieve the perfect desired effect. They are available with 180° and 360° beam options in a variety of color temperatures and are also fully compatible with advance protocols such as DMX512, RDM & DALI for control.



# JQL-WNDLH006W

#### Features

- Structure: sturdy construction, the die casting lamp body is designed to be tough, simple. The color of the product housing can be customised according to requirements
- Original CREE chip, high brightness
- Structural water-proof, well protect the inside electrical parts, easy maintenance
- Outdoor rubber cable, available with waterproof connector, easy for installation



#### SPECIFICATIONS

Power Consumption Luminous Flux Color Temperature Beam Angle Input Voltage Control Power Factor Housing Cover Dimensions IP Rating IK Rating Mounting **Operating Temperature** THD Lifespan Certificate

6 W 28 Lm / W at 3000 K 2700 K / 3000 K / 4000 K / R / G / B 3 x 180° DC24 V / 100-277 V DMX / RDM / DALI / Remote / On-Off >0.95 Aluminium body PMMA lens 102 x 45 x 102 IP66 IK10 Surface mount -30 °C ~ +45 °C <10% >50,000 Hrs (Ta=30 °C @L70) BIS / CE / RoHS



# JQL-WNDLF006W

### Features

- Structure: sturdy construction, the die casting lamp body is designed to be tough, simple. The color of the product housing can be customised according to requirements
- Original CREE chip, high brightness
- Structural water-proof, well protect the inside electrical parts, easy maintenance
- Outdoor rubber cable, available with waterproof connector, easy for installation

### SPECIFICATIONS

Power Consumption Luminous Flux Color Temperature Beam Angle Input Voltage Control Power Factor Housing Cover Dimensions **IP** Rating IK Rating Mounting Operating Temperature THD Lifespan Certificate

6 W 3000 K / 4000 K / 5700 K / RGB / RGBW 3x360° DC24 V / AC100-277 V DMX / RDM / DALI / Remote / On-Off ≥0.95 Die cast aluminium body PC Reflector L 133 x W 52 x H 85 IP66 IK10 Surface mount -30 °C ~ +45 °C <10% >50,000 Hrs (Ta=30 °C @L70) BIS / CE / RoHS



# JQL-WNDLF012W

#### Features


- Structure: sturdy construction, the die casting lamp body is designed to be tough, simple. The color of the product housing can be customised according to requirements
- Original CREE chip, high brightness
- Structural water-proof, well protect the inside electrical parts, easy maintenance
- Outdoor rubber cable, available with waterproof connector, easy for installation

## SPECIFICATIONS

12 W

Power Consumption Luminous Flux Color Temperature Beam Angle Input Voltage Control Power Factor Housing Cover Dimensions IP Rating IK Rating Mounting **Operating Temperature** THD Lifespan Certificate

-3000 K / 4000 K / 5700 K / RGB / RGBW 5x180° DC24 V / AC100-277 V DMX / RDM / DALI / Remote / On-Off ≥0.95 Die cast aluminium body PC Reflector L 121 x W 40 x H 76 IP66 IK10 Surface mount -30 °C ~ +45 °C <10% >50,000 Hrs (Ta=30 °C @L70) BIS / CE / RoHS



# JQL-WNDLF016W

#### Features

- Structure: sturdy construction, the die casting lamp body is designed to be tough, simple.
   The color of the product housing can be customised according to requirements
- Original CREE chip, high brightness
- Structural water-proof, well protect the inside electrical parts, easy maintenance
- Outdoor rubber cable, available with waterproof connector, easy for installation

All dimensions are in mm



## SPECIFICATIONS

Power Consumption Luminous Flux Color Temperature Beam Angle Input Voltage Control Power Factor Housing Cover Dimensions IP Rating IK Rating Mounting Operating Temperature THD Lifespan Certificate

16 W 342 Lm (at full on mode) 3000 K / 4000 K / 5700 K / R / G / B 3 x 180° DC24 V / 100-277 V DMX / RDM / DALI / Remote / On-Off ≥0.95 Die cast aluminium body PC Reflector L 152 x W 65 x H 95 IP66 IK10 Surface mount -30 °C ~ +45 °C <10% >50,000 Hrs (Ta=30 °C @L70) BIS / CE / RoHS



# JQL-WNDL020W

#### Features

- Unobtrusive appearance design
- Strong aviation aluminium housing
- Structured design with thermoelectric separation integrated
- Definitive and impact-resistant toughened glass
- Nano-scale optical materials adopted for accurate lighting
- Varied options of efficient and precise optical lens
- Meets international standards DMX512 protocol
- High-precision vents for greater performance, increased durability, and higher reliability





### SPECIFICATIONS

Power Consumption	20 W
Luminous Flux	800 Lm @4000 K
Color Temperature	2700 K / 3000 K / 4000 K / 5000 K / 5700 K /
	6500 K / RGB / RGBW
Beam Angle (50% Imax)	10 x 120°
Input Voltage	DC24 V
Protection Class IEC	
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Housing	Extruded aluminum 6063
Cover	Toughened glass
Dimensions	W 249.0 / W 60 x H 56 / W 42 x H 35.5
IP Rating	IP66
IK Rating	IK06
Mounting	Surface mount
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS





# Linear Inground Lights

Building on the legacy of wallwashers, Jaquar has launched the linear inground series of luminaires. They can be ground recessed to completely conceal the luminaires and create a beautiful lighting illusion. A sealed and pressure tested glass cover protects the luminaires from both walkover impact and water damage. Offering highly customizable optics and color temperatures, Jaquar aims to provide best in class solutions. They are compatible with various digital lighting control protocols for flexibility in projects.



# JQL-LIGL024W

#### Features

- Recessed luminaire is suitable for a wide range of wall washing, accent, surface grazing applications in architectural, hospitality and retail environments
- Multiple customisation options to illuminate interior walls, exterior facades and unique architectural details. Drive-over 4000 Kg at max 40 Km/h Designed to last in extremely harsh environments
- Intelligent dynamic, Tunable, White grazing; DMX and DALI controllable, easy to install with the integrated universal power supply and connect via combined power and data connectors

Power Consumption	24 W
Luminous Flux	30 Lm / W at RGBW full output, 75 Lm / W at 3000 K
Color Temperature	2700 K / 3000 K / 4000 K / RGB / RGBW
Beam Angle	6° / 10° / 15° / 25° / 30° / 45° / 60° / 90° / 10 x 45° /
	10 x 60°
Input Voltage	DC24 V
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Dimensions	1003 x 50 x 92
Housing	Aluminium body
Cover	PMMA Lens
IP Rating	IP67
IK Rating	IK10
Mounting	Recessed inground
Operating Temperature	-30 °C ~ +45 °C
THD	<10%
Lifespan	>50,000 Hrs (Ta=30 °C @L70)
Certificate	BIS / CE / RoHS



# JQL-LIGL036W / JQL-LIGL048W

#### Features

- · Recessed luminaire is suitable for a wide range of wall washing, accent, surface grazing applications in architectural, hospitality and retail environments
- Multiple customisation options to illuminate interior walls, exterior facades and unique architectural details. Drive-over 4000 Kg at max 40 Km/h Designed to last in extremely harsh environments
- Intelligent dynamic, Tunable, White grazing; DMX and DALI controllable, easy to install with the integrated universal power supply and connect via combined power and data connectors

# SPECIFICATIONS

**SPECIFICATIONS** 

Power Consumption Luminous Flux Color Temperature	36 W / 48 W 30 Lm / W at RGBW full output, 75 Lm / W at 3000 K 2700 K / 3000 K / 4000 K / RGB / RGBW
Beam Angle	6° / 10° / 15° / 25° / 30° / 45° / 60° / 90° / 10 x 45° /
	10 x 60°
Input Voltage	DC24 V
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Dimensions	1000 x 90 x 48
Housing	Aluminium body
Cover	PMMA Lens
IP Rating	IP67
IK Rating	IK10
Mounting	Recessed inground
Operating Temperature	-30 °C ~ +45 °C
THD	<10%
Lifespan	>50,000 Hrs (Ta=30 °C @L70)
Certificate	BIS / CE / RoHS





# Ground Burials


Jaquar ground burials are designed to enhance architectures, they can be used in varied applications like column uplighter, tree uplighter, etc. Their glare-free design and construction ensure maximum visual comfort. A sealed and pressure tested glass cover protects the luminaires from both walkover impact and water damage. Optics provide best in class distribution from ultra narrow beam to wide beam options. They are compatible with various digital lighting control protocols for flexibility in projects.



# JQL-GBLB006W

#### Features

- Recessed luminaire is suitable for a wide range of wallwashing, accent, surface grazing applications in architectural, hospitality and retail environments
- Multiple customisation options to illuminate interior walls, exterior facades and unique architectural details. Drive-over 4000 Kg at max 40 Km/h.
   Designed to last in extremely harsh environments
- Intelligent dynamic, tunable, white grazing; DMX and DALI controllable, easy to install with the integrated universal power supply and connect via combined power and data connectors



#### SPECIFICATIONS

Power Consumption Luminous Flux Color Temperature Beam Angle Input Voltage Control Power Factor Dimensions Housing Cover IP Rating IK Rating Mounting Operating Temperature THD Lifespan Certificate


6 W 80 Lm / W at 3000 K 2700K / 3000K / 4000K / RGB / RGB 15° / 24° / 36° AC / DC12 V / 24 V DMX / RDM / DALI / Remote / On-Off >0.95 ø80 x H 95 Stainless steel Tempered class IP67 IK09 Recessed inground -30 °C ~ +45 °C <10% >50,000 Hrs (Ta=30 °C @L70) BIS / CE / RoHS





# JQL-GBLA001W / JQL-GBLA002W / JQL-GBLA003W

#### Features

- Recessed luminaire is suitable for a wide range of wallwashing, accent, surface grazing applications in architectural, hospitality and retail environments
- Multiple customisation options to illuminate interior walls, exterior facades and unique architectural details. Drive-over 4000 Kg at max 40 Km/h.
   Designed to last in extremely harsh environments
- Intelligent dynamic, tunable, white grazing; DMX and DALI controllable, easy to install with the integrated universal power supply and connect via combined power and data connectors







# SPECIFICATIONS

Power Consumption Luminous Flux Color Temperature Beam Angle Input Voltage Control Power Factor Dimensions Housing Cover IP Rating IK Rating Mounting **Operating Temperature** THD Lifespan Certificate

1W/2W/3W 60 Lm / W at 3000 K 2700 K / 3000 K / 4000 K / RGB 8° / 15° / 30 °/ 36° / 45° / 60° / 90° AC / DC12 V / 24 V DMX / RDM / DALI / Remote / On-Off ≥0.95 ø42 x H 72 / ø52 x H 82 / ø62 x H 82 Stainless steel Tempered class IP67 IK09 Recessed inground -30 °C ~ +45 °C <10% >50,000 Hrs (Ta=30 °C @L70) BIS / CE / RoHS


# **Ground Burials**



# JQL-GBLC003W / JQL-GBLC006W / JQL-GBLC009W / JQL-GBLC012W

#### Features

- · Recessed luminaire is suitable for a wide range of wallwashing, accent, surface grazing applications in architectural, hospitality and retail environments
- Multiple customisation options to illuminate interior walls, exterior facades and unique architectural details. Drive-over 4000 Kg at max 40 Km/h. Designed to last in extremely harsh environments
- Intelligent dynamic, tunable, white grazing; DMX and DALI controllable, easy to install with the integrated universal power supply and connect via combined power and data connectors



#### **SPECIFICATIONS**


Power Consumption	3 W / 6 W / 9 W / 12 W
Luminous Flux	90 Lm / W at 3000 K
Color Temperature	2700K / 3000K / 4000K / RGB / RGBW
Beam Angle	8° / 15° / 30° / 36° / 45° / 60° / 90°
Input Voltage	DC24 V / 100-277 V
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Dimensions	ø100 x H 80 / ø130 x H 85 / ø180 x H 90 /
	ø180 x H 90
Housing	Aluminium body + Stainless steel trim
Cover	Tempered class
IP Rating	IP67
IK Rating	IK09
Mounting	Recessed inground
Operating Temperature	-25 °C ~ +50 °C
THD	<10%
Lifespan	>50,000 Hrs (Ta=30 °C @L70)
Certificate	BIS / CE / RoHS



# JQL-GBLC018W / JQL-GBLC024W / JQL-GBLC036W / JQL-GBLC050W


#### Features

- Recessed luminaire is suitable for a wide range of wallwashing, accent, surface grazing applications in architectural, hospitality and retail environments
- Multiple customisation options to illuminate interior walls, exterior facades and unique architectural details. Drive-over 4000 Kg at max 40 Km/h. Designed to last in extremely harsh environments
- Intelligent dynamic, tunable, white grazing; DMX and DALI controllable, easy to install with the integrated universal power supply and connect via combined power and data connectors
- High power recessed inground LED light, fashion and beautiful appearance
- The light body used die casting aluminium, stainless steel trim, high strength toughened glass to resist the impact and friction, glare-free design brings you visual comfort



#### **SPECIFICATIONS**

Power Consumption 18 W / 24 W / 36 W / 50 W Luminous Flux 90 Lm / W at 3000 K Color Temperature 2700K / 3000K / 4000K / RGB / RGBW Beam Angle 8° / 15° / 30° / 36° / 45° / 60° / 90° Input Voltage DC24 V / 100-277 V Control DMX / RDM / DALI / Remote / On-Off Power Factor ≥0.95 Housing Aluminium body + Stainless steel trim Tempered class Cover Dimensions ø200 x H 90 / ø200 x H 95 / ø250 x H 95 / ø300 x H 90 IP67 IP Rating IK Rating IK09 Mounting Recessed inground Operating Temperature -25 °C ~ +50 °C THD <10% >50,000 Hrs (Ta=30 °C @L70) Lifespan Certificate BIS / CE / RoHS




# Flexi Wallwasher

Jaquar conceived the idea of flexible wallwasher solutions to provide maximum flexibility and assist designers and architects in overcoming challenges posed by standard luminaires in various projects. It is the perfect solution for uneven surfaces whilst ensuring high performance. Offering highly customizable optics and color temperatures, Jaquar aims to provide a very unique and distinctive solution for this application. These are fully compatible with advanced protocols such as DMX512, RDM & DALI.

# Flexi Wallwasher





SPECIFICATIONS

# JQL-FWWL060W

### Features

- The chain module pixel lights suit for all kinds of special-shaped lighting requirements
- Unique linked chain design, it can change the shape based on various needs
- Power supply is built in each module, can connect each other at any length
- CREE XPE light source, different beam angles available
- IP67, ideal for indoor and outdoor installation, widely used in landscape architecture like trees, rockery, garden, yards, hotel pillars and similar lighting projects

Power Consumption	3 W per module
Luminous Flux	70 J m / W at 3000 K
Color Temperature	2200K / 3000K / 4000K / 5700K / RGB / RGBW
Beam Angle	10° / 30° / 45° / 60° / 15° × 45° / 10° x 60°
Input Voltage	DC24 V
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Dimensions	Ø45 x 48 per module
Housing	Aluminium body with PMMA lens and tempered glass
IP Rating	IP66
IK Rating	IK07
Mounting	Surface mount
Operating Temperature	-30 °C ~ +45 °C
THD	<10%
Lifespan	>50,000 Hrs (Ta=30 °C @L70)





# Guardrail Lights

Jaquar guardrail lights and handrail lights are a unique product solution designed to be an integrated part of the rails. They come with multiple beam symmetric and asymmetric beam options and are designed with humanized anti-glare optics. They adopt the highest electrical safety parameters and work on low voltage DC with centralised power feeding.



### JQL-HDRL002W

#### Features

- Unobtrusive appearance design
- · Strong aviation aluminium housing
- · Adopt the anti-theft design fixed by rotation
- · Self-contained stainless steel elastic bracket
- Seamless splicing of light, with optical dark-free zone design
- Meets international standards DMX512 protocol

52





#### **SPECIFICATIONS**

**Power Consumption** Luminous Flux Color Temperature Beam Angle (50% Imax) 50 x 80° Input Voltage Protection Class IEC Control Power Factor Dimensions Housing Cover IP Rating IK Rating Mounting **Operating Temperature** THD Lifespan Certificate

2 W 150 Lm @4000 K 2700 K / 3000 K / 4000 K / 5000 K / 5700 K / 6500 K DC24 V Ш DMX / RDM / DALI / Remote / On-Off ≥0.95 Ø32 / W 52 / W 30 / H 37.6 Die cast aluminum ADC12 PC IP66 IK08 Recessed -35 °C ~ 60 °C (-31 °F ~ 140 °F) <10% >50,000 Hrs (Ta=35 °C @L70) BIS / CE / RoHS



### JQL-HDRLX02W

#### Features

- Unobtrusive appearance design
- Strong aviation aluminium housing
- · Self-contained stainless steel elastic bracket
- Seamless splicing of light, with optical dark-free zone design
- Accurate and asymmetric optical design
- The surface is electroplated to prevent corrosion







#### SPECIFICATIONS

Power Consumption	2 W
Luminous Flux	130 Lm @4000 K
Color Temperature	2700 K / 3000 K / 4000 K / 5000 K / 5700 K / 6500 K
Beam Angle (50% Imax)	55 x 70°
Input Voltage	DC24 V
Protection Class IEC	III
Control	DMX / RDM / DALI / Remote / On-Off
Power Factor	≥0.95
Dimensions	Ø37 / W 33 / H 40
Housing	Die cast aluminum ADC12
Cover	PC
IP Rating	IP66
IK Rating	IK08
Mounting	Recessed
Operating Temperature	-35 °C ~ 60 °C (-31 °F ~ 140 °F)
THD	<10%
Lifespan	>50,000 Hrs (Ta=35 °C @L70)
Certificate	BIS / CE / RoHS


All dimensions are in mm



### JQL-GDRL036W

#### Features

- Unobtrusive appearance design
- Strong aviation aluminium housing
- Definitive and impact-resistant toughened glass
- Varied options of visually comfortable and precise optical lens
- Integrated extruded aluminium guardrail pipe
- High-precision vents for greater performance, increased durability, and higher reliability
- Centralised power feeding adopted and safe voltage
- Anti-glare optical design



#### SPECIFICATIONS

Power Consumption 36 W 3060 Lm @4000 K Luminous Flux 4000 K / 5000 K Color Temperature Beam Angle (50% Imax) 10 x 120° DC24 V / AC100-240 V 50 / 60 Hz Input Voltage Protection Class IEC ||| / | Control DMX / RDM / DALI / Remote / On-Off Power Factor ≥0.95 W 2250 / W 1500 / Ø112 / Ø130 / Ø1106 / W 150 / Dimensions H 315 Extruded aluminum 6063 Housing Toughened glass Cover IP66 IP Rating IK06 IK Rating Adjustable bracket Mounting **Operating Temperature** -35 °C ~ 60 °C (-31 °F ~ 140 °F) THD <10% >50,000 Hrs (Ta=35 °C @L70) Lifespan BIS / CE / RoHS Certificate



# Trunking Lights

Jaquar trunking lights have a seamless body and invisible connector design for beautiful aesthetics and are designed to create an even and soothing lighting effect. Ensuring very high efficiency parameters of up to 150 Lm / W and anti-glare technology allows for UGR<19 compliance. The housing has been specially designed to allow for very effective heat dissipation given the 24 hour usage application. Push buttons provided on the fixtures are another unique feature which allows for easy and convenient installation and maintenance.



### JQL-TRL035W

#### Features

- Robust design: tough body makes sure good heat dissipation, IP65, design, surface mounted and suspension mounted ,ensures fixtures to meet different lighting applications
- Best-in-class performance: 150 Lm / W at 4000K light output, UGR<19, glare-free
- Seamless connection: seamless body and invisible connector design creates even lighting effect
- Easy Maintenance: Push and Pull button on the fixture, easy and convenient installation and maintenance

### SPECIFICATIONS

Power Consumption Luminous Flux Color Temperature Beam Angle Input Voltage Protection Class Control Power Factor Dimensions Housing Net Weight IP Rating IK Rating Mounting **Operating Temperature** THD Lifespan

Certificate

35 W 150 Lm / W at 4000 K 2700 K / 3000 K / 4000 K / 5000 K / 6500 K 120° AC100-277 V DMX / RDM / DALI / Remote / On-Off ≥0.95 L 1200 × W 55 × H 86.4 Aluminium body with PMMA cover 0.6Kg IP66 IK06 Surface mount with adjustable bracket -30 °C ~ +45 °C <10% >50,000 Hrs (Ta=30 °C @L70) BIS / CE / RoHS





# Under Water Lights

Jaquar underwater lights are designed with high a quality 304/316 stainless steel housing which allows for longer life in both fresh water as well as salt water. Their superior anti-corrosion and anti-rust properties make them ideal for the water landscape projects. Luminaires have been designed with a high precision waterproof silicon ring to protect their IP68 structure. They are compatible with various digital lighting control protocols for flexibility in projects.


### **Under Water Lights**



### JQL-UWLB006W / JQL-UWLB009W / JQL-UWLB012W / JQL-UWLB018W / JQL-UWLB024W / JQL-UWLB036W

#### Features

- High quality 304 stainless steel material housing
- Long lasting in fresh water and sea water
- Good anti-corrusion and anti-rust performance in the water landscape project
- Highly efficient CREE LED chips and OSRAM 4-in-1 LED chips for RGBW light
- 1.5 meters UL certified cable for easy installation. Length can be customised
- High precision water-proof sllicon ring for the IP68 structure water-proof



#### SPECIFICATIONS

Power Consumption Luminous Flux Color Temperature Beam Angle Input Voltage Protection Class

Control Power Factor Housing Cover Dimensions IP Rating IK Rating

Mounting

Lifespan

Certificate

THD

**Operating Temperature** 


6 W / 9 W / 12 W / 18 W /24 W / 36 W 75 Lm/W at 3000 K 2700 K / 3000 K / 4000 K / 5700 K / RGB / RGBW 10° / 15° / 30° / 45° / 60° / 90° AC100-240 V / DC24 V IK07 DMX / RDM / DALI / Remote / On-Off ≥0.95 stainless steel body Tempered glass ø115 x H 145 / ø158 x H 150 / ø193 x H 200 / ø215 x H 215 / ø238 x H 250 IP68 IK07 Surface mount with adjustable bracket -30 °C ~ +45 °C <10% >50,000 Hrs (Ta= 30 °C @L70) BIS / CE / RoHS



### JQL-UWLA006W / JQL-UWLA009W / JQL-UWLA012W / JQL-UWLA015W / JQL-UWLA018W

#### Features

- High quality 304 stainless steel material housing
- Long lasting in fresh water and sea water
- Good anti-corrusion and anti-rust performance in the water landscape project
- Highly efficient CREE LED chips and OSRAM 4-in-1 LED chips for RGBW light
- 1.5 meters UL certified cable for easy installation. Length can be customised
- High precision water-proof sllicon ring for the IP68 structure water-proof



#### SPECIFICATIONS

Power Consumption Luminous Flux Color Temperature Beam Angle Input Voltage Protection Class Control Power Factor Housing Cover Dimensions

IP Rating IK Rating Mounting Operating Temperature THD Lifespan Certificate 6 W / 9 W / 12 W / 15 W / 18 W 75 Lm/W at 3000 K 2700 K / 3000 K / 4000 K / 5700K / RGB / RGBW 10° / 15° / 30° / 45° / 60° / 90° AC100-240 V / DC24 V IK07 DMX / RDM / DALI / Remote / On-Off ≥0.95 Stainless steel body Tempered glass ø150 x H 76 / ø170 x H 76 / ø180 x H 76 / ø210 x H 76 / ø230 x H 76 / ø250 x H 76 IP68 IK07 Surface mount with adjustable bracket -30 °C ~ +45 °C <10% >50,000 Hrs (Ta=30 °C @L70) BIS / CE / RoHS





# Chandeliers

There are a few bigger statements of luxury in an indoor space than a sparkling chandelier. Discover a grand centrepiece for your indoor space in Jaquar's range of chandeliers.

- Our chandeliers, a fusion of class and quality, are made with lead-free Spectra and Strass crystals of high-precision cut, clarity, colour, and shape, from some of the world's best crystal manufacturers.
- We use mainly brass in the frame of our chandeliers, which come with a 7 year to 10 year warranty on the plating – ranging from 24K Gold to Chrome, Antique Brass and Copper.
- With the fabrication and plating of chandeliers being done in-house, Jaquar is one of the leading brands of India with its own production facility for crystal chandeliers.
- Available in classic and contemporary styles, reflecting traditional grace or modern elegance, our chandeliers range from 3-head to 24-head designs, with suspended or ceiling-mounted options.
- In fact, apart from the extensive choice, Jaquar Lighting also offers a unique customisation option in Crystal chandeliers - you can redesign, mix and match, and even ask to increase or reduce the crystals used in the chandeliers you select.

But no matter which chandelier you choose from Jaquar Lighting, it'll definitely have the power to be the cynosure of all eyes in the room.

# Content

CHANDELIERS WITH SHADES Octans Ara Carina Ursa	088 089 090 091
TIERED CANDLE CHANDELIERS Pictor Antlia Apus Pollux Mensa Vela Grandiose Meridian Gondola Celeste Celosia Trillium Centaurus Circinus Cassia Wisteria Pegasus Bergenia Phoenix Selene Lantana	94 95 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114

CONCEALED LIGHT CHANDELIERS Sirius Noblella Grapewine Honey comb Lancia Lancia Galaxy Cosmos Supernova Digest Cairn Nimbus Starling Starling	118 119 120 121 122 123 124 125 126 127 128 129 130 131
MODERN CHANDELIERS Lepus Nebula Arcturus Nova Monsoon Umbra Norma Canis	134 135 136 137 138 139 140 141
MINIMALISTIC CHANDELIERS Tortile	144
WALL LAMPS Arena   Trident Tulipz   Exalta Trident Gold   Celestia Pear Volans	148 149 150 151





# Chandeliers with Shades

Perfect for making the light source in the room discrete, a chandelier with shades works even better when paired with drapery that matches the colour and texture of the shades in the chandelier.



# Octans

Strass Product code: CHL-ABR-CHL00954007

Color:BronzeMaterial:Zinc alloNo. of heads:5+10+1Cap type:E14Wattage:30 x 4 VDimension (mm):Ø 1500Weight (Kg):115No. of boxes for one product:6Available in Strass and Spectrarystals

Spectra Product code: CHL-ABR-CUST00954007

Bronze Zinc alloy and fabric shade 5+10+15 E14 30 x 4 W LED Ø 1500 x H 1850 115 6



## Ara

Strass Product code: CHL-ABR-CHL00954005

Color:BrMaterial:CaNo. of heads:44Cap type:EWattage:24Dimension (mm):ØWeight (Kg):59No. of boxes for one product:6Premium fabric shadeF

Bronze Copper, bronze and fabric 4+8+12 E14 24 x 4 W LED Ø 1260 x H 1850 59 :: 6



# Carina

**Strass** Product code: CHL-SKG-CHL00954003

Color:SK goldMaterial:Zinc alloNo. of heads:6+12+1Cap type:E14Wattage:36 x 4 WDimension (mm):Ø 1530Weight (Kg):177No. of boxes for one product:9Available in Strass and Spectra crystals

#### **Spectra** Product code:

Product code: CHL-SKG-S00954003

SK gold Zinc alloy and fabric shade 6+12+18 E14 36 x 4 W LED Ø 1530 x H 2300 177 9



## Ursa

Product code: CHL-GLD-14844X15C

Color:GaMaterial:ZirNo. of heads:TCap type:E1Wattage:TDimension (mm):ØWeight (Kg):20No. of boxes for one product:1

Gold finish Zinc alloy and fabric shade 15 E14 15 x 4 W LED Ø 1000 x H 600 20 1



# Tiered Candle Chandeliers

A tiered candle-chandelier like this one is the perfect way to accentuate a room's traditional elegance. Reminiscent of real candle chandeliers from many centuries ago, that were lowered, lit and then pulled up by rope, the unmasked light source allows the crystals underneath to sparkle with greater intensity.



# Pictor

Strass Product code: CHL-SKG-CHL00954009

Color:SK goldMaterial:Zine alloNo. of heads:5+10+1Cap type:E14Wattage:30 x 4 WDimension (mm):Ø 1450Weight (Kg):110No. of boxes for one product:13Available in Strass and Spectra crystals

Spectra

Product code: CHL-SKG-SCHL00954009

SK gold Zine alloy with jade 5+10+15 E14 30 x 4 W LED Ø 1450 x H 2100 110 13



# Antlia

**Strass** Product code: CHL-SLV-CHL00954008

Color:SilverMaterial:CopperNo. of heads:8+16Cap type:E14Wattage:24 x 4 VDimension (mm):Ø 1230Weight (Kg):115No. of boxes for one product:3Available in Strass and Spectra crystals

Spectra

Product code: CHL-SLV-SCHL00954008

Silver Copper and glass 8+16 E14 24 x 4 W LED Ø 1230 x H 1100 115 3

COMPLETE LED LIGHTING SOLUTIONS 095



## Apus

Strass Product code: CHL-ABR-CHL00954004 CHL-GLD-S00954004

Color: Material: No. of heads: Cap type: Wattage: Dimension (mm): Weight (Kg): No. of boxes for one product: 16 Available in Strass and Spectra crystals

Spectra Product code:

Bronze Copper with natural jade 6+10+15+20 E14 51 x 4 W LED Ø 1900 x H 2800 340



# Pollux

Strass Product code: CHL-ABR-CHL00954002

Color:BronzeMaterial:Zinc alloNo. of heads:6+8+10Cap type:E14Wattage:48 x 4 VDimension (mm):Ø 1600Weight (Kg):212No. of boxes for one product:6Available in Strass and Spect:rystals

### Spectra

Product code: CHL-ABR-S00954002

Bronze Zinc alloy and bobeche glass 6+8+10+19+5 E14 48 x 4 W LED Ø 1600 x H 2300 212 : 6



# Mensa

#### Strass

Product code: CHL-GLD-CHL00954001

Color:GolMaterial:CopNo. of heads:8+1Cap type:E14Wattage:56Dimension (mm):Ø 2Weight (Kg):450No. of boxes for one product:1324K gold used for perfect finish

#### Available in Strass and Spectra crystals

Spectra Product code: CHL-GLD-SCHL00954001

Gold Copper with natural pink jade 8+12+16+20 E14 56 x 4 W LED Ø 2260 x H 3000 450 13



# Vela

Strass Product code:

Color: Material: No. of heads: Cap type: Wattage: Dimension (mm): Weight (Kg): No. of boxes for one product: 8 Available in Strass and Spectra crystals

Spectra

Product code: CHL-SKG-CHL009540036C CHL-SKG-S0095400636C

> SK gold Zinc alloy with natural pink jade 6+12+18 E14 36 x 4 W LED Ø 1550 x H 2110 166

COMPLETE LED LIGHTING SOLUTIONS 099



### Grandiose strass

### Gold

Product code: CHL-GLD-110212B

#### Chrome

Product code: CHL-CHR-110212B

#### Spectra

Gold Product code: CHL-GLD-S110212B

Chrome Product code: CHL-CHR-S110212B

### Color:

Material:Brass caseNo. of heads:12Cap type:E14Wattage:12 x 4 WDimension (mm):Ø 850 x HWeight (Kg):18No. of boxes for one product:1Available in Strass and Spectra crystals

Gold and chrome Brass casting 12 E14 12 x 4 W LED Ø 850 x H 560 18 1



### Meridian Strass

### Gold

Product code: CHL-GLD-20918B

#### Chrome Product code: CHL-CHR-20918B

### Spectra

Gold Product code: CHL-GLD-S20918B

Chrome Product code: CHL-CHR-S20918B

- Color: Material: No. of heads: 18 Cap type: E14 Wattage: Dimension (mm): Weight (Kg): 20 No. of boxes for one product: 1 Available in Strass and Spectra crystals
- Gold and chrome Brass casting 18 x 4 W LED Ø 1050 x H 560



### Gondola <sub>Strass</sub>

### Gold

Product code: CHL-GLD-2028A

#### Chrome Product code: CHL-CHR-2028A

### Spectra

Gold Product code: CHL-GLD-S2028A

Chrome Product code: CHL-CHR-S2028A

### Color: Materia

- Material:Brass cNo. of heads:8Cap type:E14Wattage:8 x 4 WDimension (mm):Ø 700 :Weight (Kg):12No. of boxes for one product:1Available in Strass and Spectra crystals
- Gold and chrome Brass casting 8 E14 8 x 4 W LED Ø 700 x H 430 12 1



### Celeste Strass

### Gold

Product code: CHL-GLD-93112A

#### Chrome Product code: CHL-CHR-93112A

### Spectra

Gold Product code: CHL-GLD-S93112A

Chrome Product code: CHL-CHR-S93112A

Color: Gold and chrome Material: Brass No. of heads: 6+6 Cap type: Wattage: Dimension (mm): Weight (Kg): 21 No. of boxes for one product: 2 Available in Strass and Spectra crystals



# Celosia

Strass Product code: CHL-SLV-CHL7165X10C

Color:SiMaterial:CNo. of heads:10Cap type:EWattage:10Dimension (mm):ØWeight (Kg):60No. of boxes for one product:1Real silver used for perfect finish

**Spectra** Product code: CHL-SLV-S7165X10C

Silver (Real) Copper and bobeche glass 10 E14 10 x 4 W LED Ø 1000 x H 885 60



# Trillium

Strass Product code: CHL-GLD-CHLSYY15742D CHL-GLD-SCHLSYY15742D

Color: Material: No. of heads: Cap type: Wattage: Dimension (mm): Weight (Kg): No. of boxes for one product: 6 24K gold used for perfect finish Available in Strass and Spectra crystals

Spectra Product code:

Gold

Copper and bobeche glass 5+10+15 E14 30 x 4 W LED Ø 1500 x H 2120 175



# Centaurus

Strass Product code: CHL-GLD-CHL17712X30C

Colour:GoldMaterial:Zinc alloNo. of heads:15+10+Cap type:E14Wattage:30 x 4 VDimension (mm):Ø 1470Weight(Kg):160No. of boxes for one product:7Available in Strass and Spect-- crystals

Spectra Product code: CHL-GLD-S17712X30C

Gold Zinc alloy with natural jade 15+10+5 E14 30 x 4 W LED Ø 1470 x H 1900 160



# Circinus

Strass Product code: CHL-GLD-CHL17802X18C

Color: Material: No. of heads: Cap type: Wattage: Dimension (mm): Weight(Kg): No. of boxes for one product: 3

Spectra Product code: CHL-GLD-S17802X18C

Gold Zinc alloy with natural jade 12+6 E14 18 x 4 W LED Ø 1150 x H 1000 65

Available in Strass and Spectra crystals



# Cassia

Strass Product code: CHL-GLD-CHL17802X70C

Color:GoMaterial:ZinNo. of heads:70Cap type:E14Wattage:70Dimension (mm):Ø 2Weight (Kg):350No. of boxes for one product:15

Spectra Product code: CHL-GLD-S17802X70C

Gold Zinc alloy with natural jade 70 E14 70 x 4 W LED Ø 2000 x H 3100 350

Available in Strass and Spectra crystals



# Wisteria

Strass Product code: CHL-BRS-CHLSYY60170

Color:BronzeMaterial:Zinc alloNo. of heads:6+12+1Cap type:E14Wattage:80 x 4 VDimension (mm):Ø 2330Weight (Kg):300No. of boxes for one product:17Available in Strass and Spect-rystals

Spectra

Product code: CHL-BRS-SCHLSYY60170

Bronze Zinc alloy and marble 6+12+18+12+24+8 E14 80 x 4 W LED Ø 2330 x H 3300 300 17

COMPLETE LED LIGHTING SOLUTIONS 109



# Pegasus

Strass Product code: CHL-GLD-CHL1739X18C

Color: Material: No. of heads: Cap type: Wattage: Dimension (mm): Weight (Kg): No. of boxes for one product: 3

Spectra Product code: CHL-GLD-SCHL1739X18C

Gold Zinc alloy with natural jade 12+6 E14 18 x 4 W LED Ø 1160 x H 690 50

Available in Strass and Spectra crystals



# Bergenia

Strass Product code: CHL-GLD-CHL17395X36C

Color:GoldMaterial:Zinc alloNo. of heads:6+15+1Cap type:E14Wattage:36 x 4 VDimension (mm):Ø 1500Weight (Kg):118No. of boxes for one product:6Available in Strass and Spectra crystals

Spectra Product code: CHL-GLD-S17395X36C

Gold Zinc alloy and glass 6+15+10+5 E14 36 x 4 W LED Ø 1500 x H 2350 118 6



# Phoenix

Strass Product code: CHL-GLD-CHLSYA65009

Color:GoldMaterial:CopperNo. of heads:6+10+1Cap type:E14Wattage:32 x 4 VDimension (mm):Ø 1550Weight (Kg):205No. of boxes for one product:918K gold used for perfect finist-Available in Strass and Spectra crystals

Spectra Product code:

Product code: CHL-GLD-SCHLSYA65009

Gold Copper with natural jade 6+10+16 E14 32 x 4 W LED Ø 1550 x H 1920 205 9



# Selene

Strass Product code: CHL-SLV-CHL7165X30C

Color:Silver (RMaterial:CopperNo. of heads:5+10+1Cap type:E14Wattage:30 x 4 VDimension (mm):Ø 1460Weight (Kg):198No. of boxes for one product:4Real silver used for perfect finistAvailable in Strass and Spectra crystals

Spectra Product code: CHL-SLV-S7165X30C

Silver (Real) Copper and bobeche glass 5+10+15 E14 30 x 4 W LED Ø 1460 x H 1900 198



# Lantana

Strass Product code: CHL-GLD-CHLSYY66001

Color:GMaterial:GNo. of heads:15Cap type:EWattage:3Dimension (mm):ØWeight (Kg):18No. of boxes for one product:718K gold used for perfect finish

Spectra

Product code: CHL-GLD-SCHLSYY66001

Gold Copper with natural jade 15+10+6 E14 31 x 4 W LED Ø 1460 x H 2290 180

COMPLETE LED LIGHTING SOLUTIONS 115



# Concealed Light Chandeliers

A complete creation in crystal, the opulence of chandeliers like these demand décor that's no less magnificent. Concealing the light source within allows the crystals to appear as if they are the light source themselves – a multitude of little suns scattering beautiful rays around the room.



# Sirius <sub>Strass</sub>

#### Cala

Gold Product code: CHL-GLD-11063XB

#### Chrome Product code:

CHL-CHR-11063XB

# Spectra

Gold Product code: CHL-GLD-S11063XB

Chrome Product code: CHL-CHR-S11063XB

# Color:Gold andMaterial:BrassNo. of heads:27Cap type:E14Wattage:27 x 4 WDimension (mm):Ø 1066Weight (Kg):55No. of boxes for one product:2Available in Strass and Spectrarystals

Gold and chrome Brass 27 E14 27 x 4 W LED Ø 1066 x H 2743 55 2



# Nobella Strass

# Gold

Product code: CHL-GLD-1009A

### Chrome Product code: CHL-CHR-1009A

## Spectra

Gold Product code: CHL-GLD-S1009A

Chrome Product code: CHL-CHR-S1009A

## Color: Materia

#### 

COMPLETE LED LIGHTING SOLUTIONS 119

Gold and chrome



# Grapewine

## Strass Gold

Product code: CHL-GLD-40322A

#### Chrome

Product code: CHL-CHR-40322A

## Spectra

Gold Product code: CHL-GLD-S40322A

Chrome Product code: CHL-CHR-S40322A

Color:

 Material:
 Brass

 No. of heads:
 8

 Cap type:
 E27

 Wattage:
 8 x 4 W LED

 Dimension (mm):
 Ø 600 x H 380

 Weight (Kg):
 16

 No. of boxes for one product:
 1

 Available in Strass and Spectra crystals

Gold and chrome



# Honey Comb

# Strass

Gold Product code: CHL-GLD-4031A

#### Chrome

Product code: CHL-CHR-4031A

# Spectra

Gold Product code: CHL-GLD-S4031A

Chrome Product code: CHL-CHR-S4031A

# Color:Gold andMaterial:BrassNo. of heads:6Cap type:E27Wattage:6 × 4 WDimension (mm):Ø 550 ×Weight (Kg):17No. of boxes for one product:1Available in Strass and Spectrarystals

Gold and chrome Brass 6 E27 6 x 4 W LED Ø 550 x H 510 17 1



# Lancia

## **Strass** Gold

Product code: CHL-GLD-8051B

#### Chrome Product code: CHL-CHR-8051B

**Spectra** Gold

Gold Product code: CHL-GLD-S8051B

Chrome Product code: CHL-CHR-S8051B

# Color:

Material:Brass caNo. of heads:4Cap type:E14Wattage:4 × 4 WDimension (mm):Ø 400 ×Weight (Kg):4.5No. of boxes for one product:1Available in Strass and Spectra crystals

Gold and chrome Brass casting 4 E14 4 × 4 W LED Ø 400 × H 180 4.5 1 covstals



# Lancia Strass

Gold

Product code: CHL-GLD-80511

#### Chrome Product code: CHL-CHR-80511

# Spectra

Gold Product code: CHL-GLD-S80511

Chrome Product code: CHL-CHR-S80511

## Color: Material: No. of heads: Cap type: Wattage: Dimension (mm): Weight (Kg): No. of boxes for one product: 1

Gold and chrome Brass casting З E14 3 x 4 W LED Ø 250 x H 200 2 Available in Strass and Spectra crystals



# Galaxy <sub>Strass</sub>

### 011455

Gold Product code: CHL-GLD-CUST11025

Chrome Product code: CHL-CHR-CUST11025

## Spectra

Gold Product code: CHL-GLD-CUSTS11025

Chrome Product code: CHL-CHR-CUSTS11025

#### Color: Chrome and gold Material: Brass No. of heads: NA Cap type: NA Wattage: 120 W LED Dimension (mm): Ø 914 x H 330 Weight (Kg): 25 No. of boxes for one product: 1 Available in Strass and Spectra crystals



# COSMOS Strass

Gold Product code: CHL-GLD-CUST11021

Chrome Product code: CHL-CHR-CUST11021

## Spectra

Gold Product code: CHL-GLD-CUSTS11021

Chrome Product code: CHL-CHR-CUSTS11021

#### Color: Chrome and gold Material: Brass No. of heads: NA Cap type: NA Wattage: 60 W LED Dimension (mm): Ø 600 x H 90 Weight (Kg): 12 No. of boxes for one product: 1 Available in Strass and Spectra crystals



# Supernova strass

# Gold

Product code: CHL-GLD-CUST11028

Chrome Product code: CHL-CHR-CUST11028

#### Spectra

Gold Product code: CHL-GLD-CUSTS11028

Chrome Product code: CHL-CHR-CUSTS11028

#### Color: Chrome and gold Material: Brass No. of heads: NA Cap type: NA 105 W LED Wattage: Dimension (mm): L 533 x W 533 x H 533 Weight (Kg): 18 No. of boxes for one product: 1 Available in Strass and Spectra crystals



# Digest Strass

Gold

Product code: CHL-GLD-11015

Chrome Product code: CHL-CHR-11015

## Spectra

Gold Product code: CHL-GLD-S11015

Chrome Product code: CHL-CHR-S11015

# Color: Material: Wattage:

Brass No. of heads: 12 Cap type: E14 12 x 4 W LED Dimension (mm): Ø 820 x H 300 Weight (Kg): 35 No. of boxes for one product: 1 Available in Strass and Spectra crystals

Chrome and gold



# Cairn Strass

# Gold

Product code: CHL-GLD-11060

### Chrome

Product code: CHL-CHR-11060

## Spectra

Gold Product code: CHL-GLD-S11060

Chrome Product code: CHL-CHR-S11060

#### Color: Materia

 Material:
 Brass

 No. of heads:
 14

 Cap type:
 E14

 Wattage:
 14 x 4 W LED

 Dimension (mm):
 Ø 600 x H 1260

 Weight (Kg):
 35

 No. of boxes for one product:
 1

 Available in Strass and Spect= crystals

Chrome and gold



# Nimbus

## Strass Gold

Product code: CHL-GLD-689B

## Chrome

Product code: CHL-CHR-689B

## Spectra

Gold Product code: CHL-GLD-S689B

Chrome Product code: CHL-CHR-S689B

## Color:

Material:BrassNo. of heads:6Cap type:E14Wattage:6 x 4 WDimension (mm):Ø 400 xWeight (Kg):8No. of boxes for one product:1Available in Strass and Spectra crystals

Gold and chrome Brass 6 E14 6 x 4 W LED Ø 400 x H 900 8 1



# Starling Strass

# Gold

Product code: CHL-GLD-80881B

#### Chrome Product code: CHL-CHR-80881B

**Spectra** Gold

Product code: CHL-GLD-S80881B

Chrome Product code: CHL-CHR-S80881B

# Color:

Material:Brass ofNo. of heads:4Cap type:E14Wattage:4 × 4 WDimension (mm):Ø 500 ×Weight (Kg):6No. of boxes for one product:1Available in Strass and Spectra crystals

Gold and chrome Brass casting 4 E14 4 x 4 W LED Ø 500 x H 180 6 1



# Starling Strass

# Gold

Product code: CHL-GLD-8088B

### Chrome Product code: CHL-CHR-8088B

## Spectra

Gold Product code: CHL-GLD-S8088B

Chrome Product code: CHL-CHR-S8088B

# Color: Material: Wattage:

No. of heads: З Cap type: E14 Dimension (mm): Weight (Kg): 4.5 No. of boxes for one product: 1 Available in Strass and Spectra crystals

Gold and chrome Brass casting 3 x 4 W LED Ø 330 x H 140



# Modern Chandeliers

Representing the evolution of chandeliers, rectilinear and curved forms of chandeliers question traditional outlines and pay tribute to the more functional forms seen in architecture of the 20th century. Ideal for interiors where modern lines and newer, man-made materials are chosen.



# Lepus

# Strass

Gold Product code: CHL-GLD-40510X2

Chrome Product code: CHL-CHR-40510X2

## Spectra

Gold Product code: CHL-GLD-S40510X2

Chrome Product code: CHL-CHR-S40510X2

# Color:Gold andMaterial:BrassNo. of heads:12Cap type:G9Wattage:12 x 3 NDimension (mm):L 1066Weight (Kg):20No. of boxes for one product:1Available in Strass and Spect-- crystals

Gold and chrome Brass 12 G9 12 x 3 W LED L 1066 x W 406 x H 300 20 1



# Nebula

Strass Gold Product code: CHL-GLD-11058/3

Chrome Product code: CHL-CHR-11058/3

## Spectra

Gold Product code: CHL-GLD-S11058/3

Chrome Product code: CHL-CHR-S11058/3

# Color:Gold andMaterial:BrassNo. of heads:NACap type:NAWattage:225 W IDimension (mm):L 1460Weight (Kg):30No. of boxes for one product:1Available in Strass and Spectra crystals

Gold and chrome Brass NA NA 225 W LED L 1460 x W 457 x H 457 30 1



# Arcturus

## Strass Gold

Product code: CHL-GLD-11065

# Chrome

Product code: CHL-CHR-11065

## Spectra

Gold Product code: CHL-GLD-S11065

Chrome Product code: CHL-CHR-S11065

## Color: Material: No. of heads: Cap type: Wattage: Dimension (mm): Weight (Kg): No. of boxes for one product: 1

Gold and chrome Brass NA NA 150 W LED L 1062 x W 609 x H 609 28 Available in Strass and Spectra crystals



# Nova

Gold Product code: CHL-GLD-AS11066

Color:Gold andMaterial:Brass andNo. of heads:8Cap type:E14Wattage:8 x 4 W LDimension (mm):L 1219 xWeight (Kg):20No. of boxes for one product:1Available in mouth blown drop glass only

Chrome Product code: CHL-CHR-AS11066

Gold and chrome Brass and glass 8 E14 8 x 4 W LED L 1219 x W 500 x H 457 20 1



# Monsoon

Strass Gold Product code: CHL-GLD-CUST11083

Color:GatMaterial:BrNo. of heads:12Cap type:SpWattage:12Dimension (mm):12Weight (Kg):18No. of boxes for one product:1Available in Strass crystals only12

## Spectra

Chrome Product code: CHL-CHR-CUST11083

Gold and chrome Brass 12 Spot light 12 x 2 W LED L 1524 x W 304 x H 609 18





# Umbra

## Strass Gold

Product code: CHL-GLD-9111C

#### Chrome Product code: CHL-CHR-9111C

# Spectra

Gold Product code: CHL-GLD-S9111A

Chrome Product code: CHL-CHR-S9111A

Color:Gold andMaterial:BrassNo. of heads:1Cap type:E14Wattage:1 x 4 WDimension (mm):Ø 250 xWeight (Kg):1.5No. of boxes for one product:1Available in Strass and Spectrarystals

Gold and chrome Brass 1 E14 1 x 4 W LED Ø 250 x H 260 1.5 1 corstals



# Norma

Gold K9 Product code: CHL-GLD-MD177218009

Color: Gold Material: MS No. of heads: 9 Cap type: E14 9 x 4 W LED Wattage: Dimension (mm): Ø 800 x H 1375 30 Weight (Kg): No. of boxes for one product: 1 Available in K9 crystals only



# Canis Strass

Gold

Product code: CHL-GLD-11003

Chrome Product code: CHL-CHR-11003

## Spectra

Gold Product code: CHL-GLD-S11003

Chrome Product code: CHL-CHR-S11003

# Color: Material:

Brass No. of heads: 7 Cap type: G9 Wattage: 7 x 3 W LED Dimension (mm): Ø 457 x H 200 Weight (Kg): 8 No. of boxes for one product: 1 Available in Strass and Spectra crystals

Chome and gold



# Minimalistic Chandeliers

Pushing the boundaries of the definition of chandeliers, iconic pieces like these are carefully designed to achieve the maximum effect with a minimum of elements. Accepting the challenge of today's minimalistic design aesthetic, pieces like this embody the concept of 'less is more'



# Tortile <sub>Strass</sub>

# Gold

Product code: CHL-GLD-11037

## Chrome

Product code: CHL-CHR-11037

## Spectra

Gold Product code: CHL-GLD-S11037

Chrome Product code: CHL-CHR-S11037

## Color: Materia

Material:BrassNo. of heads:5Cap type:Spot ligWattage:5 x 2 WDimension (mm):Ø 360 xWeight (Kg):8No. of boxes for one product:1Available in Strass and Spectra crystals

Chrome and gold Brass 5 Spot light 5 x 2 W LED Ø 360 x H 800 8 1





# Wall Lamps

Take a look at the brilliant new ideas from Jaquar Lighting for ambient room illumination. From timeless elegance to quirky design and artful expression, there's wall light for every need here.



# Arena

Strass Gold Product code: WBR-GLD-20SWB

Chrome Product code: WBR-CHR-20SWB

Color:Chrome aMaterial:Brass andNo. of heads:2Cap type:E14Wattage:2 x 4 W LDimension (mm):L 270 x WWeight (Kg):1.3No. of boxes for one product: 1Available in Strass and Spectra crystals

Spectra Gold Product code: WBR-GLD-S20SW

Chrome Product code: WBR-CHR-S20SW

Chrome and gold Brass and bobeche glass 2 E14 2 x 4 W LED L 270 x W 190 x H 250 1.3 :1

# Trident

Strass Gold Product code: WBR-GLD-9118B

Chrome Product code: WBR-CHR-9118B

Color:Chrome aMaterial:Brass andNo. of heads:2Cap type:E14Wattage:2 x 4 W LIDimension (mm):L 250 x WWeight (Kg):1.5No. of boxes for one product:1Available in Strass and Spectra crystals

Spectra Gold Product code: WBR-GLD-S9118B

Chrome Product code: WBR-CHR-S9118B

Chrome and gold Brass and bobeche glass 2 E14 2 x 4 W LED L 250 x W 160 x H 270 1.5 : 1 ra gnatola







# Tulipz

Strass Gold Product code: WBR-GLD-7771A

Chrome Product code: WBR-CHR-7771A

Color:Chrome aMaterial:BrassNo. of heads:1Cap type:GU5.3 / 1Wattage:1 x 35 WDimension (mm):L 130 x WWeight (Kg):1.5No. of boxes for one product:1Available in Strass and Spectra crystals

#### Spectra Gold Product code: WBR-GLD-S7771A

Chrome Product code: WBR-CHR-S7771A

Chrome and gold Brass 1 GU5.3 / 12 V 1 x 35 W LED L 130 x W 140 x H 500 1.5

# Exalta

Strass Gold Product code: WBR-GLD-98181A

Chrome Product code: WBR-CHR-98181A

Color:Chrome aMaterial:Brass andNo. of heads:1Cap type:E14Wattage:1 × 4 W LDimension (mm):L 100 × WWeight (Kg):1No. of boxes for one product:1Available in Strass and Spectra crystals

Spectra Gold Product code: WBR-GLD-S98181A

Chrome Product code: WBR-CHR-S98181A

Chrome and gold Brass and bobeche glass 1 E14 1 x 4 W LED L 100 x W 180 x H 280 1 :



# **Trident Gold**

Strass Gold Product code: WBR-GLD-98182A

Chrome Product code: WBR-CHR-98182A

#### Color: Material: No. of heads: Cap type: Wattage: Dimension (mm): Weight (Kg): No. of boxes for one product: 1

Spectra Gold Product code: WBR-GLD-S98182A

Chrome Product code: WBR-CHR-S98182A

Gold and chrome Brass 2 F14 2 x 4 W LED L 300 x W 280 x H 180 1.5 Available in Strass and Spectra crystals

# Celestia Pearl

#### Strass Gold Product code: WBR-GLD-96069A

Chrome Product code: WBR-CHR-96069A

Color: Material: No. of heads: 2 Cap type: Wattage: Dimension (mm): Weight (Kg): No. of boxes for one product: 1

Product code: WBR-GLD-S96069A Chrome

Spectra

Gold

Product code: WBR-CHR-S96069A

Gold and chrome Brass E 14 2 x 4 W LED L 260 x W 240 x H 130 1.5

Available in Strass and Spectra crystals







# Volans

Chrome Product code: WBR-CHR-5057

Color:CMaterial:BNo. of heads:NCap type:LWattage:9Dimension (mm):LWeight (Kg):0No. of boxes for one product:1Available in twist glass tube1

Chome and gold Brass NA LED strip 9 W L 110 x W 75 x H 290 0.4 : 1



# Decorative Lights

Jaquar Lighting's decorative lighting collection combines the very best of global design and craftsmanship in an impressively large range of designs and shapes. Jaquar Lighting's range of products in the Decorative category includes Chandeliers, Pendant lights, Wall and Ceiling mounted lights, Table lamps and Floor lamps, and even Aqua lights for use in bathrooms.

Within each type of light too, there's one for every preference. Pendant lights are available in single or multiple heads with suspended or ceiling mounted options. Ceiling lights are available in standalone, single tier, 2 tier and 3 tier variants with Chrome, White, or Rose Gold Finishes with Metal and Glass options. Our innovative range of LED wall lights are available in standalone, single head, 2 head and 3 head variants with matching chandeliers.

For enhancing the ambience of interiors, choose from our trendsetting table lamps that are available in Chrome, Glass, Wood and Metallic Finishes with fabric or PVC shades. Similar options are available in our Floor lamps too, which are distinctive and contemporary.

For use in moist environments like bathrooms, Jaquar Lighting's Aqua Lights feature a Chrome Finish and Ingress Protection (IP) 44 rating.

Unless otherwise specified, all Jaquar Lighting products are built with the flexibility to be compatible with not just LED lamps but CFL and GLS lamps too.

# Content

# DECORATIVE LIGHTS

Ceiling Lights	154
Floor Lamps	192
Table Lamps	202
Wall Lights	216
Bath (Aqua) Lights	234





To meet the sophisticated design requirements of ceiling lighting, Jaquar offers a vast repertoire to choose from. Discover some of the most alluring models from our latest collection.



#### JES-CHR-MD400500618C

Description: 1 Tier metal string with chrome finishing ceiling light Fixture Height: 1500 Standard Packaging Box: 1 Net Weight (Kg): 18 Lamp: G9 LED 4 W x 8 L W D H 680 1500

All dimensions are in mm
156 COMPLETE LED LIGHTING SOLUTIONS



### JES-CHR-MD400500654C

Description: 3 Tier metal string with chrome finishing ceiling light Fixture Height: 2500 Standard Packaging Box: 1 Net Weight (Kg): 38 Lamp: G9 Bulb 4 W x 24 L W D H 680 2500



#### JES-CHR-MD400500636C

Description: 2 Tier metal string with chrome finishing ceiling light Fixture Height: 1700 Standard Packaging Box: 1 Net Weight (Kg): 32 Lamp: G9 LED 4 W x 16 L W D H 680 1700



#### JES-RDG-MD400500636C

Description: 2 Tier metal string with rose gold finishing ceiling light Fixture Height: 1700 Standard Packaging Box: 1 Net Weight (Kg): 32 Lamp: G9 LED 4 W x 16 L W D H 680 1700



#### JES-RDG-MD400500654C

Description: 3 Tier metal string with rose gold finishing ceiling light Fixture Height: 2500 Standard Packaging Box: 1 Net Weight (Kg): 38 Lamp: G9 Bulb 4 W x 24 L W D H 680 2500





#### JES-RDG-MD400500618C

Description: 1 Tier metal string with rose gold finishing ceiling light Fixture Height: 1500 Standard Packaging Box: 1 Net Weight (Kg): 18 Lamp: G9 LED 4 W x 8 L W D H 680 1500



Description: 3 Light cone shaped chandelier with chrome finishing ceiling light Fixture Height: 1000 Standard Packaging Box: 1 Net Weight (Kg): 1.5 Lamp: E14 LED 4 W x 3 L W D H 600 1000

#### KCH-CHR-MD80476A

Description: 6 Light cone shaped chandelier with chrome finishing ceiling light Fixture Height: 1000 Standard Packaging Box: 1 Net Weight (Kg): 2.6 Lamp: E14 LED 4 W x 6 L W D H 650 1000

All dimensions are in mm

 158
 COMPLETE LED LIGHTING SOLUTIONS





#### KCH-CHR-MX81366B Description: 6 Light star shape glass tube with chrome finishing

ceiling light Fixture Height: 225 Standard Packaging Box: 1 Net Weight (Kg): 9.2 Lamp: G9 LED 4 W x 6 L W D H 450 225

#### JES-CHR-MX81368A

Description: 8 Light star shape glass tube with chrome finishing ceiling light Fixture Height: 225 Standard Packaging Box: 1 Net Weight (Kg): 11 Lamp: G9 LED 4 W x 8 L W D H 430 430 225




#### JES-CHR-MX81364B

Description: 4 Light star shape glass tube with chrome finishing ceiling light Fixture Height: 225 Standard Packaging Box: 1 Net Weight (Kg): 5.5 Lamp: G9 LED 4 W x 4 L W D H 350 225



#### JES-CHR-MX81364A

Description: 4 Light star shape glass tube with chrome finishing ceiling light Fixture Height: 225 Standard Packaging Box: 1 Net Weight (Kg): 7 Lamp: G9 LED 4 W x 4 L W D H 330 330 225



Height Adjustable



#### KCH-RDG-MD501001512C

Description: 12 Light aluminium curved strips with rose gold finishing pendant Fixture Height: 560 Standard Packaging Box: 1 Net Weight (Kg): 5.2 Lamp: G9 LED 4 W x 12 L W D H 560 1200

Height Adjustable



#### KCH-STC-MD501001512B

Description: 12 Light aluminium curved strips with silver finishing pendant Fixture Height: 650 Standard Packaging Box: 1 Net Weight (Kg): 6.5 Lamp: G9 Bulb 4 W x 12 L W D H 650 1300 Height Adjustable



#### KCH-WTC-MD501001512B

Description: 12 Light aluminium curved strips with white finishing pendant Fixture Height: 650 Standard Packaging Box: 1 Net Weight (Kg): 6.5 Lamp: G9 LED 4 W x 12 L W D H 650 1300



Height Adjustable

#### KCH-BCH-MD501001512B

Description: 12 Light aluminium curved strips with black finishing pendant Fixture Height: 650 Standard Packaging Box: 1 Net Weight (Kg): 6.5 Lamp: G9 LED 4 W x 12 L W D H 650 1300

#### KCH-BLC-MX809812A

Description: 12 Light meta swan with black finishing ceiling light Available in: Black / Red / White / Matt Gold / Chrome Fixture Height: 620 Standard Packaging Box: 1 Net Weight (Kg): 9.5 Lamp: G4 Bulb 20 W x 12 L W D H 710 620



#### KCH-CHR-MD809824A

Ceiling Lights


Description: 24 Light meta swan with chrome finishing chandelier Available in: Black / Matt Gold / Chrome Fixture Height: 1500 Standard Packaging Box: 1 Net Weight (Kg): 21.5 Lamp: G4 Bulb 20 W x 24 L W D H 1100 1500

### KCH-GLD-MX809818A

Description: 18 Light meta swan with gold finishing ceiling light Available in: Black / Red / White / Matt Gold / Chrome Fixture Height: 780 Standard Packaging Box: 1 Net Weight (Kg): 18 Lamp: G4 Bulb 20 W x 18 L W D H 860 780

#### KCH-WHT-MX809818A

Description: 18 Light meta swan with white finishing ceiling light Available in: Black / Red / White Matt Gold / Chrome Fixture Height: 780 Standard Packaging Box: 1 Net Weight (Kg): 18 Lamp: G4 Bulb 20 W x 18 L W D H 860 780





#### KCH-GLD-MD809836A

Description: 36 Light meta swan with gold finishing chandelier Available in: Black / Red / White / Matt Gold / Chrome Fixture Height: 2400 Standard Packaging Box: 1 Net Weight (Kg): 28 Lamp: G4 Bulb 20 W x 36 L W D H





#### STL-BLK-SL1027S400 Description: 1 Light black hemp

rope ball pendant Fixture Height: 400 Standard Packaging Box: 1 Net Weight (Kg): 1.2 Lamp: E27 LED Filament 6 W x 1 L W D H 400 1200

All items are available in brown & white colour complete family



STL-BLK-SL1027S600 Description: 1 Light black hemp rope ball pendant Fixture Height: 600 Standard Packaging Box: 1 Net Weight (Kg): 1.5 Lamp: E27 LED Filament 6 W x 1 L W D H 600 1200

All items are available in brown & white colour complete family

All dimensions are in mm



#### STL-BLK-SL1027S800

Description: 1 Light black hemp rope ball pendant Fixture Height: 800 Standard Packaging Box: 1 Net Weight (Kg): 4.2 Lamp: E27 LED Filament 6 W x 1 L W D H 800 1300

All items are available in brown & white colour complete family

STL-CHR-SL1128S Description: 9 Light black fabric shade with chrome finishing pendant Fixture Height: 970 Standard Packaging Box: 1 Net Weight (Kg): 23 Lamp: E27 LED 7 W x 9 L W D H 1030 1750

#### KCH-CHR-MD150330028A

Description: 8 Light champagne opal glass with chrome finish chandelier Fixture Height: 620 Standard Packaging Box: 1 Net Weight (Kg): 12 Lamp: E14 LED 4 W x 8 L W D H 730 1200

15

#### KCH-CHR-MD1503300212

Description: 12 Light champagne opal glass with chrome finish chandelier Fixture Height: 620 Standard Packaging Box: 1 Net Weight (Kg): 15 Lamp: E14 LED 4 W x 12 L W D H 830 1200

All dimensions are in mm
164 COMPLETE LED LIGHTING SOLUTIONS



#### KCH-CHR-MD150330026A

Description: 6 Light champagne opal glass with chrome finish chandelier Fixture Height: 620 Standard Packaging Box: 1 Net Weight (Kg): 7 Lamp: E14 LED 4 W x 6 L W D H 600 1200



#### KCH-WTC-MD1503000818

Description: 18 Light white pitcher glass with white finishing chandelier Fixture Height: 380 Standard Packaging Box: 1 Net Weight (Kg): 18 Lamp: E14 LED 4 W x 18 L W D H 1050 1200



#### KCH-WTC-MD150300088A

Description: 8 Light white pitcher glass with white finishing chandelier Fixture Height: 380 Standard Packaging Box: 1 Net Weight (Kg): 6 Lamp: E14 LED 4 W x 8 L W D H 760 1200



#### KCH-WTC-MX150300086A

Description: 6 Light white pitcher glass with white finishing chandelier Fixture Height: 380 Standard Packaging Box: 1 Net Weight (Kg): 5 Lamp: E14 LED 4 W x 6 L W D H 430 600

#### KCH-WTC-MX1503000812

Description: 12 Light white pitcher glass with white finishing chandelier Fixture Height: 380 Standard Packaging Box: 1 Net Weight (Kg): 10 Lamp: E14 LED 4 W x 12 L W D H 870 490



Description: 8 Light frosted glass with chrome finishing chandelier Fixture Height: 540 Standard Packaging Box: 1 Net Weight (Kg): 6.5 Lamp: E14 LED 4 W x 8 L W D H 700 1200 Description: 3 Light frosted glass, aluminium with black & gold finishing pendant Fixture Height: 50 Standard Packaging Box: 1 Net Weight (Kg): 4.02 Lamp: E14 LED 4 W x 3 L W D H 350 1100



#### JNL-COP-MD150031251C

Description: 1 Light copper glass with copper finishing pendant Fixture Height: 270 Standard Packaging Box: 8 Net Weight (Kg): 0.9 Lamp: E27 LED 9 W x 1 L W D H 100 1200



#### JNL-CHR-MD160020053B

Description: 3 Light clear glass, rose gold mesh with chrome finishing pendant Fixture Height: 260-750 Standard Packaging Box: 1 Net Weight (Kg): 3.5 Lamp: G9 LED 4 W x 3 L W D H 300 1200



#### JNL-CHR-MD160020051C

Description: 1 Light clear glass, rose gold mesh with chrome finishing pendant Fixture Height: 200 Standard Packaging Box: 1 Net Weight (Kg): 1 Lamp: G9 LED 4 W x 1 L W D H 195 1200

### KCH-RDG-MD140030571C

Description: 1 Light PC globe diffuser with rose gold finishing pendant Fixture Height: 250 Standard Packaging Box: 1 Net Weight (Kg): 1.4 Lamp: E27 LED 7 W x 1 L W D H 200 1500





### KCH-CHR-MD150031291A

Description: 1 Light smoky glass with chrome finishing pendant Fixture Height: 240 Standard Packaging Box: 1 Net Weight (Kg): 1.2 Lamp: E27 LED 9 W x 1 L W D H 120 1200 JNL-CHR-MD150031291B

Description: 1 Light smoky glass with chrome finishing pendant Fixture Height: 260 Standard Packaging Box: 1 Net Weight (Kg): 1 Lamp: E27 LED 9 W x 1 L W D H 160 1200

4

#### JNL-COP-MD150031251B

Description: 1 Light copper glass with copper finishing pendant Fixture Height: 280 Standard Packaging Box: 1 Net Weight (Kg): 0.8 Lamp: E27 LED 9 W x 1 L W D H 130 1200

#### JNL-COP-MD150031251A

Description: 1 Light copper glass with copper finishing pendant Fixture Height: 220 Standard Packaging Box: 1 Net Weight (Kg): 0.6 Lamp: E27 LED 9 W x 1 L W D H 170 1300



#### STL-GRY-SL966S1

Description: 2 Light dark grey carbon steel pendant Fixture Height: 620 Standard Packaging Box: 1 Net Weight (Kg): 9.5 Lamp: E27 LED 9 W x 2 L W D H 510 615



STL-GLD-SL966S3 Description: 2 Light dark gold carbon steel pendant Fixture Height: 820 Standard Packaging Box: 1 Net Weight (Kg): 12.5 Lamp: E27 LED 9 W x 2 L W D H 750 810



#### STL-COP-SL1204S3

Description: 3 Light aluminium hexagon style with antique copper finishing pendant Fixture Height: 200 Standard Packaging Box: 1 Net Weight (Kg): 4.5 Lamp: E14 LED 4 W x 3 L W D H 500 210-2000



#### STL-COP-SL1204S14

Description: 14 Light aluminium hexagon style with antique copper finishing pendant Fixture Height: 200 Standard Packaging Box: 1 Net Weight (Kg): 21 Lamp: E14 LED 4 W x 14 L W D H 1474 410 2000



170 COMPLETE LED LIGHTING SOLUTIONS



#### JNL-BLK-SL00WCNIE27

Description: 1 Light bar with black finishing conical pendant Fixture Height: 380 Standard Packaging Box: 4 Net Weight (Kg): 1.3 Lamp: E27 LED Filament 6 W x 1 L W D H 300 1600



#### JNL-BLK-SL00WCYIE27 Description: 1 Light bar with black finishing cylindrical pendant Fixture Height: 230 Standard Packaging Box: 4 Net Weight (Kg): 2.4 Lamp: E27 LED Filament 6 W x 1 L W D H 220 1600



#### JNL-GRY-CL92931

Description: 1 Light cage type, antique green marble with antique finish ceiling light Fixture Height: 280 Standard Packaging Box: 2 Net Weight (Kg): 2.4 Lamp: E27 LED Filament 6 W x 1 L W D H 130 280

#### JNL-GRY-SL92931A

Description: 1 Light cage type, antique green marble with antique finish pendant Fixture Height: 1525 Standard Packaging Box: 2 Net Weight (Kg): 3.2 Lamp: E27 LED Filament 6 W x 1 L W D H 180 1525







All dimensions are in mm
172 COMPLETE LED LIGHTING SOLUTIONS



#### JNL-COP-SL180461A Description: 1 Light mesh shade with copper finishing pendant Fixture Height: 320 Standard Packaging Box: 4 Net Weight (Ka): 1.2

Net Weight (Kg): 1.2 Lamp: E27 Filament LED 6 W x 1 L W D H 130 1100



#### STL-BLK-SL1121S Description: 1 Light Black aluminium shade, inside gold finishing pendant Fixture Height: 480 Standard Packaging Box: 1 Net Weight (Kg): 5.25 Lamp: E27 LED 9 W x 1 L W D H 600 2000



#### STL-GLD-SL1133S

Description: 24 Light trumpet style with gold finishing pendant Fixture Height: 730 Standard Packaging Box: 1 Net Weight (Kg): 20 Lamp: E14 LED 4 W x 24 L W D H 1500 1400-2000



### STL-GLD-SL1133S1

Description: 24 Light trumpet style with gold finishing pendant Fixture Height: 730 Standard Packaging Box: 1 Net Weight (Kg): 12.5 Lamp: E14 LED 4 W x 24 L W D H 1080 1400~2000


JNL-BRS-MD150273871B Description: 1 Light clear glass with brass finishing pendant Fixture Height: 270 Standard Packaging Box: 1 Net Weight (Kg): 1.3 Lamp: E27 LED 7 W x 1

L W D H 200 1200

JNL-GRY-SL91301

Description: 1 Light mesh / ceramic with rusty finishing pendant Fixture Height: 280 Standard Packaging Box: 1 Net Weight (Kg): 4.6 Lamp: E27 LED Filament 6 W x 1 L W D H 210 210 1100





STL-COP-SL1162S2 Description: 14 Light aluminium pipe with copper finishing pendant Fixture Height: 320 Standard Packaging Box: 1 Net Weight (Kg): 33.2 Lamp: E14 LED 4 W x 14 L W D H 1720 300 2000



#### STL-COP-SL1162S3

Description: 37 Light aluminium pipe with copper finishing pendant Fixture Height: 750 Standard Packaging Box: 1 Net Weight (Kg): 44 Lamp: E14 LED 4 W x 37 L W D H 1050 2000-3000




STL-COP-SL1162S1 Description: 12 Light aluminium pipe with copper finishing pendant Fixture Height: 320 Standard Packaging Box: 1 Net Weight (Kg): 26 Lamp: E14 LED 4 W x 12 L W D H 950 2000



#### STL-COP-SL1162S7

Description: 89 Light aluminium pipe with copper finishing pendant Fixture Height: 1250 Standard Packaging Box: 1 Net Weight (Kg): 164 Lamp: E14 LED 4 W x 89 L W D H 1950 2000-3000






#### STL-GLD-SL1153S10

Description: 10 Light frosted glass with matt gold finishing pendant Fixture Height: 300-600 Standard Packaging Box: 1 Net Weight (Kg): 8.8 Lamp: G9 LED 4 W x 10 L W D H 1100 1400



#### JIG-BRS-SL1260S200 Description: 1 Light clear glass with brushed brass finishing pendant Fixture Height: 420 Standard Packaging Box: 1 Net Weight (Kg): 0.9 Lamp: G4 LED 3 W x 1 L W D H 200 420-2000



#### STL-GLD-SL1153S14

Description: 14 Light frosted glass with matt gold finishing pendant Fixture Height: 500-1000 Standard Packaging Box: 1 Net Weight (Kg): 13.7 Lamp: G9 LED 4 W x 14 L W D H 1700 1400



#### JIG-BRS-SL1260S250

Description: 1 Light clear glass with brushed brass finishing pendant Fixture Height: 500 Standard Packaging Box: 1 Net Weight (Kg): 1.2 Lamp: G4 LED 3 W x 1 L W D H 250 520-2000



#### JIG-BRS-SL1260SX3

Description: 3 Light clear glass with brushed brass finishing chandelier Fixture Height: 600 Standard Packaging Box: 1 Net Weight (Kg): 4.5 Lamp: G4 LED 3 W x 3 L W D H 700 700-2000



#### JIG-BRS-SL1260S1

Description: 6 Light clear glass with brushed brass finishing chandelier Fixture Height: 600 Standard Packaging Box: 1 Net Weight (Kg): 6.43 Lamp: G4 LED 3 W x 6 L W D H 960 650 900-1800



#### JIG-BRS-SL1260S2

Description: 6 Light clear glass with brushed brass finishing chandelier Fixture Height: 620 Standard Packaging Box: 1 Net Weight (Kg): 7.68 Lamp: G4 LED 3 W x 6 L W D H 1300 900 1000-1900



#### JIG-BRS-SL1260S3 Description: 8 Light clear glass with brushed brass finishing chandelier Fixture Height: 1000 Standard Packaging Box: 1 Net Weight (Kg): 11.40 Lamp: G4 LED 3 W x 8 L W D H 2000 1140 950-1900



#### STL-ABS-SLSF9001S1

Description: 1 Light diamond cut style glass with antique brass finishing pendant Fixture Height: 460 Standard Packaging Box: 1 Net Weight (Kg): 1 Lamp: G4 LED 3 W x 2 L W D H 60 500





#### STL-GLD-SL1219SX

Description: 1 Light clear glass with matt gold bronze finishing pendant L W D H

Fixture Height: 400 Standard Packaging Box: 1 Net Weight (Kg): 3.6 Lamp: E27 LED 4 W x 1 300 165 250 2000

#### STL-GLD-SL1219S

Description: 1 Light clear glass with matt gold bronze finishing pendant Fixture Height: 400 Standard Packaging Box: 1 Net Weight (Kg): 5.1 Lamp: E27 LED 4 W x 1 L W D H 300 165 185 2000

(Adjustable)





#### STL-GRY-SLSM2329S

Description: 1 Light smokey glass with chrome finishing pendant Fixture Height: 250 Standard Packaging Box: 1 Net Weight (Kg): 1.5 Lamp: G9 LED 4 W x 1 L W D H 80 1200



STL-ABS-SL1217S2 Description: 1 Light copper plated glass with copper finish pendant Fixture Height: 560 Standard Packaging Box: 1 Net Weight (Kg): 3.5 Lamp: E27 LED 9 W x 1 L W D H

350 2000



#### STL-COP-SL1217S

Description: 1 Light copper plated glass with copper finish pendant Fixture Height: 560 Standard Packaging Box: 1 Net Weight (Kg): 1.6 Lamp: E27 LED 9 W x 1 L W D H 190 2000





#### JFO-COP-SLPEA089AE27

Description: 1 Light aluminium globe shape with copper finishing pendant Fixture Height: 400 Standard Packaging Box: 1 Net Weight (Kg): 1.7 Lamp: E27 LED 9 W x 1 L W D H 400 1200

All dimensions are in mm

 182
 COMPLETE LED LIGHTING SOLUTIONS

### JFO-BLK-SLPEA089AE27

Description: 1 Light aluminium globe shape with gun black finishing pendant Fixture Height: 400 Standard Packaging Box: 1 Net Weight (Kg): 1.7 Lamp: E27 LED 9 W x 1 L W D H 400 1200



#### STL-ANT-SL1137S1

Description: 1 Light aluminium with antique finishing pendant Fixture Height: 150 Standard Packaging Box: 1 Net Weight (Kg): 0.5 Lamp: E27 LED 5 W x 1 L W D H 125 2000



#### STL-ANT-SL1131S1

Description: 1 Light aluminium with antique finishing pendant Fixture Height: 300 Standard Packaging Box: 1 Net Weight (Kg): 0.45 Lamp: E27 LED 5 W x 1 L W D H 138 2000



CHL-BLK-11086X3 Description: 3 Light black powder coated pendant Fixture Height: 305 Standard Packaging Box: 1 Net Weight (Kg): 1.5 Lamp: LED 3 W x 3 In-built L W D H 510 65 1150






#### CHL-BLK-11086

Description: 1 Light black powder coated pendant Fixture Height: 300 Standard Packaging Box: 12 Net Weight (Kg): 0.6 Lamp: LED 3 W x 1 In-built L W D H 25 1150



#### STL-COP-SL1131S2

Description: 1 Light aluminium with red copper finishing pendant Fixture Height: 150 Standard Packaging Box: 1 Net Weight (Kg): 0.9 Lamp: E27 LED 5 W x 1 L W D H 192 2000



JCN-BLK-MDRD1762628 Description: 28 Heads glass pendant with black finish Fixture Height: 450 Standard Packaging Box: 1 Net Weight (Kg): 1200 Lamp: E14 LED 4 W x 28 L W D H 3000 200 450



All dimensions are in mm

 186
 COMPLETE LED LIGHTING SOLUTIONS



#### JFO-BLK-SLHPP0414E27

Description: 1 Light aluminium industrial style with sanded black finishing pendant Fixture Height: 380 Standard Packaging Box: 1 Net Weight (Kg): 2.8 Lamp: E27 LED 9 W x 1 L W D H 380 1200



#### JFO-WHT-SLPEAT31330E27

Description: 1 Light aluminum with water printing of marble pattern pendant Fixture Height: 420 Standard Packaging Box: 1 Net Weight (Kg): 1.2 Lamp: E27 LED 9 W x 1 L W D H 300 1200



#### JFO-BRN-SLPEA299E27

Description: 1 Light aluminum with coffee painted finishing pendant Fixture Height: 310 Standard Packaging Box: 1 Net Weight (Kg): 1 Lamp: E27 LED 9 W x 1 L W D H 320 1200



#### JFO-BLK-SLPEA138E27

Description: 1 Light aluminum with sanded black painted finishing pendant Fixture Height: 370 Standard Packaging Box: 1 Net Weight (Kg): 1.2 Lamp: E27 LED 9 W x 1 L W D H 350 1200



#### JFO-NKL-SLPEAW15833E27

Description: 1 Light aluminum, brown wood with satin nickel finishing pendant Fixture Height: 400 Standard Packaging Box: 1 Net Weight (Kg): 2 Lamp: E27 LED 9 W x 1 L W D H 330 1200

#### JFO-COP-SLHPPA0414DE27

Description: 1 Light aluminium industrial style, frosted glass with copper finishing pendant Fixture Height: 430 Standard Packaging Box: 1 Net Weight (Kg): 2.4 Lamp: E27 LED 9 W x 1 L W D H 400 1200



#### JFO-NAW-SLPEW00833E27 Description: 1 Light bamboo wood

with natural wooden finishing pendant Fixture Height: 230 Standard Packaging Box: 1 Net Weight (Kg): 1 Lamp: E27 LED 9 W x 1 L W D H 330 1200



#### JFO-NAW-SLPEW00435E27

Description: 1 Light bamboo wood with natural wooden finishing pendant Fixture Height: 430 Standard Packaging Box: 1 Net Weight (Kg): 1.2 Lamp: E27 LED 9 W x 1 L W D H 350 1200

All dimensions are in mm

 188
 COMPLETE LED LIGHTING SOLUTIONS



#### JFO-NAW-SLPEW00445E27

Description: 1 Light bamboo wood with natural wooden finishing pendant Fixture Height: 530 Standard Packaging Box: 1 Net Weight (Kg): 2 Lamp: E27 LED 9 W x 1 L W D H 450 1200



#### JFO-NAW-SLPEW00735E27

Description: 1 Light bamboo wood with natural wooden finishing pendant Fixture Height: 340 Standard Packaging Box: 1 Net Weight (Kg): 1 Lamp: E27 LED 9 W x 1 L W D H 350 1200



#### JFO-NAW-SLPEW00325E27

Description: 1 Light bamboo wood with natural wooden finishing pendant Fixture Height: 450 Standard Packaging Box: 1 Net Weight (Kg): 1.5 Lamp: E27 LED 9 W x 1 L W D H 250 1200



#### JES-BLK-CHL0006PRE14

Description: 6 Light black glass with black crystal chandelier Fixture Height: 900 Standard Packaging Box: 1 Net Weight (Kg): 6.1 Lamp: E14 LED 4 W x 6 L W D H 580 1200



#### JES-AMB-CHL0006SYE14

Description: 6 Light honey glass with gold finish chandelier Fixture Height: 900 Standard Packaging Box: 1 Net Weight (Kg): 5 Lamp: E14 LED 4 W x 6 L W D H 770 1200

All dimensions are in mm
190 COMPLETE LED LIGHTING SOLUTIONS





#### JNL-WHT-SLPEA034AE27

Description: 1 Light aluminium with white powder finishing pendant Fixture Height: 260 Standard Packaging Box: 1 Net Weight (Kg): 0.8 Lamp: E27 LED 9 W x 1 L W D H 350 1200

Description: 6 Light clear glass with gold finish chandelier Fixture Height: 1100 Standard Packaging Box: 1 Net Weight (Kg): 10.5 Lamp: E27 LED 4 W x 6 L W D H 755 1400



# Floor Lamps

Add a unique touch to your décor with our exciting range of floor lights that not only add functional elegance to the room, but also become conversation pieces for your visitors.



#### STL-WHT-FLSM2155F

Description: 1 Light conical black shade with carbon powder finishing Fixture Height: 2070 Standard Packaging Box: 1 Net Weight (Kg): 70 Lamp: E27 LED 14 W x 1 L W D H 1150 2070

#### STL-BLK-FL902F2

Description: 1 Light conical black shade with carbon powder finishing Fixture Height: 1800 Standard Packaging Box: 1 Net Weight (Kg): 45 Lamp: E27 LED 14 W x 1 L W D H 2035 600 1800



#### STL-WHT-FL306F

Description: 1 Light aluminium shade with white painted finishing floor lamp Fixture Height: 1765 Standard Packaging Box: 1 Net Weight (Kg): 12.5 Lamp: E27 LED 14 W x 1 L W D H 500 1765

#### STL-BLK-FL306F

Lamp: E27 LED 14 W x 1 L W D H

1780

2330

Description: 1 Light aluminium shade with black painted finishing floor lamp Fixture Height: 1765 Standard Packaging Box: 1 Net Weight (Kg): 12.5 Lamp: E27 LED 14 W x 1 L W D H 500 1765



Fixture Height: 1850 Standard Packaging Box: 1 Net Weight (Kg): 16 Lamp: E27 LED 14 W x 1

#### STL-WNG-FL1092FA

Description: 1 Light diffuser glass with wood, alloy zinc floor lamp Fixture Height: 1850 Standard Packaging Box: 1 Net Weight (Kg): 35 Lamp: E27 LED 14 W x 1 L W D 850 800 Н 1850





#### STL-GRY-FL737F

Description: 1 Light grey fabric shade pattern with black powder coated floor lamp Fixture Height: 1900-2400 Standard Packaging Box: 1 Net Weight (Kg): 8.4 Lamp: E27 LED 9 W x 1 L W D H 935 860 1900-2400



#### KPT-CHR-ML49061A

Description: 1 Light opal glass shade with marble base & chrome finishing floor lamp Fixture Height: 1900 Standard Packaging Box: 1 Net Weight (Kg): 20 Lamp: E27 LED 14 W x 1 L W D H 1250 300 1900



#### STL-BLK-FL737F

Description: 1 Light black fabric shade with black powder coated floor lamp Fixture Height: 1900-2400 Standard Packaging Box: 1 Net Weight (Kg): 14 Height: Adjustable Lamp: E27 LED 9 W x 1 L W H 935 860 1900-2400



#### STL-BRS-FL1260F

Description: 2 Light clear glass withbrushed brass finishing floor lampFixture Height: --Standard Packaging Box: 1Net Weight (Kg): 8Lamp: G4 LED 3 W x 2LWDH11002501220-1880

#### STL-BLK-FL1029F Description: 1 Light PVC shade

cheval floor lamp with black finishing Fixture Height: 2550 Standard Packaging Box: 1 Net Weight (Kg): 52 Lamp: E27 LED 14 W x 1 L W D H 2400 550 2550

#### STL-WHT-FL1029F

Description: 1 Light PVC shadecheval floor lamp with white finishingFixture Height: 2550Standard Packaging Box: 1Net Weight (Kg): 52Lamp: E27 LED 14 W x 1LWDH2400550





#### STL-WHT-FL1213F Description:

3 Light metal half dome with antique white finishing floor lamp Fixture Height: 1680 Standard Packaging Box: 1 Net Weight (Kg): 30 Lamp: G9 LED 4 W x 3 L W D H 455 1680



#### STL-GLD-FL1133F

Description: 8 Light trumpet style with gold finishing floor lamp Fixture Height: 1700 Standard Packaging Box: 1 Net Weight (Kg): 16 Lamp: E14 LED 4 W x 8 L W D H 650 1700



#### STL-WHT-FL1174F

Description: 3 Light frosted glass with antique white finishing floor lamp Fixture Height: 1400 Standard Packaging Box: 1 Net Weight (Kg): 16.2 Lamp: E14 LED 4 W x 3 L W H 610 350 1400

#### STL-BLK-FL1174F

Description: 3 Light frosted glass with black & gold finishing floor lamp Fixture Height: 1400 Standard Packaging Box: 1 Net Weight (Kg): 16.2 Lamp: E14 LED 4 W x 3 L W D H 610 350 1400





All dimensions are in mm
200 COMPLETE LED LIGHTING SOLUTIONS





For the demanding needs of task lighting around your work spaces and your bedside, Jaquar Lighting's table lamps span a wide range of design influences – from the classic to the ultra contemporary.



## STL-GLD-TL1018T2

**Description:** 1 Light PVC shade with gold finishing table lamp Fixture Height: 750 Standard Packaging Box: 1 Net Weight (Kg): 3.26 Lamp: E27 LED 7 W x 1 L W D Н 230 750





#### JIG-BLK-TL1018T2

Description: 1 Light fabric black shade finishing table lamp Fixture Height: 750 Standard Packaging Box: 1 Net Weight (Kg): 3.26 Lamp: E27 LED 7 W x 1 L W D H 230 750



#### STL-WHT-TL765T

Description: 1 Light strip fabric shade with chrome finishing table lamp Fixture Height: 850 Standard Packaging Box: 1 Net Weight (Kg): 4.5 Lamp: E27 LED 14 W x 1 L W D H 370 850



#### STL-CHR-TL1018T2

Description: 1 Light PVC shade with chrome finishing table lamp Fixture Height: 750 Standard Packaging Box: 1 Net Weight (Kg): 3.26 Lamp: E27 LED 7 W x 1 L W D H 230 750





#### STL-CHR-TL1128T

Description: 3 Light black fabric shade with chrome finishing table lamp Fixture Height: 875 Standard Packaging Box: 1 Net Weight (Kg): 13 Lamp: E27 LED 5 W x 3 L W D H 490 875



#### STL-BLK-TL306T

Description: 1 Light aluminium shade with black painted finishing table lamp Fixture Height: 575 Standard Packaging Box: 1 Net Weight (Kg): 3.1 Lamp: E27 LED 9 W x 1 L W D H 390 575



////

#### STL-BLK-TL1093T

Description: 1 Light leather shade with black wooden base table lamp Fixture Height: 833 Standard Packaging Box: 1 Net Weight (Kg): 3.7 Lamp: E27 LED 9 W x 1 L W D H 400 833



#### STL-CHR-TL1211T Description: 1 Light trumpet style, black base with gold finishing table lamp Fixture Height: 695 Standard Packaging Box: 1 Net Weight (Kg): 11 Lamp: G9 LED 4 W x 6 L W D H

250 695

STL-BLE Description glass, alum gold finishi Fixture He Standard I Net Weigh Lamp: E14 L W

STL-BLK-TL1174T Description: 3 Light frosted glass, aluminium with black and gold finishing table lamp Fixture Height: 430 Standard Packaging Box: 1 Net Weight (Kg): 3.18 Lamp: E14 LED 4 W x 3 L W D H 350 430



STL-WHT-TL1174T Description: 3 Light frosted glass, aluminium with antique white finishing table lamp Fixture Height: 430 Standard Packaging Box: 1 Net Weight (Kg): 3.18 Lamp: E14 LED 4 W x 3 L W D H 350 430



#### KTL-CHR-MT49061A

Description: 1 Light opal glass, marble base with chrome finishing table lamp Fixture Height: 520 Standard Packaging Box: 1 Net Weight (Kg): 2 Lamp: E27 LED 9 W x 1 L W D H 425 130 520



#### STL-COP-TLKS6308T

Description: 1 Light opal glass with copper finishing table lamp Fixture Height: 250 Standard Packaging Box: --Net Weight (Kg): 2 Lamp: G9 LED 4 W x 1 L W D H 180 250



#### JNL-BRS-TL1300H

Description: 1 Light fabric shade with hammered pattern base brash finishing table lamp Fixture Height: 460 Standard Packaging Box: 4 Net Weight (Kg): 0.9 Lamp: E27 7 W x 1 L W D H 350 460





#### JNL-CHR-TL400WOS

Description: 1 Light fabric shade with nickel finishing table lamp Fixture Height: 470 Standard Packaging Box: 4 Net Weight (Kg): 0.75 Lamp: E27 LED 7 W x 1 L W D H 300 470



#### STL-WHT-TL1213T

Description: 3 Light metal half dome with antique white finishing table lamp Fixture Height: 600 Standard Packaging Box: 1 Net Weight (Kg): 9.9 Lamp: G9 LED 4 W x 3 L W D H 305 600



JNL-WNT-TLHPWODE27

Description: 1 Light fabric shade with wooden horizontal pyramid base table lamp Fixture Height: 650 Standard Packaging Box: 4 Net Weight (Kg): 1.5 Lamp: E27 LED 7 W x 1 L W D H 300 650



#### JNL-WNT-TLVPWODE27

Description: 1 Light fabric shade with wooden vertical pyramid base table lamp Fixture Height: 650 Standard Packaging Box: 4 Net Weight (Kg): 1.3 Lamp: E27 LED 7 W x 1 L W D H 300 650





#### KCH-CHR-MT160275451B

Description: 1 Light fabric shade with chrome finishing table lamp Fixture Height: 610 Standard Packaging Box: 1 Net Weight (Kg): 2 Lamp: E27 LED 9 W x 1 L W D H 350 610



#### KCH-CHR-MT160275451A

Description: 1 Light fabric shade with chrome finishing table lamp Fixture Height: 680 Standard Packaging Box: 1 Net Weight (Kg): 2.65 Lamp: E27 LED 9 W x 1 L W D H 380 680



#### KCH-CHR-MT170275021L

Description: 1 Light fabric shade, red leather with chrome finishing table lamp Fixture Height: 950 Standard Packaging Box: 1 Net Weight (Kg): 2.6 Lamp: E27 LED 9 W x 1 L W D H 355 950



### KCH-CHR-MT170275041C

Description: 1 Light PVC shade, red leather with chrome finishing table lamp Fixture Height: 880 Standard Packaging Box: 1 Net Weight (Kg): 3.2 Lamp: E27 LED 9 W x 1 L W D H 355 880



#### KCH-CHR-MT1702750711

Description: 1 Light fabric shade, crystal with chrome finishing table lamp Fixture Height: 670 Standard Packaging Box: 1 Net Weight (Kg): 4.2 Lamp: E27 LED 9 W x 1 L W D H 410 670



JCN-WHT-TBL00954004

shade clear crystal with chrome





KCH-ABR-MT170275071J Description: 1 Light fabric shade, crystal with antique brass finishing table lamp Fixture Height: 710 Standard Packaging Box: 1 Net Weight (Kg): 4.2 Lamp: E27 LED 9 W x 1 LW D H 380 710

All dimensions are in mm 212 COMPLETE LED LIGHTING SOLUTIONS





#### KCH-CHR-MT170275071J

Description: 1 Light fabric shade, crystal with chrome finishing table lamp Fixture Height: 670 Standard Packaging Box: 1 Net Weight (Kg): 2.75 Lamp: E27 LED 9 W x 1 L W D H 410 670



#### JCN-GLD-TBL00280281T Description: 1 Light fabric shade, crystal base with gold finishing table lamp Fixture Height: 360 Standard Packaging Box: 1 Net Weight (Kg): 5 Lamp: E27 LED 7 W x 1 L W D H 220 360



#### JCN-WHT-TBL00954001

Description: 1 Light fabric shade with crystal base table lamp Fixture Height: 760 Standard Packaging Box: 1 Net Weight (Kg): 7 Lamp: E27 LED 7 W x 1 L W D H 380 760



#### JCN-WHT-TBL00954005

Description: 1 Light fabric shade, clear crystal with chrome finishing table lamp Fixture Height: 730 Standard Packaging Box: 1 Net Weight (Kg): 9 Lamp: E27 LED 7 W x 1 L W D H 410 730



#### JCN-GLD-TBL0017616T

Description: 1 Light green ceramic, fabric shade with gold finishing table lamp Fixture Height: 690 Standard Packaging Box: 1 Net Weight (Kg): 5.5 Lamp: E27 LED 7 W x 1 L W D H 400 690





JCN-BRN-TBL00280381T Description: 1 Light fabric shade, mouth blown glass with brown finishing table lamp Fixture Height: 650 Standard Packaging Box: 1 Net Weight (Kg): 6 Lamp: E27 LED 7 W x 1 LW D H 470 650

All dimensions are in mm 214 COMPLETE LED LIGHTING SOLUTIONS





#### JCN-BRN-TBL00280341T

Description: 1 Light fabric shade, mouth blown glass with brown finishing table lamp Fixture Height: 654 Standard Packaging Box: 1 Net Weight (Kg): 6 Lamp: E27 LED 7 W x 1 L W D H 460 654





#### STL-GRY-TL1187T1

STL-RED-TL1187T2 Description: 1 Light smoky grey glass with chrome finishing table lamp Fixture Height: 850 Standard Packaging Box: 1 Net Weight (Kg): 8.5 Lamp: E27 LED 14 W x 1 L W D H 509 850




#### JIG-BRS-TL1260T

Description: 2 Light clear glass with brushed brass table lamp Fixture Height: 510 Standard Packaging Box: 1 Net Weight (Kg): 3 Lamp: G4 LED 3 W x 2 L W D H 400 200 360-510



#### JNL-AGR-TLight89871

Description: 1 Light tap style with antique green finishing table lamp Fixture Height: 440 Standard Packaging Box: 1 Net Weight (Kg): 2.5 Lamp: E27 LED 4 W x 1 L W D H 200 440



# Wall Lights

Take a look at the brilliant new ideas from Jaquar Lighting for ambient room illumination. From timeless elegance to quirky design and artful expression, there's a wall light for every need here.



KWB-RDG-MB80983A Description: 3 Light meta swan shape with red finishing wall lamp **Fixture Height:** 470 Standard Packaging Box: 1 Net Weight (Kg): 2 Lamp: G4 Bulb 20 W x 3 L W D H 228 425 470

# Wall Lights



# KWB-CHR-MB80985A

Description: 5 Light meta swan shape with chrome finishing wall lamp Fixture Height: 850 Standard Packaging Box: 1 Net Weight (Kg): 3 Lamp: G4 Bulb 20 W x 5 L W D H 230 460 850



#### KWB-CHR-MB80471A

Description: 1 Light cone shaped chrome finishing wall lamp Fixture Height: 310 Standard Packaging Box: 6 Net Weight (Kg): 0.8 Lamp: E14 LED 4 W x 1 L W D H 280 110 310



### WBR-CHR-MB12021181A

Description: 1 Light ivory fabric shade with chrome finishing wall lamp Fixture Height: 472 Standard Packaging Box: 2 Net Weight (Kg): 1.5 Lamp: E14 LED 4 W x 1 L W D H 238 140 472



# **KWB-CHR-MB12021201A Description:** 1 Light ivory fabric shade

with chrome finishing wall lamp Fixture Height: 205 Standard Packaging Box: 1 Net Weight (Kg): 2 Lamp: E14 LED 4 W x 1 L W D H 155 280 205





# WBR-CHR-MB11002351B

Description: 1 Light aluminium mesh with clear glass, chrome finishing wall lamp Fixture Height: 160 Standard Packaging Box: 8 Net Weight (Kg): 1.0 Lamp: G9 Bulb 40 W x 1 L W D H 150 160 160



#### JIG-BRS-WL1260W Description: 1 Light clear glass with brushed brass wall lamp Fixture Height: 370 Standard Packaging Box: 1 Net Weight (Kg): 0.9 Lamp: G4 LED 3 W x 1 L W D H 150 215 370

# KWB-WTC-MB150300081A

Description: 1 Light white pitcher glass with white finishing wall lamp Fixture Height: 300 Standard Packaging Box: 1 Net Weight (Kg): 0.9 Lamp: E14 LED 4 W x 1 L W D H 280 150 300



# KWB-WTC-MB150300082A

Description: 2 Light white pitcher glass with white finishing wall lamp Fixture Height: 250 Standard Packaging Box: 1 Net Weight (Kg): 2.5 Lamp: E14 LED 4 W x 2 L W D H 280 440 250

# Wall Lights



# STL-WHT-WL688WS

Description: 1 Light fabric shade with aluminium finishing wall lamp Fixture Height: 326 Standard Packaging Box: 1 Net Weight (Kg): 1.5 Lamp: E27 LED 9 W x 1 L W D H 180 278 326

# STL-WHT-WL688W1

Description: 1 Light fabric shade with aluminium finishing wall lamp Fixture Height: 355 Standard Packaging Box: 1 Net Weight (Kg): 1.2 Lamp: E27 LED 9 W x 1 L W D H 240 374 355



# STL-COP-WL1162W

Description: 1 Light aluminium pipe with copper finishing wall lamp Fixture Height: 300 Standard Packaging Box: 1 Net Weight (Kg): 2 Lamp: E14 LED 4 W x 1 L W D H 120 180 300



# STL-COP-WL1162W3

Description: 5 Light aluminium pipe with copper finishing wall lamp Fixture Height: 600 Standard Packaging Box: 1 Net Weight (Kg): 4 Lamp: E14 LED 4 W x 5 L W D H 420 210 600



# STL-CHR-WL1128W

Description: 2 Light black fabricshade with chrome finishing wall lampFixture Height: 785Standard Packaging Box: 1Net Weight (Kg): 4.2Lamp: E27 LED 5 W x 2LWDH470360785



#### JNL-CHR-MB140048C1E


Description: 1 Light opal glass with nickel finishing wall lamp Fixture Height: 310 Standard Packaging Box: 4 Net Weight (Kg): 0.8 Lamp: E27 LED 7 W x 1 L W D H 165 130 310





# STL-BLK-WL1174W

Description: 3 Light frosted glass, aluminium with black & gold finishing wall lamp Fixture Height: 360 Standard Packaging Box: 1 Net Weight (Kg): 3.9 Lamp: E14 LED 4 W x 3 L W D H 590 350 360



### STL-GLD-WL1153W2

Description: 2 Light frosted glass with matt gold finishing wall lamp Fixture Height: 860 Standard Packaging Box: 1 Net Weight (Kg): 1.8 Lamp: G9 LED 4 W x 2 L W D H 760 160 95



#### STL-GLD-WL1153W4

Description: 4 Light frosted glass with matt gold finishing wall lamp Fixture Height: 300 Standard Packaging Box: 1 Net Weight (Kg): 3.9 Lamp: G9 LED 4 W x 4 L W D H 870 760 300



# KCH-GLD-MB120010121A

Description: 1 Light clear glass with gold finishing wall lamp Fixture Height: 279 Standard Packaging Box: 1 Net Weight (Kg): 1.5 Lamp: E27 LED 7 W x 1 L W D H 152 177 279





# JNL-GRY-WL92931

Description: 1 Light cage type, antique green marble with antique finish wall lamp Fixture Height: 310 Standard Packaging Box: 4 Net Weight (Kg): 2.3 Lamp: E27 LED Filament 6 W x 1 L W D H 130 170 310



# JNL-GRY-WL92932

Description: 2 Light cage type, antique green marble with antique finish wall lamp Fixture Height: 310 Standard Packaging Box: 1 Net Weight (Kg): 4.5 Lamp: E27 LED Filament 6 W x 2 L W D H 340 160 310



# JNL-CHR-MB160275211A

Description: 1 Light frosted glass with chrome finishing wall lamp Fixture Height: 200 Standard Packaging Box: 1 Net Weight (Kg): 0.9 Lamp: E14 LED 4 W x 1 L W D H 120 160 200 

# JNL-CHR-MB160275212A

Description: 2 Light frosted glass with chrome finishing wall lamp Fixture Height: 200 Standard Packaging Box: 1 Net Weight (Kg): 2 Lamp: E14 LED 4 W x 2 L W D H 310 160 200





# KCH-CHR-MB150330021A

Description: 1 Light champagne opal glass with chrome finish wall lamp Fixture Height: 355 Standard Packaging Box: 1 Net Weight (Kg): 1.5 Lamp: E14 LED 4 W x 1 L W D H 210 330 355



### KCH-CHR-MB150330022A

Description: 2 Light champagne opal glass with chrome finish wall lamp Fixture Height: 355 Standard Packaging Box: 1 Net Weight (Kg): 2.2 Lamp: E14 LED 4 W x 2 L W D H 480 260 355



# JES-CHR-MB160275531B

Description: 1 Light opal glass with chrome finishing wall lamp Fixture Height: 235 Standard Packaging Box: 1 Net Weight (Kg): 0.6 Lamp: E14 LED 4 W x 1 L W D H 120 130 235



# KCH-CHR-MB160275532B

Description: 2 Light opal glass with chrome finishing wall lamp Fixture Height: 225 Standard Packaging Box: 4 Net Weight (Kg): 1 Lamp: E14 LED 4 W x 2 L W D H 270 130 225





# JNL-AGR-WL89873

Description: 3 Light tap style with<br/>antique green finishing wall lampFixture Height: 270Standard Packaging Box: 1Net Weight (Kg): 2.4Lamp: E27 LED Filament 6 W x 3LWH485150270



JNL-AGR-WL89872 Description: 2 Light tap style with antique green finishing wall lamp Fixture Height: 270 Standard Packaging Box: 1 Net Weight (Kg): 1.6 Lamp: E27 LED Filament 6 W x 2 L W D H 315 150 270

# Wall Lights



# JNL-AGR-WL89871

Description: 1 Light tap style with antique green finishing wall lamp Fixture Height: 270 Standard Packaging Box: 2 Net Weight (Kg): 0.6 Lamp: E27 LED Filament 6 W x 1 L W D H 130 167 270



JNL-GRY-WL91301 Description: 1 Light mesh / ceramic with rusty finish wall lamp Fixture Height: 340 Standard Packaging Box: 1 Net Weight (Kg): 3.5 Lamp: E27 LED Filament 6 W x 1 L W D H 210 150 340



# JNL-CHR-MB160275542A

Description: 2 Light opal glass with chrome finishing wall lamp Fixture Height: 240 Standard Packaging Box: 1 Net Weight (Kg): 1.2 Lamp: E27 LED 7 W x 2 L W D H 310 150 240



# JNL-CHR-MB160275541A

Description: 1 Light frosted glass with chrome finishing wall lamp Fixture Height: 250 Standard Packaging Box: 1 Net Weight (Kg): 0.65 Lamp: E27 LED 7 W x 1 L W D H 150 120 250





# JNL-CHR-WLRB0480SE27

Description: 1 Light opal glass with nickel finishing wall lamp Fixture Height: 270 Standard Packaging Box: 8 Net Weight (Kg): 0.58 Lamp: E27 LED 7 W x 1 L W D H 165 110 270



#### JNL-COP-WL180461B Description: 1 Light mesh with rusty finish wall lamp Fixture Height: 350

Fixture Height: 350 Standard Packaging Box: 8 Net Weight (Kg): 1.5 Lamp: E27 LED Filament 6 W x 1 L W D H 120 140 350



# JNL-CHR-WLSL55004E27

Description: 1 Light opal glass with nickel finishing wall lamp Fixture Height: 290 Standard Packaging Box: 8 Net Weight (Kg): 0.65 Lamp: E27 LED 7 W x 1 L W D H 120 210 290



# JNL-NKL-WLBPGG001E27

Description: 1 Light opal globeglass with nickel finishing wall lampFixture Height: 290Standard Packaging Box: 8Net Weight (Kg): 0.7Lamp: E27 LED 7 W x 1LWDH120210290





### JNL-NKL-WLBPGG002E27

Description: 2 Light opal globe glass with nickel finishing wall lamp Fixture Height: 290 Standard Packaging Box: 4 Net Weight (Kg): 1.45 Lamp: E27 LED 7 W x 2 L W D H 280 210 290



# JIG-COP-WL1204W1

Description: 1 Light aluminium hexagon style with antique copper finishing wall lamp Fixture Height: 160 Standard Packaging Box: 1 Net Weight (Kg): 1.2 Lamp: E14 LED 4 W x 1 L W D H 230 160 160



# JNL-BRG-WLCONESIE14

Description: 1 Light cone opal glass wall lamp Fixture Height: 280 Standard Packaging Box: 8 Net Weight (Kg): 0.7 Lamp: E14 LED 4 W x 1 L W D H 80 100 280



# JNL-BRG-WLCYLNDSIE14

Description: 1 Light cylindrical opal glass wall lamp Fixture Height: 300 Standard Packaging Box: 8 Net Weight (Kg): 0.6 Lamp: E14 LED 4 W x 1 L W D H 100 100 300

# Wall Lights





# JES-WHT-WL00002TAE14

 Description:
 2 Light clear glass

 with crystals wall lamp

 Fixture Height:
 360

 Standard Packaging Box:
 4

 Net Weight (Kg):
 2.1

 Lamp:
 E27 LED 5 W x 2

 L
 W
 D

 440
 160
 360

JNL-COG-WL1216W

Description: 1 Light copper glass with cognac finishing wall lamp Fixture Height: 550 Standard Packaging Box: 1 Net Weight (Kg): 1.5 Lamp: E14 LED 4 W x 1 L W D H 130 210 550









### WBR-CHR-MB12021191B

Description: 1 Light black fabric shade with chrome finishing wall lamp Fixture Height: 205 Standard Packaging Box: 1 Net Weight (Kg): 1.5 Lamp: E14 LED 4 W x 1 L W D H 240 280 205

# JES-AMB-WL00002SYE14

Description: 2 Light honey glass wall lamp Fixture Height: 225 Standard Packaging Box: 4 Net Weight (Kg): 1.9 Lamp: E14 LED 4 W x 2 L W D H 590 200 225



# WBR-CHR-MB12021192A

Description: 1 Light ivory fabric shade with chrome finishing wall lamp Fixture Height: 405 Standard Packaging Box: 1 Net Weight (Kg): 2 Lamp: E14 LED 4 W x 1 L W D H 155 280 405



# WBR-CHR-MB12021192B

Description: 1 Light black fabric shade with chrome finishing wall lamp Fixture Height: 405 Standard Packaging Box: 1 Net Weight (Kg): 1.5 Lamp: E14 LED 4 W x 1 L W D H 240 280 405





# WBR-SNS-5048X2

Description: 2 Light SS finish with 3 watt double neck LED wall lamp Fixture Height: 80 Standard Packaging Box: 1 Net Weight (Kg): 1 Lamp: LED 3 W x 2 (In-built) L W D H 228 100 110



WBR-SNS-5048Description: 1 Light SS finishwith 3 watt LED wall lampFixture Height: 125Standard Packaging Box: 1Net Weight (Kg): 0.6Lamp: LED 3 W x 1 (In-built)LWDH77100125



### STL-WHT-WL1174W

Description: 3 Light frosted glass, aluminium with antique white finishing wall lamp Fixture Height: 360 Standard Packaging Box: 1 Net Weight (Kg): 4.3 Lamp: E14 LED 4 W x 3 L W D H 590 350 360

All dimensions are in mm

# WBR-CHR-MB12021182A

Description: 1 Light ivory fabric shade with chrome finishing wall lamp Fixture Height: 480 Standard Packaging Box: 2 Net Weight (Kg): 1.5 Lamp: E14 LED 4 W x 1 L W D H 240 180 480





COMPLETE LED LIGHTING SOLUTIONS 233



# Bath (Aqua) Lights

Take bath décor beyond the ordinary with Jaquar's Aqualite range. Created specially for the bathroom, these are the perfect choice for withstanding the rigours of the bath environment.



# Bath (Aqua) Lights



# KWB-CHR-MB12021151A

Description: 1 Light opal glass with chrome finishing wall lamp Fixture Height: 280 Standard Packaging Box: 12 Net Weight (Kg): 0.900 Lamp: G9 LED 4 W x 1 L W D H 80 100 280



#### KWB-CHR-MB12021161A

Description: 1 Light opal glass with chrome finishing wall lamp Fixture Height: 145 Standard Packaging Box: 12 Net Weight (Kg): 0.600 Lamp: G9 LED 4 W x 1 L W D H 150 120 145



Description: 1 Light opal glass with chrome finishing wall lamp Fixture Height: 190 Standard Packaging Box: 1 Net Weight (Kg): 1.2 Lamp: G9 LED 4 W x 1 L W D H 170 130 190



KWB-CHR-MB12021321ADescription: 1 Light opal glasswith chrome finishing wall lampFixture Height: 270Standard Packaging Box: 12Net Weight (Kg): 1.5Lamp: E14 LED 4 W x 1LWDHeight: 270



# Bath (Aqua) Lights



# KWB-CHR-MB48011A

Description: 1 Light opal glasswith nickel finishing wall lampFixture Height: 235Standard Packaging Box: 12Net Weight (Kg): 0.8Lamp: G9 LED 4 W x 1LWDH8674235



Description: 1 Light matt opalglass with nickel finishing wall lampFixture Height: 260Standard Packaging Box: 12Net Weight (Kg): 1.5Lamp: E14 LED 4 W x 1LWDH8674260





# KWB-CHR-MB12021121A

Description: 1 Light opal glass with chrome finishing wall lamp Fixture Height: 265 Standard Packaging Box: 12 Net Weight (Kg): 0.600 Lamp: G9 LED 4 W x 1 L W D H 135 60 265





# KWB-CHR-MB48022A

Description: 2 Light opal glass with nickel finishing wall lamp Fixture Height: 105 Standard Packaging Box: 12 Net Weight (Kg): 1.0 Lamp: E14 LED 4 W x 2 L W D H 500 74 105 KWB-CHR-MB12021172A

Description: 2 Light opal glass with chrome finishing wall lamp Fixture Height: 63 Standard Packaging Box: 12 Net Weight (Kg): 1.3 Lamp: E14 LED 4 W x 2 L W D H 485 95 63





# KWB-CHR-MB48012D

Description: 2 Light clear glass with chrome finishing wall lamp, inside frosted glass Fixture Height: 400 Standard Packaging Box: 12 Net Weight (Kg): 1.3 Lamp: G9 LED 4 W x 2 L W D H 130 100 400

All dimensions are in mm
240 COMPLETE LED LIGHTING SOLUTIONS

# KWB-CHR-MB12021262A

Description: 2 Light opal glass with chrome finishing wall lamp Fixture Height: 60 Standard Packaging Box: 12 Net Weight (Kg): 0.6 Lamp: G9 LED 4 W x 2 L W D H 330 330 60











# Commercial Lights

Jaquar Lighting pushes the boundaries of commercial lighting to provide you with some of the most advanced, high performance, energy-saving lighting systems for the workplace. Choose from a wide variety of products to suit every application and meet the lighting needs of all kinds of commercial spaces, from workstations to conference rooms, reception areas to cabins, and small and large showrooms, workshops and factories.

APPLICATIONS HOTEL AND RESIDENCE STAIRCASE





AUDITORIUM

242 COMPLETE LED LIGHTING SOLUTIONS

OFFICE

# Content

# INDOOR COMMERCIAL LIGHTS

DOWNLIGHTS Neve Plus (Round) Neve Plus (Square) Nero Plus Round Areva (Round) Ensave Plus Neve Surface (Round) Neve Surface (Square)	247 247 248 249 249 250 250	Sauver Sauver (Surface) Sauver (Linear) Ultima (1 Ft × 1 Ft) Ultima (2 Ft × 2 Ft) Ultima (1 Ft × 4 Ft) Ultima Ultra Ultima Multicolour
Espot Nero Surface (Round) Nero Surface (Square	250 251 251	<b>BATTENS</b> Glaze Glaze (PC)
COB-DOWNLIGHTS Teny Estus Fixed Estus Swivel (Round)	252 252 253	Glaze Ultra (PC) T8 Retro Glaze Ultra Aluminium
Eris Fixed (Low Border Deep Recess) Eris Deep (Round) Eris Reflecto Eris Fixed	253 254 255 255 256	DESIGNERS LIGHTS Lattice Crystic Reflectorz DAZY- Trimless (Deep-Recessed)
PANELS Sauver	257	Eris Surface (Deep Surface) GU10 MR16



RETAIL LIGHTS	
Zoom Light	270
Multiple Zoom Light	271
Focus Light	272
Track Light	272
Accessories for Track Light	273
Epito	274
Cyno	274
Empha	274
Rene	275
Indoor Strip Light (24 V DC)	275
Outdoor Strip Light (24 V DC)	276
Power Supply for Indoor	
Strip Light	276
Power Supply for Outdoor	
Strip Light (IP65 rated)	276
INDUSTRIAL LIGHTS	
Glaze	280
Pride (Weather Proof IP65 rated)	280
Unilite	280
Bulk Head	281
Pit Light	281
Well Glass	281
Ultralite Highbay (>130 Lm / W)	282
Highbay (>100 Lm / W)	282
ROADWAY LIGHT	
PCR	286
Trump	286
Street Light (45 W)	286
Street Light (30 W)	286
Street Light (60, 70 & 72 W)	287
Street Light (90, 120, 150 & 200 W)	287
Elood Light	207

Flodz (Low Wattage Floodlight) Ledstar Floodlight (> 110 Lm / W)

259 259

265



# Indoor Commercial Lights

Jaquar Lighting's solutions for indoor commercial spaces include a wide range of high quality Downlights, COB Downlights, Battens and Panel lights. The choice makes it easy to find the perfect solution for every décor and lighting need.

# Downlights

Choose from as many as 10 different design ranges with sleek profiles, and multiple shapes and specifications.

# COB Downlights

Jaquar's recess-mounted COB downlights are available in 3 extensive design ranges with multiple choices of illumination power.

# Panels

Available in recess-mounted, surface-mounted or pendant applications, Jaquar Lighting's LED panels are first among the equals

# Battens and Tubes

Jaquar offers Battens in 2 designs, a variety of outputs, and 3 different colour temperatures. Also available are a wide range of Tubes.



Recess-mounted round panel with die cast aluminium housing

		Neve Plus (F	Round)		
and a state of the		Item Code	Wattage (w)	CCT (k)	Case No.
399		LNEP01R003XC	3	6500	20
and the second se		LNEP01R003XN	3	4000	20
/		LNEP01R003XW	3	3000	20
1		LNEP01R006XC	6	6500	20
		LNEP01R006XN	6	4000	20
	and the second se	LNEP01R006XW	6	3000	20
	PC	LNEP01R012XC	12	6500	10
		LNEP01R012XN	12	4000	10
The	D	LNEP01R012XW	12	3000	10
	[**]	LNEP01R015XC	15	6500	10
		LNEP01R015XN	15	4000	10
		LNEP01R015XW	15	3000	10
		LNEP01R018XC	18	6500	10
		LNEP01R018XN	18	4000	10
		LNEP01R018XW	18	3000	10
		LNEP01R024XC	24	6500	10
		LNEP01R024XN	24	4000	10
		LNEP01R024XW	24	3000	10
	C	<b>3 W</b> Cutout: Ø 72 mm Height: 20 mm	<b>6 W</b> Cutout: Ø 107 mm Height: 20 mm	<b>12 W</b> Cutout: Ø Height: 20 mm	) 160 mm
		<b>15 W</b> Cutout: Ø 180 mm Height: 20 mm	<b>18 W</b> Cutout: Ø 206 mm Height: 20 mm	<b>24 W</b> Cutout: @ Height: 20 mm	) 275 mm
	1	* THD < 10% for wattage $\ge$ 12	W.		

к і

 $\mathbf{I}$ 

Recess-mounted square panel with die cast aluminium housing


# Neve Plus (Square)

Item Code	Wattage (w)	CCT (k)	Case No.
LNEP01S003XC	3	6500	20
LNEP01S003XN	3	4000	20
LNEP01S003XW	3	3000	20
LNEP01S006XC	6	6500	20
LNEP01S006XN	6	4000	20
LNEP01S006XW	6	3000	20
LNEP01S012XC	12	6500	10
LNEP01S012XN	12	4000	10
LNEP01S012XW	12	3000	10
LNEP01S015XC	15	6500	10
LNEP01S015XN	15	4000	10
LNEP01S015XW	15	3000	10
LNEP01S018XC	18	6500	10
LNEP01S018XN	18	4000	10
LNEP01S018XW	18	3000	10
LNEP01S024XC	24	6500	10
LNEP01S024XN	24	4000	10
LNEP01S024XW	24	3000	10
<b>3 W</b> Cutout: 72 x 72 mm	6 W Cutout: 107	x 107 mm <b>12 W</b> Cu	utout: 160 x 160 m

Height: 20 mm **15 W** Cutout: 180 x 180 mm **18 W** Cutout: 206 x 206 mm **24 W** Cutout: 275 x 275 mm Height: 20 mm



Height: 20 mm Height: 20 mm




 $^{\star}$  THD < 10% for wattage  $\geq$  12 W.

# Downlights

Recess-mounted round panel with die cast aluminium housing





# Nero Plus (Round)

Item Code	Wattage (w)	(	CCT (k)	Case No.
LNRP01R003XC	3	6000		20
LNRP01R003XN	3	4000		20
LNRP01R003XW	3	3000		20
LNRP01R006XC	6	6000		20
LNRP01R006XN	6	4000		20
LNRP01R006XW	6	3000		20
LNRP01R009XC	9	6000		20
LNRP01R009XN	9	4000		20
LNRP01R009XW	9	3000		20
LNRP01R012XC	12	6000		10
LNRP01R012XN	12	4000		10
LNRP01R012XW	12	3000		10
LNRP01R015XC	15	6000		10
LNRP01R015XN	15	4000		10
LNRP01R015XW	15	3000		10
LNRP01R018XC	18	6000		10
LNRP01R018XN	18	4000		10
LNRP01R018XW	18	3000		10
LNRP01R022XC	22	6000		10
LNRP01R022XN	22	4000		10
LNRP01R022XW	22	3000		10
<b>3 W</b> Cutout: Ø 72 mm Height: 20 mm <b>12 W</b> Cutout: Ø 128 mm Height: 20 mm	6 W Cutout: Ø 1 Height: 20 mm 15 W Cutout: Ø Height: 20 mm		9 W Cutout: Ø 1 Height: 20 mm 18 W Cutout: Ø Height: 20 mm	
Height: 20 mm	Height: 20 mm		Height: 20 mm	

**22 W** Cutout: Ø 174 mm Height: 20 mm Low depth, recess-mounted, sleek, round downlight with die cast aluminium housing & polycarbonate diffuser

Item Code         Wattage (w)         CCT (k)           LARV01R006XC         6         6500           LARV01R006XN         6         4000           LARV01R006XW         6         3000           LARV01R009XC         9         6500           LARV01R009XC         9         6500           LARV01R009XW         9         3000           LARV01R009XW         9         3000           LARV01R012XC         12         6500           LARV01R012XN         12         4000           LARV01R012XW         12         3000           LARV01R015XN         15         6500           LARV01R015XW         15         3000           LARV01R015XN         15         4000           LARV01R015XN         15         4000           LARV01R015XN         15         3000           LARV01R015XN         15         3000           LARV01R015XN         15         3000           LARV01R018XN         18         6500           LARV01R018XN         18         4000           LARV01R018XN         18         4000	
LARV01R006XN 6 4000 LARV01R006XW 6 3000 LARV01R009XC 9 6500 LARV01R009XN 9 4000 LARV01R009XW 9 3000 LARV01R012XC 12 6500 LARV01R012XN 12 4000 LARV01R012XW 12 3000 LARV01R015XC 15 6500 LARV01R015XN 15 4000 LARV01R015XW 15 3000 LARV01R015XW 15 3000 LARV01R015XW 18 6500 LARV01R018XN 18 4000	Case No.
LARV01R006XW 6 3000 LARV01R009XC 9 6500 LARV01R009XN 9 4000 LARV01R009XW 9 3000 LARV01R012XC 12 6500 LARV01R012XN 12 4000 LARV01R012XW 12 3000 LARV01R015XC 15 6500 LARV01R015XN 15 4000 LARV01R015XN 15 3000 LARV01R015XW 15 3000 LARV01R015XW 18 6500 LARV01R018XN 18 4000	10
LARV01R009XC 9 6500 LARV01R009XN 9 4000 LARV01R009XW 9 3000 LARV01R012XC 12 6500 LARV01R012XN 12 4000 LARV01R012XW 12 3000 LARV01R015XC 15 6500 LARV01R015XN 15 4000 LARV01R015XW 15 3000 LARV01R015XW 15 3000 LARV01R018XC 18 6500 LARV01R018XN 18 4000	10
LARV01R009XN 9 4000 LARV01R009XW 9 3000 LARV01R012XC 12 6500 LARV01R012XN 12 4000 LARV01R012XW 12 3000 LARV01R015XC 15 6500 LARV01R015XN 15 4000 LARV01R015XW 15 3000 LARV01R015XW 15 3000 LARV01R015XW 18 6500 LARV01R018XN 18 4000	10
LARV01R009XW 9 3000 LARV01R012XC 12 6500 LARV01R012XN 12 4000 LARV01R012XW 12 3000 LARV01R015XC 15 6500 LARV01R015XN 15 4000 LARV01R015XW 15 3000 LARV01R015XW 15 3000 LARV01R015XW 18 6500 LARV01R018XN 18 4000	10
LARV01R012XC 12 6500 LARV01R012XN 12 4000 LARV01R012XW 12 3000 LARV01R015XC 15 6500 LARV01R015XN 15 4000 LARV01R015XW 15 3000 LARV01R015XW 15 3000 LARV01R018XC 18 6500 LARV01R018XN 18 4000	10
LARV01R012XN 12 4000 LARV01R012XW 12 3000 LARV01R015XC 15 6500 LARV01R015XN 15 4000 LARV01R015XW 15 3000 LARV01R018XC 18 6500 LARV01R018XN 18 4000	10
LARV01R012XW         12         3000           LARV01R015XC         15         6500           LARV01R015XN         15         4000           LARV01R015XW         15         3000           LARV01R015XW         15         3000           LARV01R015XW         15         3000           LARV01R018XC         18         6500           LARV01R018XN         18         4000	10
LARV01R015XC         15         6500           LARV01R015XN         15         4000           LARV01R015XW         15         3000           LARV01R018XC         18         6500           LARV01R018XN         18         4000	10
LARV01R015XN         15         4000           LARV01R015XW         15         3000           LARV01R018XC         18         6500           LARV01R018XN         18         4000	10
D         LARV01R015XW         15         3000           LARV01R018XC         18         6500           LARV01R018XN         18         4000	10
D         LARV01R018XC         18         6500           LARV01R018XN         18         4000	10
LARV01R018XN 18 4000	10
	10
	10
LARV01R018XW 18 3000	10
LARV01R024XC 24 6500	10
LARV01R024XN 24 4000	10
LARV01R024XW 24 3000	10
6 W Cutout: Ø 75 mm9 W Cutout: Ø 75 mm12 W CutoutHeight: 33 mmHeight: 33 mmHeight: 33 mm	
C 15 W Cutout: Ø 106 mm 18 W Cutout: Ø 158 mm 24 W Cutout Height: 33 mm Height: 33 mm Height: 33 m	
H THD < 10%	

Н

Recess-mounted round downlight with die cast aluminium housing

# Ensave Plus


Item Code	Wattage (w)	CCT (k)	Case No.
LESP01R009XC	9	6500	20
LESP01R009XN	9	4000	20
LESP01R009XW	9	3000	20
LESP01R015XC	15	6500	10
LESP01R015XN	15	4000	10
LESP01R015XW	15	3000	10
LESP01R025XC	25	6500	10
LESP01R025XN	25	4000	10
LESP01R025XW	25	3000	10
<b>9 W</b> Cutout: Ø 100 mm Height: 60 mm	<b>15 W</b> Cutout: Ø 160 mm Height: 85 mm	<b>25 W</b> Cutout: Ø Height: 85 mm	160 mm




Surface-mounted, round panel with die cast aluminium housing



Surface-mounted, square panel with die cast aluminium housing



Recess-mounted spotlight with aluminium housing & prismatic diffuser (white finish)



Surface-mounted round panel with die cast aluminium housing



Nero	Surface	(Round)
		(


Item Code	Wattage (w)	CCT (k)	Case No.
LNRO02R006SC	6	6500	20
LNRO02R006SN	6	4000	20
LNR002R006SW	6	3000	20
LNRO02R012SC	12	6500	12
LNRO02R012SN	12	4000	12
LNRO02R012SW	12	3000	12
LNRO02R018SC	18	6500	12
LNRO02R018SN	18	4000	12
LNRO02R018SW	18	3000	12
<b>6 W</b> Dia: Ø 125 mm Height: 35 mm	<b>12 W</b> Dia: Ø 175 mm Height: 35 mm	<b>18 W</b> Dia: Ø 2 Height: 35 mr	

Surface-mounted square panel with die cast aluminium housing



# Nero Surface (Square)

Item Code	Wattage (w)	CCT (k)	Case No.
LNRO02S006SC	6	6500	20
LNRO02S006SN	6	4000	20
LNRO02S006SW	6	3000	20
LNRO02S012SC	12	6500	12
LNRO02S012SN	12	4000	12
LNRO02S012SW	12	3000	12
LNRO02S018SC	18	6500	12
LNRO02S018SN	18	4000	12
LNRO02S018SW	18	3000	12
<b>6 W</b> Length: 125 mm Width: 125 mm Height: 35 mm	<b>12 W</b> Length: 175 mm Width: 175 mm Height: 35 mm	<b>18 W</b> Length: 225 mm Width: 225 mm Height: 35 mm	



# COB-Downlights

Recess-mounted COB spotlight with aluminium housing (white finish)



Recess-mounted, COB-based, round fixed downlight with die cast aluminium housing and 60° beam angle

Item Code	Wattage (w)	CCT (k)	Case No.
LETS01R010XC	10	6500	20
LETS01R010XN	10	4000	20
LETS01R010XW	10	3000	20
LETS01R020XC	20	6500	10
LETS01R020XN	20	4000	10
LETS01R020XW	20	3000	10
LETS01R030XC	30	6500	10
LETS01R030XN	30	4000	10
LETS01R030XW	30	3000	10
10 W Cutout: Ø 97 mm	20 W Cutout: Ø 121 mm	30 W Cutout: Ø 1	56 mm

10 W Cutout: Ø 97 mm Height: 65 mm

Estus Fixed


20 W Cutout: Ø 121 mm Height: 86 mm

Height: 96 mm



Recess-mounted, COB-based, round tiltable downlight with die cast aluminium housing and 36º beam angle





## Estus Swivel (Round)

Item Code	Wattage (w)	CCT (k)	Case No.
LETS36R003XC	3	6500	20
LETS36R003XN	3	4000	20
LETS36R003XW	3	3000	20
LETS36R006XC	6	6500	20
LETS36R006XN	6	4000	20
LETS36R006XW	6	3000	20
LETS36R009XC	9	6500	20
LETS36R009XN	9	4000	20
LETS36R009XW	9	3000	20
LETS36R012XC	12	6500	20
LETS36R012XN	12	4000	20
LETS36R012XW	12	3000	20
LETS36R015XC	15	6500	20
LETS36R015XN	15	4000	20
LETS36R015XW	15	3000	20
LETS36R018XC	18	6500	10
LETS36R018XN	18	4000	10
LETS36R018XW	18	3000	10
LETS36R024XC	24	6500	10
LETS36R024XN	24	4000	10
LETS36R024XW	24	3000	10
LETS36R030XC	30	6500	10
LETS36R030XN	30	4000	10
LETS36R030XW	30	3000	10
<ul> <li>3 W Cutout: Ø 58 mm</li> <li>Height: 50 mm</li> <li>12 W Cutout: Ø 95 mm</li> <li>Height: 85 mm</li> <li>24 W Cutout: Ø 118 mm</li> <li>Height: 85 mm</li> </ul>	6 W Cutout: Ø 74 mm Height: 65 mm 15 W Cutout: Ø 95 mm Height: 85 mm 30 W Cutout: Ø 118 mm Height: 100 mm	9 W Cutout: Ø 74 Height: 65 mm 18 W Cutout: Ø 1 Height: 85 mm	


\*Beam angle of  $25^{\circ}$  is available on request

\* THD < 10% for wattage  $\geq$  6 W.

COB-Downlights

Deep recess-mounted, COB based round fixed downlight with die cast aluminium housing and 24° beam angle





# Eris Fixed (Low Border Deep Recess)

Item Code	Wattage (w)	CCT (k)	Case No.
LERS02R005XC	5	6500	20
LERS02R005XN	5	4000	20
LERS02R005XW	5	3000	20
LERS02R010XC	10	6500	20
LERS02R010XN	10	4000	20
LERS02R010XW	10	3000	20
LERS02R015XC	15	6500	10
LERS02R015XN	15	4000	10
LERS02R015XW	15	3000	10
LERS02R020XC	20	6500	10
LERS02R020XN	20	4000	10
LERS02R020XW	20	3000	10
5 W Cutout: Ø 47 mm	10 W Cutout: Ø 69 mm	15 W Cutor	ut: Ø 80 mm

Height: 110 mm

**5 W** Cutout: Ø 47 mm Height: 100 mm **20 W** Cutout: Ø 115 mm 15 W Cutout: Ø 80 mm Height: 120 mm

Height: 130 mm

\* THD < 10% \*CRI>90 Deep recess-mounted, COB based swivel downlight with 38º beam angle




Recess-mounted, COB based downlight with die cast aluminium housing and anodized reflector




Item Code	Wattage (w)	CCT (k)	Case No.
	_	0500	50
LERS04R007XC	7	6500	50
LERS04R007XN	7	4000	50
LERS04R007XW	7	3000	50
LERS04R012XC	12	6500	10
LERS04R012XN	12	4000	10
LERS04R012XW	12	3000	10
LERS04R020XC	20	6500	20
LERS04R020XN	20	4000	20
LERS04R020XW	20	3000	20
LERS04R030XC	30	6500	20
LERS04R030XN	30	4000	20
LERS04R030XW	30	3000	20
7 W Cutout: Ø 75mm Height: 43 mm Beam angle: 38° 30 W Cutout: Ø 140 mm Height: 75 mm Beam angle: 52°	<b>12 W</b> Cutout: Ø 97 mm Height: 53 mm Beam angle: 43°	<b>20 W</b> Cutout: Ø 1 Height: 75 mm Beam angle: 52°	40 mm

Recess-mounted, COB based downlight with die cast aluminium housing and clear glass








# Eris Fixed

Item Code	Wattage (w)	CCT (k)	Case No.
LERS05R007XC	7	6500	50
LERS05R007XN	7	4000	50
LERS05R007XW	7	3000	50
LERS05R012XC	12	6500	40
LERS05R012XN	12	4000	40
LERS05R012XW	12	3000	40
LERS05R020XC	20	6500	10
LERS05R020XN	20	4000	10
LERS05R020XW	20	3000	10
LERS05R035XC	35	6500	10
LERS05R035XN	35	4000	10
LERS05R035XW	35	3000	10
7 W Cutout: Ø 80 mm Height: 60 mm Beam angle: 33° 35 W Cutout: Ø 185 mm Height: 95 mm Beam angle: 50°	<b>12 W</b> Cutout: Ø 100 mm Height: 65 mm Beam angle: 45°	20 W Cutout: Ø 1 Height: 75 mm Beam angle: 45°	30 mm

Ultra slim panel made from extruded aluminium housing frame (recess / pendant) 1 Ft x 1 Ft.



Ultra slim panel made from extruded aluminium housing frame (recess / pendant) 2 Ft x 2 Ft.



Surface-mounted panel made from extruded aluminium housing (surface) 2 Ft x 2 Ft.




## Sauver (Surface)

Item Code	Wattage	CCT	Case
	(w)	(k)	No.
LSVR01S036SC	36	6000	1
LSVR01S036SN	36	4000	1

36 W

Length x Width: 600 x 600 mm Height: 55 mm Ultra-slim panel made from extruded aluminium housing frame (pendant) 1 Ft x 4 Ft.



### Sauver (Linear)

Item Code	Wattage (w)	CCT (k)	Case No.
LSVR03S042XC	42	6000	1
LSVR03S042XN	42	4000	1
LSVR03S042XW	42	3000	1
<b>42 W</b> Length x Width: 1196 x 2 Height: 10 mm	296 mm		
*Surface-mount option a	vailable		


Recess-mounted panel with white powder-coated CRCA housing and full mounted acrylic diffuser (1 Ft x 1 Ft).



Recess-mounted panel with white powder-coated CRCA housing and full mounted window acrylic diffuser (2 Ft x 2 Ft).



Recess-mounted panel with white powder-coated CRCA housing and full mounted acrylic diffuser (1 Ft x 4 Ft).



High efficacy, recess-mounted panel with white powder-coated CRCA housing and full mounted acrylic diffuser (2 Ft x 2 Ft) 125 Lm / W for 36 W & 120 Lm / W for 24 W.



Multi-colour changeable recess-mounted panel with white powder-coated CRCA housing and full mounted acrylic diffuser (2 Ft x 2 Ft).



#### Battens-Tubes

High quality batten with extruded aluminium housing and decorative end caps

	Glaze			
	Item Code	Wattage (w)	CCT (k)	Case No.
	LGLZ01X010XC	10	6500	20
	LGLZ01X010XN	10	4000	20
	LGLZ01X010XW	10	3000	20
	LGLZ01X020XC	20	6500	20
	LGLZ01X020XN	20	4000	20
	LGLZ01X020XW	20	3000	20
	LGLZ01X024XC	24	6500	20
н	LGLZ01X024XN	24	4000	20
	LGLZ01X024XW	24	3000	20
 W	<b>10 W</b> Length: 570 mm Width: 22 mm Height: 37 mm	<b>20 W</b> Length: 1135 mm Width: 22 mm Height: 37 mm	<b>24 W</b> Length: 1185 mm Width: 22 mm Height: 37 mm	

High quality batten with polycarbonate housing and decorative end caps



### Glaze (PC)

Item Code	Wattage (w)	CCT (k)	Case No.
LGLZPCX020XC	20	6500	20
LGLZPCX020XN	20	4000	20
LGLZPCX020XW	20	3000	20`

**20 W** Length: 1135 mm Width: 22 mm Height: 37 mm

High quality batten with polycarbonate housing and decorative end caps



### Glaze Ultra (PC)

Item Code	Wattage (w)	CCT (k)	Case No.
LGLZPCX022XC	22	6500	20
LGLZPCX022XW	22	3000	20

**22 W** Length: 1145 mm Width: 30 mm Height: 40 mm

### Battens-Tubes

Indoor tube light with aluminium housing and polycarbonate diffuser



### T8 Retro Tube

Item Code	Wattage (w)	CCT (k)	Case No.
LTBL01X010XC	10	6000	10
LTBL01X010XW	10	3000	10
LTBL01X018XC	18	6000	10
LTBL01X018XW	18	3000	10
LTBL01X020XC	20	6000	10
LTBL01X020XW	20	3000	10
<b>10 W</b> Length: 600 mm Height: Ø 30 mm	<b>18 W</b> Length: 1200 mm Height: Ø 30 mm	<b>20 W</b> Length: 1 Height: Ø 30 m	

High quality batten with extruded aluminium housing and decorative end caps



### Glaze Ultra Aluminium

Item Code	Wattage (w)	CCT (k)	Case No.
LGLZU1X022XC	22	6500	20
LGLZU1X022XN	22	4000	20
LGLZU1X022XW	22	3000	20

#### 22 W

Length: 1135 mm Width: 20 mm Height: 35 mm






# Designer Lights


Jaquar has two stunning offerings in its Designer Lighting series, with more on the way, that bring state-of-the-art lighting solutions to commercial spaces. Any space that uses the Trius or Lattice lights moves several notches up the scale in aesthetic appeal.

### Designer Lights

Suspended opti-flow linear light with contemporary design for modern office spaces



Suspended light with contemporary design for modern office spaces (up and downlight) (50:50)



Deep recessed, anti-glare light with die cast aluminium housing, aluminium heat sink and tiltable arrangement



### Reflectorz

Item Code	Wattage (w)	CCT (k)	Case No.
LSYGRDR007XN	7	4000	20
LSYGRDR007XW	7	3000	20
LSYGRDR009XN	9	4000	20
LSYGRDR009XW	9	3000	20
LSYGRDR012XN	12	4000	20
LSYGRDR012XW	12	3000	20

7 W, 9 W, 12 W Cutout: Ø68 mm Height: 93 mm

Item Code	Wattage (w)	CCT (k)	Case No.
LSYGOVR007XW	7	3000	20
LSYGOVR007XN	7	4000	20
LSYGOVR009XW	9	3000	20
LSYGOVR009XN	9	4000	20
LSYGOVR012XW	12	3000	20
LSYGOVR012XN	12	4000	20


**7 W, 9 W, 12 W** Cutout: Ø68 mm Height: 93 mm

\*THD <10%, CRI > 90 2700k available on request

### Designer Lights

Recess-mounted COB based, trimless, fixed downlight with die cast aluminium housing. Adjustable height and tempered transparent glass diffuser with 36° beam angle





# DAZY- Trimless (Deep-Recessed)

Item Code	Wattage (w)	CCT (k)	Case No.
LDZY01R008XC	8	6500	36
LDZY01R008XN	8	4000	36
LDZY01R008XW	8	3000	36
LDZY01R012XC	12	6500	27
LDZY01R012XN	12	4000	27
LDZY01R012XW	12	3000	27
LDZY01R018XC	18	6500	22
LDZY01R018XN	18	4000	22
LDZY01R018XW	18	3000	22
<b>8 W</b> Cutout: Ø62 mm Height: 94 mm	<b>12 W</b> Cutout: Ø85 mm Height: 115 mm	<b>18 W</b> Cutou Height: 129	

Surface-mounted COB downlight with die cast aluminium housing and gold finish reflector and 30° beam angle


Eris Surfa	ace (Deep	Surface)
------------	-----------	----------



Item Code	Wattage (w)	CCT (k)	Case No.
LERSWGS012SC	12	6500	40
LERSWGS012SN	12	4000	40
LERSWGS012SW	12	3000	40
LERSWGS020SC	20	6500	30
LERSWGS020SN	20	4000	30
LERSWGS020SW	20	3000	30
LERSWGS030SC	30	6500	16
LERSWGS030SN	30	4000	16
LERSWGS030SW	30	3000	16
Item Code	Wattage (w)	CCT (k)	Case No.
LERSBGS012SC	12	6500	40
LERSBGS012SN	12	4000	40
LERSBGS012SW	12	3000	40
LERSBGS0123W	20	6500	40 30
LERSBGS020SC	20	4000	30
LERSBGS020SW	20	3000	30
			30 16
LERSBGS030SC	30	6500	
LERSBGS030SN	30	4000	16
LERSBGS030SW	30	3000	16
<b>12 W</b> Length: 73 mm Width: 73 mm Height: 95 mm	<b>20 W</b> Length: 95 mm Width: 95 mm Height: 110 mm	<b>30 W</b> Length: 115 Width: 115 n Height: 125 r	nm

Decorative, energy efficient, flicker-free low power consumption bulb






### GU10

Item Code	Wattage (w)	CCT (k)	Case No.
	-	4000	000
LGU10XX005XN	5	4000	200
LGU10XX005XW	5	2700	200
LGU10XX006DN*	6	4000	200
LGU10XX006DW*	6	2700	200
LGU10XX007XN	7	4000	200
LGU10XX007XW	7	2700	200
*Dimmable product			
5 W Dia: Ø50 mm	6 W Dia: Ø50 mm	<b>7 W</b> Dia: Ø50	) mm
Height: 55 mm	Height: 55 mm	Height: 55 m	m

Decorative, energy efficient, flicker-free low power consumption bulb





## MR16

Item Code	Wattage (w)	CCT (k)	Case No.
LMR16XX007XN	7	4000	200
LMR16XX007XW	7	3000	200

**7 W** Dia: Ø50 mm Height: 55 mm







For the specialised needs of the retail industry, Jaquar offers a complete range of recess-mounted and surface-mounted spot lights, strip lights and accessories, which make innovative and highly attractive product lighting possible.

Recess-mounted zoom light with powder-coated die cast aluminium housing and anodized aluminium reflector. 38º beam angle










# Zoom Light

Item Code	Wattage (w)	CCT (k)	Case No.
LZOM01R015XC	15	6500	1
LZOM01R015XN	15	4000	1
LZOM01R015XW	15	3000	1
LZOM01R025XC	25	6500	1
LZOM01R025XN	25	4000	1
LZOM01R025XW	25	3000	1
LZOM01R035XC	35	6500	1
LZOM01R035XN	35	4000	1
LZOM01R035XW	35	3000	1
<b>15 W</b> Cutout: 85 mm Height: 72 mm	<b>25 W</b> Cutout: 140 mm Height: 121 mm	<b>35 W</b> Cutout: 14 Height: 121 mm	

Height: 72 mm \* CRI > 90, THD <10%

Recess-mounted, COB based multiple zoom light with die cast aluminium housing, anodized reflector and tempered transparent glass diffuser. 40° beam angle





# Multiple Zoom Light

Item Code	Wattage (w)	CCT (k)	r	Case No.
LZOMMLR115XC	15	650	0	40
LZOMMLR115XN	15	400		40
LZOMMLR115XW	15	300	0	40
LZOMMLR135XC	35	650	0	12
LZOMMLR135XN	35	400	0	12
LZOMMLR135XW	35	300	0	12
LZOMMLR215XC	2x15	650	0	20
LZOMMLR215XN	2x15	400	0	20
LZOMMLR215XW	2x15	300	0	20
LZOMMLR235XC	2x35	650	0	8
LZOMMLR235XN	2x35	400	0	8
LZOMMLR235XW	2x35	300	0	8
LZOMMLR315XC	3x15	650	0	16
LZOMMLR315XN	3x15	400	0	16
LZOMMLR315XW	3x15	300	0	16
LZOMMLR335XC	3x35	650	0	6
LZOMMLR335XN	3x35	400	0	6
LZOMMLR335XW	3x35	300	0	6
<b>15 W</b> Cutout: 92 x 92 mm Height: 86 mm	<b>35 W</b> Cutout: 16 Height: 139 mm	0 x 160 mm	<b>2 x 15</b> Cutout: 19 Height: 86 mm	92 x 92 mm
<b>3 x 15</b> Cutout: 270 x 92 mm Height: 86 mm CRI > 90	<b>2 x 35</b> Cutout: 33 Height: 139 mm		<b>3 x 35</b> Cutout: 48 Height: 139 mm	35 x 160 mm

Surface-mounted, powder coated focus light with die cast aluminium housing and anodized aluminium reflector. Clear diffuser and fully adjustable with 40° beam angle

			, i i c		
		Item Code	Wattage (w)	CCT (k)	Case No.
-		LFCL01R010XC	10	5000	1
19		LFCL01R010XN	10	4000	1
		LFCL01R010XW	10	3000	1
SP. V		LFCL01R020XC	20	5000	1
	W	LFCL01R020XN	20	4000	1
		LFCL01R020XW	20	3000	1
Contraction of the local division of the loc	۲	LFCL01R030XC	30	5000	1
		LFCL01R030XN	30	4000	1
		LFCL01R030XW	30	3000	1
		LFCLB1R010XC	10	5000	1
	223	LFCLB1R010XN	10	4000	1
	н	LFCLB1R010XW	10	3000	1
		LFCLB1R020XC	20	5000	1
	L D	LFCLB1R020XN	20	4000	1
		LFCLB1R020XW	20	3000	1
		LFCLB1R030XC	30	5000	1
		LFCLB1R030XN	30	4000	1
		LFCLB1R030XW	30	3000	1
(CRI > 90)		<b>10 W</b> Length: 195 mm Width: 110 mm Height: 106 mm	<b>20 W</b> Length: 198 mr Width: 140 mm Height: 130 mn	n Le W	<b>0 W</b> ength: 198 mm /idth: 140 mm leight: 130 mm

Track-mounted round focus light with moveable base. Fully adjustable with aluminium housing (including driver casing). 40° beam Angle



# Accessories for Track Light

## 2 Line Track

Item Code	Length	Colour
LTRK2L1MTRBL	1 MTR	BLK
LTRK2L1MTRWH	1 MTR	WHT
LTRK2L2MTRBL	2 MTR	BLK
LTRK2L2MTRWH	2 MTR	WHT

# 3 Line Track

Item Code	Length	Colour
LTRK3L1MTRBL	1 MTR	BLK
LTRK3L1MTRWH	1 MTR	WHT
LTRK3L2MTRBL	2 MTR	BLK
LTRK3L2MTRWH	2 MTR	WHT

### 2 Line Track Connector


Item Code	Shape	Colour
LTRCBL2LISHP	l	BLK
LTRCBL2LLSHP	L	BLK
LTRCBL2LTSHP	T	BLK

## 3 Line Track Connector

Item Code	Shape	Colour
		51.17
LTRCBL3LISHP	I	BLK
LTRCWH3LISHP		WHT
LTRCBL3LLSHP	L	BLK
<b>LTRCWH3LLSHP</b>	L	WHT
LTRCBL3LXSHP	Х	BLK
LTRCWH3LXSHP	Х	WHT
LTRCBL3LTSHP	Т	BLK
LTRCWH3LTSHP	Т	WHT

Recessed directional COB downlight with die cast aluminium housing






—			r.		
⊢	n	Ľ	t	$\cap$	
_	Μ	1		$\sim$	

Item Code	Wattage (w)	CCT (k)	Case No.
	10		10
LEP001R012XC	12	6500	10
LEP001R012XN	12	4000	10
LEP001R012XW	12	3000	10
LEP001R020XC	20	6500	10
LEP001R020XN	20	4000	10
LEP001R020XW	20	3000	10
<b>12 W</b> Cutout: ø75 mm Dia: 85 mm Height: 70 mm	<b>20 W</b> Cutout: 9 Dia: 108 Height: 8	mm	

Deep recessed surface mount focus light with die cast aluminium housing







Item Code	Wattage (w)	CCT (k)	Case No.
LCYN01R010SC	10	6500	20
LCYN01R010SN	10	4000	20
LCYN01R010SW	10	3000	20

Dia: 42 mm Height: 120 mm

Deep recessed extended COB focus light with die cast aluminium housing







### Empha

Height: 98 mm

Item Code	Wattage (w)	CCT (k)	Case No.
LEMP01R007XC	7	6500	20
LEMP01R007XN	7	4000	20
LEMP01R007XW	7	3000	20
LEMP01R015XC	15	6500	10
LEMP01R015XN	15	4000	10
LEMP01R015XW	15	3000	10
<b>7 W</b> Cutout: ø62 mm Dia: 72 mm	<b>15 W</b> Cutout: 9 Dia: 103		


Dia:	103 mm
Heig	ht: 99 mm

Recess-mounted, COB based tiltable linear spotlight with die cast aluminium housing and 30° beam angle

and the second second	Rene			
	Item Code	Wattage (w)	CCT (k)	Ca: N
	LRNE01S002XC	2	6500	
	LRNE01S002XN	2	4000	
	LRNE01S002XW	2	3000	
	LRNE01S006XC	6	6500	
	LRNE01S006XN	6	4000	
	LRNE01S006XW	6	3000	
	LRNE01S010XC	10	6500	
	LRNE01S010XN	10	4000	
	LRNE01S010XW	10	3000	
	LRNE01S020XC	20	6500	
	LRNE01S020XN	20	4000	
	LRNE01S020XW	20	3000	
	LRNE01S030XC	30	6500	
	LRNE01S030XN	30	4000	
	LRNE01S030XW	30	3000	
V-, 	<b>2 W</b> Cutout: 50 x 47 mm Length: 55 mm Width: 55 mm Height: 47mm	<b>6 W</b> Cutout: 111 x 47 mm Length: 116 mm Width:55 mm Height: 47 mm	<b>10 W</b> Cutout: 153 x Length: 158 r Width: 55 mr Height: 47 m	mm n
- ] <sub>H</sub> ]_]	<b>20 W</b> Cutout: 286 x 47 mm Length: 290 mm Width: 55 mm Height: 47 mm	<b>30 W</b> Cutout: 419 x 47 mm Length: 423 mm Width: 55 mm Height: 47 mm		

IP20 rated strip light suitable for indoor applications with different colours and wattages. Standard 5.0 mtr roll






# Indoor Strip Light (24 V DC)


Item Code	Wattage (w)	CCT (k)	Case No.
LSTP03X005XC	25	6000	5
LSTP03X005XN	25	4000	5
LSTP03X005XW	25	3000	5
LSTP03X005XB	25	Blue	5
LSTP03X008XC	40	6000	5
LSTP03X008XW	40	3000	5
LSTP03X015XC	75	6000	5
LSTP03X015XW	75	3000	5
LSTP03X015XM	75	RGB	5
LSTP03X008XM	40	RGB	5
<b>25 W</b> Width: 8 mm Height: 2.5 mm	<b>40 W</b> Width: 8 mm Height: 2.5 mm		<b>75 W</b> Width: 8 mm Height: 2.5 mm

IP65 rated strip light suitable for outdoor applications with different colours and wattages. Standard 5.0 mtr roll



# Outdoor Strip Light (24 V DC)

Item Code	Wattage (w)	CCT (k)	Case No.
LSTP04X005XC	25	6000	5
LSTP04X005XW	25	3000	5
LSTP04X015XC	75	6000	5
LSTP04X015XW	75	3000	5
LSTP04X008XM	40	RGB	5
LSTP04X015XM	75	RGB	5
<b>25 W</b> Width: 10 mm Height: 4.5 mm	<b>40 W</b> Width: 10 mm Height: 4.5 mm		<b>75 W</b> Width: 10 mm Height: 4.5 mm



### Power Supply for Indoor Strip Light

Item Code	Wattage (w)
LDRV01S030XX	30
LDRV01S048XX	48
LDRV01S060XX	60
LDRV01S072XX	72
LDRV01S096XX	96

\*Prices on request for RGB controller & amplifier



## Power Supply for Outdoor Strip Light (IP65 rated)

Item Code	Wattage (w)
LDRV02S030XX	30
LDRV02S048XX	48
LDRV02S060XX	60
LDRV02S072XX	72
LDRV02S096XX	96

\*Prices on request for RGB controller & amplifier






# Industrial Lighs

For the heavy-duty lighting requirements of industrial plants, factories and shop floors, Jaquar has high-powered, long–lasting solutions. Choose from weather-proof, corrosion-resistant lights, twin-tube lights, bulk heads, and suspended, industrial COB highbay lights in a wide range of options.

### Industrial Lights

High quality batten with extruded aluminium housing and decorative end caps



Glaze			
Item Code	Wattage	CCT	Case
	(w)	(k)	No.
LGLZ01X040XC	40	6500	10
LGLZ01X040XN	40	6500	10
LGLZ01X040XW	40	6500	10
<b>40 W</b> Length: 1185 mm Width: 25 mm Height: 45 mm			

Corrosion and impact resistant batten with polycarbonate housing. Dust and water proof



## Pride (Weather Proof IP65 rated)

Item Code	Wattage (w)	CCT (k)	Case No.
LPRD01X020XC LPRD01X020XW LPRD01X040XC LPRD01X040XW	20 20 40 40	6000 3000 6000 3000	1 1 1
<b>20 W</b> Length: 590 mm Width: 86 mm Height: 67 mm	<b>40 W</b> Length: 1180 r Width: 86 mm Height: 67 mm		

Single or twin tube with powder coated MS box



### Unilite

Item Code	Wattage (w)	CCT (k)	Case No.
LUNI01X120XC LUNI01X120XW LUNI01X220XC LUNI01X220XW LRFT01XXXXXX (Reflector)	20 20 40 40	6500 3000 6500 3000	1 1 1 1
<b>20 W</b> Length: 1251 mm Width: 47 mm Height: 78 mm	<b>40 W</b> Length: 1251 Width: 110 mr Height: 78 mn	n	

#### Industrial Lights


Bulk head with pressure die cast aluminium housing and acrylic diffuser (IP65 protection)



### Bulk Head

Item Code	Wattage (w)	CCT (k)	Case No.
	10	0500	
LBLK02X010XC	10	6500	I
LBLK02X010XN	10	4000	1
LBLK02X010XW	10	3000	1
<b>10 W</b> Length: 193 mm Width: 118 mm Height: 56 mm			

Pit light with die cast aluminium housing and clear polycarbonate diffuser (IP66 rating)



Pit Light			
Item Code	Wattage (w)	CCT (k)	Case No.
LPIT01R016XC	16	6000	20
<b>16 W</b> Length: 240 mm Width: 130 mm Height: 90 mm			

Well glass light with die cast aluminium housing and polycarbonate diffuser (IP65 rating)



# Well Glass


Item Code	Wattage	CCT	Case
	(w)	(k)	No.
LWGL01X030XC	30	6500	4
LWGL01X035XC	35	6500	
LWGL01X040XC	40	6500	
<b>30 W</b> Dia: Ø130 mm	<b>35 W</b> Dia: Ø130 mm	<b>40 W</b> Dia: Ø1	
Height: 206 mm	Height: 206 mm	Height: 206 n	

\*3000K/4000K available on request

#### Industrial Lights

Discrete highbay light with die cast aluminium housing offering lumen intensity >130 Lm / W. Excellent thermal management with compact heat sink (IP65 rating)







Height: 132 mm

# Ultralite Highbay (>130 Lm / W)

Height: 132 mm

Item Code	Wattage (w)	CCT (k)	Case No.
	70	5700	-1
LHBLDUL070XC	70	5700	I
LHBLDUL100XC	100	5700	1
LHBLDUL120XC	120	5700	1
LHBLDUL150XC	150	5700	1
LHBLDUL200XC	200	5700	1
<b>70 W</b> Dia: Ø285 mm Height: 115 mm	<b>100 W</b> Dia: Ø285 mm Height: 115 mm	<b>120 W</b> Dia: Ø28 Height: 115 mm	
150 W Dia: Ø360 mm	200 W Dia: Ø360 mm		

Discreet highbay light with die cast aluminium housing offering lumen intensity ≥100 Lm / W. Excellent thermal management with compact heat sink (IP65 rating)






## Highbay (>100 Lm / W)

Item Code	Wattage (w)	CCT (k)	Case No.
LHBLD1S070XC	70	5700	1
LHBLD1S100XC	100	5700	1
LHBLD1S120XC	120	5700	1
LHBLD1S150XC	150	5700	1
LHBLD1S200XC	200	5700	1
<b>70 W</b> Dia: Ø285 mm Height: 115 mm	<b>100 W</b> Dia: Ø285 mm Height: 115 mm	<b>120 W</b> Dia: Ø285 Height: 115 mm	5 mm

200 W Dia: Ø360 mm

Height: 132 mm





150 W Dia: Ø360 mm

Height: 132 mm






# Roadway Lights

Reducing energy consumption and increasing road safety can now go hand-in-hand with Roadway Lighting solutions from Jaquar. Choose from a wide range of durable and weather-resistant street light and flood light options in a choice of outputs to suit every road's requirement.

### Roadway Lights

IP66 rated street light with pressure die cast aluminium housing, glass cover and lens\*\*



Item Code	Wattage (w)	CCT (k)	Case No.
LPCRSRT25WLC	25	5700	1
LPCRSRT25WLW	25	3000	1
LPCRSRT30WXC	30	5700	1
LPCRSRT30WXW	30	3000	1
LPCRSRT36WXC	36	5700	1
LPCRSRT36WXW	36	3000	1

**25 / 30 / 36 W** Dia: Ø42 mm

Length x Width x Height:  $330 \times 117 \times 67 \text{ mm}$ 

Note: All street lights are available with THD <10\%  $\,$ 

IP66 rated street light with pressure die cast aluminium housing and polycarbonate cover



### Trump

PCR

Item Code	Wattage (w)	CCT (k)	Case No.
LTRUMP0025XC	25	5700	1
LTRUMP0025XW	25	3000	1
LTRUMP0030XC	30	5700	1
LTRUMP0030XW	30	3000	1

25 / 30 W Dia: Ø41 mm

Length x Width x Height: 355 x 105 x 75 mm

LED Street light with pressure die cast aluminium housing with toughened glass cover



### Street Light

Item Code	Wattage (w)	CCT (k)	Case No.
			1101
LSRT01S045XC	45	5700	10
LSRT01S045XW	45	3000	10
LSRT02S045XC*	45	5700	10

**45 W** Length x Width x Height: 372 x 146 x 65 mm

\*Sytem lumen efficacy >120 Lm / W

LED Street light with pressure die cast aluminium housing, top opening with seperate driver compartment & toughened glass / polycarbonate cover



### Street Light

Item Code	Wattage (w)	CCT (k)	Case No.
LSRT015030XC	30	5700	10
LSRT015030XW	30	3000	10
LSRTTOS030XC*	30	5700	10

**30 W** Length x Width x Height: 180 x 115 x 60 mm **Note:** 30W Street light with polycarbonate cover

\*System lumen efficacy 120 Lm / W

#### Roadway Lights

LED Street light with pressure die cast aluminium housing, top opening with seperate driver compartment & toughened glass / polycarbonate cover



# Street Light

Item Code	Wattage (w)	CCT (k)	Case No.
LSRT015060XC	60	5700	1
LSRT015060XW	60	3000	1
LSRTTOS060XC*	60	5700	1
LSRT015070XC	70	5700	1
LSRT015070XW	70	3000	1
LSRTTOS072XC*	72	5700	1

**60 W, 70 W, 72 W** Length x Width x Height: 320 x 190 x 80 mm \*System lumen efficacy 120 Lm / W

LED Street light with pressure die cast aluminium housing, top opening with seperate driver compartment & toughened glass / polycarbonate cover



### Street Light

Item Code	Wattage (w)	CCT (k)	Case No.
LSRT015090XC	90	5700	1
LSRT015090XW	90	3000	1
LSRTTOS090XC*	90	5700	1
LSRT015120XC	120	5700	1
LSRT015120XW	120	3000	1
LSRTTOS120XC*	120	5700	1
LSRT015150XC	150	5700	1
LSRT015150XW	150	3000	1
LSRTTOS150XC*	150	5700	1
LSRT015200XC	200	5700	1
LSRT015200XW	200	3000	1
LSRTTOS200XC*	200	5700	1

90 W, 120 W Length x Width x Height: 400 x 200 x 108 mm 150 W, 200 W Length x Width x Height: 520 x 200 x 75 mm \*System lumen efficacy 120 Lm / W

IP66 rated floodlight with high pressure die cast aluminium housing, toughened glass cover and lens



IP65 rated floodlight with high pressure die cast aluminium housing and impact resistant polycarbonate lens



# Flodz (Low Wattage Floodlight)

Item Code	Wattage (w)	CCT (k)	Case No.
LFLD04S030XC	30	6500	1
LFLD04S050XC	50	6500	1
<b>30 W</b> Length x Width: 190 x 148 r Height: 40 mm	nm	<b>50 W</b> Length x Width: 240 x 185 mm Height: 40 mm	
*Efficacy is > 100 Lm / W			

IP66 rated floodlight with high pressure die cast aluminium housing, individual lens and toughened glass cover

mal	Ledstar Floodlight (>110 Lm / W)			
With external SPD 10KV*	Item Code	Wattage (w)	CCT (k)	Case No.
A REFERENCE OF THE REFE	LFLDSLM070XC	70	5700	1
100 (1000) (1000)	LFLDSLM070XW	70	3000	1
	LFLDSLM100XC	100	5700	1
	LFLDSLM100XW	100	3000	1
Property and	LFLDSLM120XC	120	5700	1
	LFLDSLM120XW	120	3000	1
	LFLDSLM150XC	150	5700	1
	LFLDSLM150XW	150	3000	1
	LFLDSLM180XC	180	5700	1
	LFLDSLM180XW	180	3000	1
	LFLDSLM200XC	200	5700	1
	LFLDSLM200XW	200	3000	1
	LFLDSLM250XC	250	5700	1
	LFLDSLM250XW	250	3000	1
	LFLDSLM300XC	300	5700	1
	LFLDSLM300XW	300	3000	1
Aiming and angle adjustment	<b>70 W</b> Length x Width: 235 x 23	5 mm	<b>100 / 120 W</b> Length x Width: 292 x 262 mm	
· · · · · · · · · · · · · · · · · · ·	Height: 75 mm		Height: 80 mm	
	<b>150 / 180 W</b> Length x Width: 352 x 318 Height: 89 mm	8 mm	<b>200 / 250 / 300 W</b> Length x Width: 420 x 370 mm Height: 100 mm	





Jaquar Lighting, an amalgamation of the most admired and desired lighting products, presents the most comprehensive range of high quality outdoor lighting products. Unparalleled and beyond compare, Jaquar's lighting products are carefully monitored at each and every step, right from the manufacturing process to the final delivery of the products. That is because Jaquar seeks to fulfill customer needs as well as anticipate future market needs and trends, an effort which has enabled us to achieve constant growth in an increasingly competitive market.

# Content

<b>PROJECTOR LIGHTS</b> Lyras 65 Lyras 160	294 294	WALL LIGHTS Pisa Sirio	314 315
GROUND BURIAL Mira 65 Mira 65 Mira 65 Mira 65 Mira 65 Mira 150 Mira 220	298 299 299 300 300 300	Firenze Morphis Neway Kubs Brick Light Mira 65 Dolby 2 Cervinia Lyras 130 Acqua <b>POLE LIGHTS</b> Monaco Romantica Morphis Morphis	315 315 315 316 316 316 317 317
GATE TOP Morphis Monaco Romantica Neway Firenze	304 304 305 305 305		317 317 320 320 321 321
BOLLARD Monaco Morphis Romantica Neway Orion Kubs Titano	308 309 309 309 310 310 310	worpins	521






# Projector Lights

- Facade lighting
- Accent lighting
- Atriums and columns
- Architectural lighting
- Varied beam angle applications







### Lyras 65

#### Features

Decorative fixture (3000 K) Transparent glass diffuser 30° Narrow beam IP67 IK08

#### Product Code

4699LL5H.BRZ

#### Wattage

5 W LED

## Lyras 160


#### Features

Decorative fixture Die cast aluminium housing Transparent glass diffuser Grey colour 60° beam angle IP67

Product Code 4641LL10H.NHG 4641LL20H.NHG

#### Wattage


10 W / 20 W LED



20.5








# Ground Burial

- Outdoor facade lighting
- Landscape lighting
- Accent lighting





### Mira 65

#### Features

Decorative fixture (3000 K) Extruded anodized aluminium housing Transparent glass diffuser 30° beam angle IP67 IK08

Product Code 5351LL5H.INX

Wattage 5 W LED

### Ground Burial

### Mira 65

#### Features


Decorative fixture (3000 K) Extruded anodized aluminium housing Glass diffuser 30° beam angle IP67 IK08

#### Product Code

5383LL5H.INX

### Wattage

5 W LED







### Mira 65

Features Decorative fixture Extruded anodized aluminium housing Glass diffuser IP67 IK08

Product Code

5382L5H.INX

Wattage

5 W LED


### Mira 65

Features

Decorative fixture Extruded anodized aluminium housing Glass diffuser IP67 IK08

Product Code 5385LL5H.INX

Wattage 5 W LED







## Mira 65

#### Features


Decorative fixture Extruded anodized aluminium housing Glass diffuser IP67 IK08

### Product Code


5386LL5H.INX

#### Wattage

5 W LED









## Mira 220

#### Features


Decorative fixture (3000 K) Die cast aluminium housing Stainless steel AISI 316L frame Transparent glass diffuser 60° beam angle IP67 IK10

Product Code 5521LL20H.INX 5521LL30H.INX

Wattage 20 W / 30 W LED

Wattage 12 W LED





# Gate Top

- Bungalows
- Villas
- Pavement lighting
- Landscape lighting



## Morphis

#### Features

Decorative fixture (3000 K) Die cast aluminium housing Transparent glass diffuser Grey colour IP65

#### Product Code

177.33L24H.NHG 177.33.NHG

Base Cap / Wattage E27 / 24 W LED





### Monaco

#### Features

Decorative fixture (3000 K) Die cast aluminium housing Transparent glass diffuser Black colour IP43

Product Code 340.33.NGG

Base Cap E27






### Romantica

#### Features

Decorative fixture (3000 K) Die cast aluminium housing Polycarbonate frosted diffuser Black colour IP43


#### Product Code 350.33L10H.NGG

Base Cap E27





Neway



#### Features

Decorative fixture (3000 K) Die cast aluminium housing Polycarbonate diffuser Grey colour IP65

Product Code 405.03L10H.NHG

Wattage 10 W LED

### Firenze




#### Features

Decorative fixture Die cast aluminium housing Glass diffuser Black colour IP43

Product Code 330.33.NGG

Base Cap E27





# Bollard

- Landscape lighting
- Parks
- Lawns
- Colony streets
- Pathways
- Banquet Halls



# Monaco

#### Features


Decorative fixture Die cast aluminium housing Glass diffuser Black colour IP43

Product Code 340.44.NGG

Base Cap E27



## Morphis



#### Features

Decorative fixture (3000 K) Die cast aluminium housing Transparent diffuser Grey colour IP65

Product Code 177.095L24H.NHG

Wattage 24 W LED

### Romantica



#### Features


Decorative fixture Die cast aluminium housing Polycarbonate frosted diffuser Black colour IP43


#### Product Code

350.44L10H.NGG

#### Wattage

10 W LED





#### Features

Decorative fixture (3000 K) Die cast aluminium housing Polycarbonate diffuser Grey colour / wood finish IP65


**Product Code** 405.075L10H.NHG 405.K075L10H.NHG

Wattage 10 W LED

### Neway



### Bollard



#### Features

Decorative fixture Die cast aluminium housing Glass diffuser Black colour IP44

#### Product Code

400.075.NHG


#### Base Cap

E27





All dimensions are in mm 310 COMPLETE LED LIGHTING SOLUTIONS



#### Features

Decorative fixture (3000 K) Die cast aluminium housing Transparent diffuser Grey colour IP65

#### Product Code

404.070L8X1H.NHG 404.070L4X2H.NHG

Wattage 8 / 2 x 4 W LED






404.070L4X2H.NHG



## Titano



Features Decorative fixture Die cast extruded aluminium housing Polycarbonate transparent diffuser Grey colour / wood colour IP65

Product Code 825.K075L10H.NHG

Wattage 10 W LED





- Residential
- Offices
- Hotels
- Banquet Halls
- Malls





### Pisa


#### Features


Decorative fixture Die cast aluminium housing Glass diffuser Black colour IP43

Product Code 300.00.NGG

Base Cap E27

All dimensions are in mm 314 COMPLETE LED LIGHTING SOLUTIONS





## Sirio

#### Features

Decorative fixture Die cast aluminium housing Opal polycarbonate diffuser White / black colour IP43



150.01.NGG

Base Cap E27






### Firenze

Features Decorative fixture Die cast aluminium housing Glass diffuser Black colour IP43

Product Code 330.00.NGG

Base Cap E27





# Morphis

#### Features

Decorative fixture (3000 K) Die cast aluminium housing Transparent diffuser Grey colour IP65

Product Code 175L12H.NHG

Wattage 12 W LED



### Neway

#### Features

Decorative fixture Die cast aluminium housing Polycarbonate diffuser Grey colour IP44


Product Code 405.NHG

Base Cap E27



19.5





## Kubs

Features Decorative fixture (3000 K) Die cast aluminium housing Transparent diffuser Grey colour Narrow beam 10° (up and down) Wide beam 45° (up and down) Narrow beam 10° + wide beam 45° (up and down) IP65

#### Product Code

404LS4X2H.NHG 404LL4X2H.NHG 404LMA4X2H.NHG

Wattage 2 x 4 W LED

### Brick Light

#### Features


Decorative fixture (3000 K) Recess mounted Die cast aluminium housing Polycarbonate diffuser Grey colour IP54

#### **Product Code**


410L6HM.NGG 410M.NGG

Base Cap / Wattage E27 / 6 W









## Mira 65

#### Features


Decorative fixture (3000 K) Recess mounted extruded anodized aluminium housing Opal glass diffuser IP66 IK08

Product Code 4183LL5H.BRZ

Wattage 5 W LED









#### Features

Decorative fixture (3000 K) Die cast aluminium housing Transparent diffuser Grey colour 45° beam angle / 45° beam angle + 45° beam angle (up and down light) IP65

#### **Product Code**

457LL12X1H.NHG 457LL18X2H.NHG

Wattage 12 / 18 W LED



13.8

45° beam angle 457LL12X1H.NHG



45° beam angle 457LL18X2H.NHG

40° beam angle 465LL5X1H.NHG



40° beam angle 465LL5X2H.NHG



45° beam angle 460LL9X1H.NHG



45° beam angle 460LL9X2H.NHG



## Lyras 130

#### Features

17.4

Т 8.2 5.2

13.8 8.6



Decorative fixture (3000 K) Die cast aluminium housing Transparent diffuser Grey colour 40° medium beam angle / 40° medium beam angle (up and down light) 45° medium beam angle /


45° medium beam angle (up and down light) IP66

#### **Product Code**

465LL5X1H.NHG / 465LL5X2H.NHG 460LL9X1H.NHG / 460LL9X2H.NHG

Wattage 1 x 5 / 2 x 5 / 1 x 12 / 2 x 12 W LED





sensor

# Cervinia

#### Features

Decorative fixture

Die cast aluminium housing Opal polycarbonate diffuser Grey colour

Auto sensor with a range of 1-8 mtr (adjustable) IK07

IP54

#### **Product Code**

9008.NHG 9008SEN.NHG

Base Cap E27



# Acqua

sensor •••••

#### Features

Decorative fixture Stainless steel AISI 316L housing Opal polycarbonate diffuser Auto sensor with a range of 1-8 mtr (adjustable) IK07 IP54

Product Code

9100SEN.INX

Base Cap E27







24.5 -







# Pole Lights

- Landscape lighting
- Parks
- Lawns
- Colony streets
- Pathways
- Banquet Halls





30


## Monaco

Features Decorative fixture Die cast aluminium housing Glass diffuser IP43

Product Code 340.PE8.NGG

Base Cap / Wattage 20 W LED





## Romantica

Features

Decorative fixture (3000 K) Die cast aluminium housing Glass diffuser IP43

Product Code 350.PE8L10H.NGG

Wattage 10 W LED





# Morphis

Features Decorative fixture Die cast aluminium housing Glass diffuser IP65

#### **Product Code** 177.300L20H.NHG - 24 W 177.300.NHG - E27 Cap

Wattage 24 W LED





- 57 ----Z

### Morphis

Features

Decorative fixture (3000 K) Die cast aluminium housing Glass diffuser IP65

Product Code 178L24H.P1.NHG

Wattage 24 W LED



# Content

PROJECTOR LIGHTS Luminz Electra Sparklz Splash Illumine Rigel Ossum Garnet	326 327 327 328 328 328 329 329
<b>GROUND BURIAL</b> Castor Hydrus Polaris Ikon	332 332 333 333
GATE TOP Capella Orbiss Irena Reneva Avior Turais Lex Vimio Navis Sentinel	336 337 337 338 338 339 339 340 340

BOLLARD Illumitz Zibal Miram Visio Cone Bollard Orbarix Elumx Cylinder Bollard Disc Bollard	344 345 345 346 346 347 347 348 348
WALL LIGHTS Brightex Breva Lupus Carina Xcellent Octan Alfie Cooper Luke Nash Preston Woody Lima Kira Casper Foot Light	352 353 353 353 354 354 354 355 355 356 356 356 356 357 357 357






# Projector Lights

### Applications:

- Facade lighting
- Accent lighting
- Atriums and columns
- Architectural lighting
- Varied beam angle applications









#### Features

Die cast aluminium housing Transparent tempered glass diffuser Matt grey finish 90 V - 260 V AC Warm white IP65


### Product Code

LSPK03R104XW

#### Wattage

4 x 1 W LED





## Electra

### Features

Die cast aluminium housing Transparent tempered glass diffuser Matt grey finish 90 V - 260 V AC Warm white IP65

### Product Code

LSPK04R108XW

Wattage 1 x 8 W COB LED



## Sparklz

### Features

Die cast aluminium housing Transparent tempered glass diffuser Matt grey finish 90 V - 260 V AC Warm white IP65


### Product Code

LSPK04R112XW

### Wattage

1 x 12 W COB LED





## Splash

### Features

Die cast aluminium housing Transparent tempered glass diffuser Matt grey finish 90 V - 260 V AC Warm white IP54

Product Code LSPK05R112SW

Wattage 1 x 12 W COB LED





### Illumine

### Features

Die cast aluminium housing Transparent tempered glass diffuser Matt grey finish 90 V - 260 V AC Warm white IP54

### Product Code

LSPK05R112XW

### Wattage

1 x 12 W COB LED



## Rigel

### Features

Die cast aluminium housing Clear glass diffuser 90 V - 260 V AC Warm white IP65

### Product Code

LSPK06R103SW

### Wattage

1 x 3 W LED



## Ossum

### Features

304 stainless steel housing Tempered glass diffuser 12 V AC Warm white IP68

### **Product Code**


LSPK68R103SW

### Wattage

3 x 1 W LED

Note: Product has to be used with 12 V AC power supply at the site





## Garnet

### Features

304 stainless steel housing Tempered glass diffuser 12 V AC Warm white IP68

### Product Code

LSPK68R108SW

#### Wattage

8 x 1 W LED

Note: Product has to be used with 12 V AC power supply at the site



## Ground Burial

### Applications:

- Outdoor facade lighting
- Landscape lighting
- Accent lighting



### Castor

#### Features

304 stainless steel ring Transparent tempered glass diffuser Stainless steel finish 90 V - 260 V AC Warm white IP67

### Product Code

LGBL04R301XW

#### Wattage

3 x 1 W LED





## Hydrus

### Features


Die cast aluminium housing 304 stainless steel ring Transparent tempered glass diffuser 90 V - 260 V AC Warm white IP67

Product Code LGBL06R601XW

Wattage 6 x 1 W LED







### Polaris

#### Features

Die cast aluminium housing 304 stainless steel ring Transparent tempered glass diffuser Stainless steel finish 90 V - 260 V AC Warm white IP67

### Product Code

LGBL05R101XW

Wattage 10 x 1 W LED

## Ikon

### Features

Die cast aluminium housing 304 stainless steel ring Transparent tempered glass diffuser 90 V - 260 V AC Warm white IP67

Product Code LGBL07R181XW

Wattage 18 x 1 W LED



# Gate Top

### Applications:

- Bungalows
- Villas
- Pavement lighting
- Landscape lighting



## Capella

### Features


Die cast aluminium housing Clear polycarbonate diffuser Matt grey finish 90 V - 260 V AC Warm white IP65

### Product Code

LGTP03X012XW

#### Wattage

1 x 12 W COB LED (12 W)







## Orbiss

### Features

Die cast aluminium housing Frosted polycarbonate diffuser Matt grey finish 90 V - 260 V AC Warm white IP54

### Product Code

LGTP01X012XW

Wattage 1 x 12 W





### Irena

### Features

Die cast aluminium housing Opal polycarbonate diffuser Matt grey finish 90 V - 260 V AC Warm white IP54

### Product Code

LGTP02X006XW

### Wattage

6 x 1 W LED (6 W)



### Reneva

#### Features

MS housing with PU paint Top canopy made of spun aluminium IP65 IK10

### Product Code

LGTP01X030XW

### Wattage

30 W LED COB

### Avior

### Features


Die cast aluminium housing Heat resistant toughened bell shaped acrylic diffuser MS housing with PU paint Top canopy made of spun aluminium IP65

### Product Code

LGTP04X028XW

Wattage

28 W LED









## Turais

### Features

Die cast aluminium housing Heat resistant toughened glass (clear diffuser) IP65

### Product Code

LGTP02X030XW

### Wattage

30 W mid power LED







### Lex

### Features

Heavy spun aluminium housing PU paint Heavy duty heat resistance / toughened acrylic diffuser IP65

### Product Code

LWLL01X045XW

### Wattage

45 W LED

## Vimio

### Features

Die cast aluminium housing Heat resistant toughened glass diffuser IP65

### Product Code

LGTP05X030XW

Wattage 30 W LED



## Navis

### Features

Die cast aluminium housing Polycarbonate diffuser Powder coated IP65

### Product Code LGTP06X040XC LGTP06X040XW

Wattage 40 W LED





## Sentinel

### Features

Die cast aluminium housing Polycarbonate diffuser Powder coated IP65

### Product Code

LGTP08X060XC / LGTP08X060XW LGTP08X120XC / LGTP08X120XW LGTP08X150XC / LGTP08X150XW

#### Wattage

60 W LED 120 W LED 150 W LED






## Bollard

### Applications:

- Landscape lighting
- Parks
- Lawns
- Colony streets
- Pathways
- Banquet Halls







## Illumitz

### Features

Die cast aluminium housing Frosted polycarbonate diffuser Matt grey finish 90 V - 260 V AC Warm white IP65

Product Code LBLD03R108XW

Wattage 16 x 0.5 W LED






### Features

Die cast aluminium housing Opal white polycarbonate diffuser Matt grey finish 90 V - 260 V AC Warm white IP54

Product Code LBLD04R108XW

### Wattage

16 x 0.5 W LED (8 W)



## Miram

### Features


Die cast aluminium housing Opal white polycarbonate diffuser Matt grey finish 90 V - 260 V AC Warm white IP54

### Product Code LBLD01R305XW

Wattage 3 x 10 x 0.5 W LED







## Visio

### Features


Die cast aluminium housing Tempered glass diffuser Matt grey finish 90 V - 260 V AC Warm white IP54

Product Code LBLD06R108XW

Wattage 1 x 8 W COB LED

All dimensions are in mm
346 COMPLETE LED LIGHTING SOLUTIONS





## Cone Bollard

### Features

Die cast aluminium housing Opal diffuser with in-built LED IP65

Product Code LBLDCON010XW

Wattage 10 W LED






Ø108

### Features

Die cast aluminium housing Tempered glass diffuser Matt grey finish 90 V - 260 V AC Warm white IP54

Product Code LBLD02R108XW

Wattage 1 x 8 W COB LED



## Elumx

### Features

Die cast aluminium housing Opal white polycarbonate diffuser Matt grey finish 90 V - 260 V AC Warm white IP54

Product Code LBLD05R601XW

Wattage 6 x 1 W LED





# Cylinder Bollard

ø140

ø88

### Features


600

Die cast aluminium housing Opal diffuser with in-built LED IP65

Product Code LBLDCYL010XW

Wattage 10 W LED





## Disc Bollard

### Features

Die cast aluminium housing Opal diffuser with in-built LED IP65

Product Code LBLDDSC010XW

Wattage 10 W LED





# Wall Lights

### Applications:

- Residential
- Offices
- Hotels
- Banquet Halls
- Malls



## Brightex


### Features

Die cast aluminium housing Transparent tempered glass diffuser Grey finish 90 V - 260 V AC Up and down light Warm white IP54

### Product Code


LWWL01X208XW

Wattage 2 x 8 W COB LED









Breva

#### Features


Die cast aluminium housing Transparent tempered glass diffuser Matt grey finish 90 V - 260 V AC Warm white IP54

Product Code LWWL01X108XW

Wattage 1 x 8 W COB LED







### Lupus

### Features

Die cast aluminium housing Transparent tempered glass diffuser Matt grey finish 90 V - 260 V AC Up and down light Warm white IP54

### Product Code

LWWL03X203XW

#### Wattage

2 x 3 W COB LED


## Carina

### Features

Die cast aluminium housing Transparent tempered glass diffuser Matt grey finish 90 V - 260 V AC Warm white IP54

Product Code LWWL03X103XW

Wattage 1 x 3 W COB LED







### Features

140

141


Die cast aluminium housing Opal polycarbonate diffuser Matt grey finish 90 V - 260 V AC Up and down light Warm white IP54

### Product Code


LWWL02R206XW

### Wattage

2 x 6 W COB LED







### Octan

#### Features

Die cast aluminium housing Opal polycarbonate diffuser Matt grey finish 90 V - 260 V AC Warm white IP54

### Product Code

LWWL02R108XW

### Wattage

1 x 8 W COB LED

## Alfie


### Features

Die cast aluminium housing SUS304 ring Frosted polycarbonate diffuser Anti-glare 90 V - 260 V AC Warm white IP65


### Product Code LBRK01S105XW

Wattage 10 x 0.5 W LED









### Cooper

### Features

Die cast aluminium housing Transparent tempered glass diffuser Matt grey finish 90 V - 260 V AC Up and down light Warm white IP54

### Product Code

LWWL04X206XW

### Wattage

2 x 6 W COB LED

All dimensions are in mm
354 COMPLETE LED LIGHTING SOLUTIONS









## Luke

### Features

Die cast aluminium housing Opal white polycarbonate diffuser 90 V - 260 V AC Warm white IP54

### Product Code

LBRK02S105XW

#### Wattage

10 x 0.5 W LED



## Nash


### Features

Die cast aluminium housing Transparent tempered glass diffuser Grey finish 90 V - 260 V AC Warm white IP54

### Product Code


LFLT01S105XW

Wattage 10 x 0.5 W LED









### Preston


### Features

Die cast aluminium housing Tempered glass diffuser Grey finish 90 V - 260 V AC Up and down light Warm white IP54

Product Code LWWL02X203XW

Wattage 2 x 3 W LED





### Lima

### Features

Die cast aluminium housing Transparent tempered glass diffuser Matt grey finish 170 V-260 V AC Warm white Wall washer light IP54

### Product Code

LWWL03X012XW


Wattage 1 x 12 W COB LED

#### All dimensions are in mm 356 COMPLETE LED LIGHTING SOLUTIONS

IP54







## Kira

### Features


Die cast aluminium housing Transparent tempered glass diffuser Matt grey finish 90 V - 260 V AC Warm white Wall washer light IP54

### Product Code

LWWL04X012XW

#### Wattage

1 x 12 W COB LED







## Foot Light

#### Features

Die cast aluminium housing Polycarbonate diffuser White and grey finish IP65

#### Product Code

LFTL01S003XW\* LFTLW1S003XW<sup>#</sup>

#### Wattage 3 W LED

\*Grey housing | \*White housing

# Smart Lights

The world of devices is getting smarter and so are Jaquar Lighting products.

For your daily lighting requirements, our in-house R&D has come up with several next generation products.

From a bulb which can be operated using Bluetooth and Wi-Fi, to an emergency bulb with in-built battery to stay lit during power cuts, and motion-sensing battens, downlights and panels which get switched on automatically as you approach.

All these products are designed to need minimal human touch to allow better hygiene, as well as provide ease of operation and save time, effort and energy.

# Content

### SMART LIGHTS

Smart Pole	360
Strella Smart	361
Pride Smart	362
Kubik Smart	362
Starlite Alika Kubik	362
Kriza Emergency Bulb	363
Vivid	363



# FUTURE PRODUCT

### Smart Pole

Next generation street light LED pole with multiple applications, like:

- HI-DEF 360° camera for surveillance
- LED display board for traffic alert, public announcement, weather report and general advertising

Wei

- Electric vehicle charger
- Fully customized wi-fi
- Weather station, which can measure air temperature, noise, air humidity, pressure, wind speed and direction



#### SMART LIGHTS Products

The world is getting smarter and so are the Jaquar Lighting Products. Have a look:





Motion sensor based commercial downlights

Item Code	Wattage (w)	CCT (k)
LSTS01S008XC	8	6500
LSTS01S008XN	8	4000
LSTS01S008XW	8	3000
LSTS01S015XC	15	6500
LSTS01S015XN	15	4000
LSTS01S015XW	15	3000
LSTS01S022XC	22	6500
LSTS01S022XN	22	4000
LSTS01S022XW	22	3000

8 W Cutout: 105 x 105 mm Height: 35 mm
15 W Cutout: 155 x 155 mm Height: 35 mm
22 W Cutout: 205 x 205 mm

Height: 35 mm



# STRELLA

Motion sensor based commercial downlights

			-
Item Code	Wattage (w)	CCT (k)	
LSTS01R008XC	8	6500	
LSTS01R008XN	8	4000	
LSTS01R008XW	8	3000	
LSTS01R015XC	15	6500	
LSTS01R015XN	15	4000	
LSTS01R015XW	15	3000	
LSTS01R022XC	22	6500	
LSTS01R022XN	22	4000	
LSTS01R022XW	22	3000	

8 W Cutout: Ø 105 mm Height: 35 mm
15 W Cutout: Ø 155 mm Height: 35 mm
22 W Cutout: Ø 205 mm Height: 35 mm




Light turns on in presence of motion and will turn off after 2 minutes if there is no motion

#### Technical & Commercial Data:

Input voltage range: 140 - 270 V AC Luminous efficacy: 8 W >80 Lm / W 15 W & 22 W >90 Lm / W Power factor: >0.95 Sensor coverage range: 5-7 meters Mounting height: 3 meter Housing materials: Thermally conductive polycarbonate







Motion sensor based battens

Item Code	Wattage (w)	CCT (k)
LPRD01S040XC	40	6500
LPRD01S040XN	40	4000
LPRD01S040XW	40	3000

**40 W** L x W: 1180 x 86 mm Height: 67 mm



Motion sensor based battens

Item Code	Wattage (w)	CCT (k)
LKBS01S020XC	20	6500
20 W   x W 113	5 x 22 mm	

**20 W** L x W: 1135 x 22 mm Height: 37 mm

DETECTING SENSOR

#### **Benefits:**

- With motion detecting sensor
- 80% energy saving
- IP65 for dust & water-proof
   performance
- Brightness: 0 100%



USP:

Light turns on in presence of motion and will turn off after 2 minutes if there if no motion



Remote control operated batten with tunable colors

Item Code	Wattage (w)	CCT (k)
LSRA01S020DM*	20	WW to CW (Tunable)

Benefits:

- 80% energy saving
- Compact and sleek design
- 2000 Lm lumen output
- Single batten with tunable colors

**20 W** L x W: 1135 x 22 mm Height: 37 mm \*3-in-1 Color option \*Remote control operation



#### NEXT GEN Products

The world is getting smarter and so are the Jaquar Lighting products. Have a look:



Item Code	Wattage (w)	CCT (k)
LVVD07B22RG	9	6500 K



Control the light, any where, any time

Item Code	Wattage (w)	Color
LVVD07B22RG	7	RGB / CW
LVDWF07B2RGB	7	RGB / CW

R/G/B/C/W




6

3 Million colour options

Wireless connection through wi-fi



) Wireless connection bluetooth 4.0 support



 $\begin{array}{c} \begin{array}{c} \begin{array}{c} & \\ \end{array}_{HIGH}^{I} & High \ efficiency \end{array}$ 





# Home Lighting

Make the switch to energy-saving, eco-friendly lighting solutions for your home with Jaquar Lighting's LED products. These maintenance-free, UV / IR radiation-free, glare-free, lamps, panels, battens and strip lights open up exciting new lighting design possibilities and promise cost efficiencies better than ever before.






laguar

### Content

<b>LAMPS</b> Prima HD Spark HD Illuminator/Prima Plus Night Lamps (0.5 W)	368 369 369 369	<b>STREET LIGHTS</b> Hummer PCR Street Lights
BATTERNS Kubik Ultra Kubik Plus Kubik Starlite	372 372 373 373	SPOT LIGHTS Jasper Neo Jasper Plus STRIP LIGHTS Janus Strip Driver
DOWNLIGHTS Pearl/Pearl Plus Glory Striker Strella Lumax Plus Skylite Turnoe Gem Plus	376 377 378 379 380 380 381	

Turnoe Gem Plus	380 381	



### Lamps

From lightening up small space to illuminating an entire room, Jaquar LED lamps bring along holistic lighting solutions. From low wattage night bulbs to high wattage LED lamps, you have a range that fits every budget and requirement.

Bring home Jaquar LED Lamps. And enjoy the extra brightness of happiness! Some examples include:











Full glove diffuser for wide distribution of light

#### Technical & Commercial Data:

Input voltage range: 100 V - 300 V AC Luminous efficacy: 100 Lm / W Power factor: >0.95 Housing material: Overmoulded PC Lot size: 3 W to 14 W- 50 pcs 20 W- 20 pcs

### Prima HD

Product Code	Base Cap	Power (W)	ССТ	Dimension (MM)
LPRM4KV03B2C	B22	3 W	CW	Ф 50 х 92
LPRM4KV03B2W	B22	3 W	WW	Ф 50 х 92
LPRM4KV03E2C	E27	3 W	CW	Ф 50 х 92
LPRM4KV03E2W	E27	3 W	WW	Ф 50 х 92
LPRM4KV05B2C	B22	5 W	CW	Ф 60 х 112
LPRM4KV05B2W	B22	5 W	WW	Ф 60 х 112
LPRM4KV05E2C	E27	5 W	CW	Ф 60 х 112
LPRM4KV05E2W	E27	5 W	WW	Ф 60 х 112
LPRM4KV07B2C	B22	7 W	CW	Ф 60 х 112
LPRM4KV07B2W	B22	7 W	WW	Ф 60 х 112
LPRM4KV07E2C	E27	7 W	CW	Ф 60 х 112
LPRM4KV07E2W	E27	7 W	WW	Ф 60 х 112
LPRM4KV09B2C	B22	9 W	CW	Ф 60 х 112
LPRM4KV09B2W	B22	9 W	WW	Ф 60 х 112
LPRM4KV09E2C	E27	9 W	CW	Ф 60 х 112
LPRM4KV09E2W	E27	9 W	WW	Ф 60 х 112
LPRM012B22CW	B22	12 W	CW	Ф 65 х 118
LPRM012B22 WW	B22	12 W	WW	Ф 65 х 118
LPRM012E27CW	E27	12 W	CW	Ф 65 х 118
LPRM012E27WW	E27	12 W	WW	Ф 65 х 118
LPRM4KV14B2C	B22	14 W	CW	Ф 65 х 126
LPRM4KV14B2W	B22	14 W	WW	Ф 65 х 126
LPRM4KV14E2C	E27	14 W	CW	Ф 65 х 126
LPRM4KV14E2W	E27	14 W	WW	Ф 65 х 126
LPRM4KV20B2C	B22	20 W	CW	Ф 80 х 152
LPRM4KV20B2W	B22	20 W	WW	Ф 80 х 152
LPRM4KV20E2C	E27	20 W	CW	Ф 80 х 152
LPRM4KV20E2W	E27	20 W	WW	Φ 80 x 152








**Technical & Commercial Data:** Input voltage range: 100 V - 300 V AC Luminous efficacy: 100 Lm / W Power factor: >0.95 Housing material: Overmoulded PC Lot size: 50 pcs

### Spark HD

Product Code	Base Cap	Power (W)	ССТ	Dimension (MM)
LSAK4KV05B2C	B22	5 W	CW	Ф 57 х 100
LSAK4KV07B2C	B22	7 W	CW	Ф 57 х 100
LSAK4KV09B2C	B22	9 W	CW	Ф 57 х 102





Input voltage range: 100 V - 300 V AC Luminous efficacy: 100 Lm / W Power factor: >0.95 Housing material: Die cast aluminium Lot size: 10 pcs

# Illuminator/Prima Plus

Product Code	Base Cap	Power (W)	ССТ	Dimension (MM)
LILM030B22CW	B22	30 W	CW	Ф 100 х 180
LILM040B22CW	B22	40 W	CW	Ф 115 х 198
LILM050B22CW	B22	50 W	CW	Ф 125 х 220
LPRP030B22CW	B22	30 W	CW	Ф 100 х 185
LPRP040B22CW	B22	40 W	CW	Ф 120 х 232
LPRP050B22CW	B22	50 W	CW	Ф 142 х 262






Technical & Commercial Data: Input voltage range: 100 V - 300 V AC Luminous efficacy: >40 Lm / W Housing material: Polycarbonate Lot size: 60 pcs

# Night Lamps (0.5 W)

-		-	-	-
Product Code	Base Cap	Power (W)	ССТ	Dimension (MM)
LPRM01R001XC	B22	0.5 W	CW	Φ 45 x 70
LPRM01R001XY	B22	0.5 W	YELLOW	Φ 45 x 70
LPRM01R001XR	B22	0.5 W	RED	Φ 45 x 70
LPRM01R001XG	B22	0.5 W	GREEN	Φ 45 x 70
LPRM01R001XB	B22	0.5 W	BLUE	Φ 45 x 70
LPRM01R001XO	B22	0.5 W	ORANGE	Φ 45 x 70
LPRM01R001XP	B22	0.5 W	PINK	Φ 45 x 70



### Battens


A wide range of environment-friendly LED battens that are sure to brighten up your rooms. From different lumen intensity and colour temperature, we have batten that would suit any home's design.

Choose from a wide variety of options and pick the one that matches your home décor perfectly. Some examples include:




# Kubik Ultra

Product Code	Power (W)	ССТ	Dimension (MM)
LGLZU1X025XC	25 W	CW	1135 x 31 x 40



Mushroom shape batten gives wider distribution as well as decorative design

**Technical & Commercial Data:** Input voltage range: 100 V - 300 V AC Power factor: >0.95 Housing material: Conductive extruded aluminium Lot size: 20 pcs



Input voltage range: 100 V - 300 V AC Luminous efficacy: 6 W - 20 W >100 Lm / W Power factor: >0.95 Housing material: Thermally conductive polycarbonate Lot size: 20 pcs



### Kubik Plus

Product Code	Power (W)	ССТ	Dimension (MM)
LKBP01S006XC	6 W	CW	300 x 22 x 37
LKBP01S006XN	6 W	NW	300 x 22 x 37
LKBP01S006XW	6 W	WW	300 x 22 x 37
LKBP4KV010XC	10 W	CW	575 x 22 x 37
LKBP4KV010XN	10 W	NW	575 x 22 x 37
LKBP4KV010XW	10 W	WW	575 x 22 x 37
LKBP01S018XC	18 W	CW	1135 x 22 x 37
LKBP01S018XW	18 W	WW	1135 x 22 x 37
LKBP4KV020XC	20 W	CW	1135 x 22 x 37
LKBP4KV020XN	20 W	NW	1135 x 22 x 37
LKBP4KV020XW	20 W	WW	1135 x 22 x 37
LKBP01S022XC	22 W	CW	1135 x 31 x 40
LKBP01S022XN	22 W	NW	1135 x 31 x 40
LKBP01S022XW	22 W	WW	1135 x 31 x 40




# Kubik

Product Code	Power (W)	ССТ	Dimension (MM)
LKBK02S020XC	20 W	CW	1145 x 21 x 33
LKBK02S020XN	20 W	NW	1145 x 21 x 33
LKBK02S020XW	20 W	WW	1145 x 21 x 33



#### Technical & Commercial Data:

Input voltage range: 100 V - 300 V AC Luminous efficacy: 100 Lm / W Power factor: >0.95 Housing material: Thermally conductive polycarbonate Lot size: 20 pcs







Changing tri-color from CW to NW to WW in manual switching

**Technical & Commercial Data:** Input voltage range: 100 V - 300 V AC Luminous efficacy: >100 Lm / W Power factor: >0.95 Housing materials: Thermally conductive polycarbonate Lot size: 20 pcs



### Starlite

Product Code	Power (W)	ССТ	Dimension (MM)
LSRE01S020X	20 W	CW/NW/WW	1170 x 24 x 40



# Downlights

High-performance LED downlights that will not only help you in creating ambient lighting but also make a nice addition to the entire decor of your house. A combination of recessed, surface mounted, fixed, and trimless downlights are available in different wattages. You also have the option to choose from round and square shapes as per your requirement: Some examples include:





#### **Technical & Commercial Data:** Input voltage range: 100 V - 300 V AC Luminous efficacy: 3 W >70 Lm / W, 6 W >80 Lm / W, 15 W >90 Lm / W Power factor: >0.9 Housing material: Thermally conductive polycarbonate

Lot size: 20 pcs

Suitable for junction box fitment

# Pearl / Pearl Plus

Product Code	Power (W)	ССТ	Cutout (MM)	Dimension (MM)
LPAL01R003XC	3 W	CW	Φ45	Ф 80 x 45
LPAL01R003XN	3 W	NW	Φ45	Φ 80 x 45
LPAL01R003XW	3 W	WW	Φ45	Φ 80 x 45
LPAL01R003XR	3 W	RED	Φ45	Ф 80 х 45
LPAL01R003XG	ЗW	GREEN	Φ45	Φ 80 x 45
LPAL01R003XB	3 W	BLUE	Φ45	Ф 80 х 45
LPAL01R003XP	3 W	PINK	Φ45	Φ 80 x 45
LPAL01R003XV	3 W	VIOLET / PURPLE	Φ45	Φ 80 x 45
LPAL02R003XC	3 W	CW	Φ45	Φ 80 x 45
LPAL02R003XN	3 W	NW	Φ45	Φ 80 x 45
LPAL02R003XW	3 W	WW	Φ45	Φ 80 x 45
LPAL02R003XR	3 W	RED	Φ45	Φ 80 x 45
LPAL02R003XG	3 W	GREEN	Φ45	Φ 80 x 45
LPAL02R003XB	3 W	BLUE	Φ45	Φ 80 x 45
LPAL02R003XP	3 W	PINK	Φ45	Φ 80 x 45
LPAL02R003XV	3 W	VIOLET / PURPLE	Φ45	Φ 80 x 45
LPPS01R006XC	6 W	CW	Φ45	Ф 80 х 65
LPPS01R006XN	6 W	NW	Φ45	Ф 80 х 65
LPPS01R006XW	6 W	WW	Φ45	Ф 80 х 65
LPPS01R006XR	6 W	RED	Φ45	Ф 80 х 65
LPPS01R006XG	6 W	GREEN	Φ45	Ф 80 х 65
LPPS01R006XB	6 W	BLUE	Φ45	Ф 80 х 65
LPPS01R006XP	6 W	PINK	Φ45	Ф 80 х 65
LPPS01R006XV	6 W	VIOLET / PURPLE	Φ45	Ф 80 х 65
LPPS02R006XC	6 W	CW	Φ45	Ф 80 х 65
LPPS02R006XN	6 W	NW	Φ45	Ф 80 х 65
LPPS02R006XW	6 W	WW	Φ45	Ф 80 х 65
LPPS02R006XR	6 W	RED	Φ45	Ф 80 х 65
LPPS02R006XG	6 W	GREEN	Φ45	Ф 80 х 65
LPPS02R006XB	6 W	BLUE	Φ45	Ф 80 х 65
LPPS02R006XP	6 W	PINK	Φ45	Ф 80 х 65
LPPS02R006XV	6 W	VIOLET / PURPLE	Φ45	Ф 80 х 65
LPPS01R015XC	15 W	CW	Φ45	Ф 140 х 65
LPPS01R015XN	15 W	NW	Φ45	Ф 140 х 65
LPPS01R015XW	15 W	WW	Φ45	Ф 140 х 65
LPPS01R015XR	15 W	RED	Φ45	Ф 140 х 65
LPPS01R015XG	15 W	GREEN	Φ45	Φ 140 x 65
LPPS01R015XB	15 W	BLUE	Φ45	Φ 140 x 65
LPPS01R015XP	15 W	PINK	Φ45	Φ 140 x 65
LPPS01R015XV	15 W	VIOLET / PURPLE	Φ45	Φ 140 x 65

#### Downlights



# Glory

<u> </u>				
Product Code	Power (W)	ССТ	Cutout (MM)	Dimension (MM)
LGOR01S003XC	ЗW	CW	Φ73	92 x 92 x 54
LGOR01S003XN	ЗW	NW	Φ73	92 x 92 x 54
LGOR01S003XW	ЗW	WW	Φ73	92 x 92 x 54
LGOR01R003XC	ЗW	CW	Φ73	Ф 92 x 54
LGOR01R003XN	ЗW	NW	Φ73	Ф 92 x 54
LGOR01R003XW	3 W	WW	Φ73	Ф 92 x 54
LGOR01S006XC	6 W	CW	Φ84	113 x 113 x 65
LGOR01S006XN	6 W	NW	Φ84	113 x 113 x 65
LGOR01S006XW	6 W	WW	Φ84	113 x 113 x 65
LGOR01R006XC	6 W	CW	Φ84	Ф 113 x 65
LGOR01R006XN	6 W	NW	Φ84	Ф 113 x 65
LGOR01R006XW	6 W	WW	Φ84	Ф 113 x 65
LGOR01R006XR	6 W	RED	Φ84	Ф 113 x 65
LGOR01R006XG	6 W	GREEN	Φ84	Ф 113 x 65
LGOR01R006XB	6 W	BLUE	Φ84	Ф 113 x 65
LGOR01R006XP	6 W	PINK	Φ84	Ф 113 x 65
LGOR01R006XV	6 W	VIOLET / PURPLE	Φ84	Ф 113 x 65
LGOR02S006XC	6 W	CW	Φ84	113 x 113 x 65
LGOR02S006XN	6 W	NW	Φ84	113 x 113 x 65
LGOR02R006XC	6 W	CW	Φ84	Ф 113 x 65
LGOR02R006XN	6 W	NW	Φ84	Ф 113 x 65
LGOR02R006XW	6 W	VVVV	Φ84	Ф 113 x 65
LGOR02R006XR	6 W	RED	Φ84	Ф 113 x 65
LGOR02R006XG	6 W	GREEN	Φ84	Ф 113 x 65
LGOR02R006XB	6 W	BLUE	Φ84	Ф 113 x 65
LGOR02R006XP	6 W	PINK	Φ84	Ф 113 x 65
LGOR02R006XV	6 W	VIOLET / PURPLE	Φ84	Ф 113 x 65
LGOR01S010XC	10 W	CW	Φ 104	127 x 127 x 70
LGOR01S010XN	10 W	NW	Φ 104	127 x 127 x 70
LGOR01S010XW	10 W	WW	Φ 104	127 x 127 x 70
LGOR01R010XC	10 W	CW	Φ 104	Φ 125 x 70
LGOR01R010XW	10 W	WW	Φ 104	Φ 125 x 70



Long life

Beam angle >120°

#### **Technical & Commercial Data:**

Input voltage range: 100 V - 300 V AC Luminous efficacy: 3 W >70 Lm / W, 6 W >75 Lm / W, 10 W >85 Lm / W Power factor: >0.9 Housing material: Thermally conductive polycarbonate Lot size: 20 pcs Suitable for junction box filament



Input voltage range: 100 V - 300 V AC Luminous efficacy: >75 Lm / W Power factor: >0.95 Housing material: Thermally conductive polycarbonate with aluminium heat sink Lot size: 20 pcs Suitable for junction box filament

Product Code	Power (W)	ССТ	Cutout (MM)	Dimension (MM)
LSTK01R006XC	6 W	CW	Φ83	Φ 108 x 62
LSTK01R006XN	6 W	NW	Φ83	Ф 108 х 62
LSTK01R006XW	6 W	VVVV	Φ83	Ф 108 x 62
LSTK01R006XR	6 W	RED	Φ83	Ф 108 x 62
LSTK01R006XG	6 W	GREEN	Φ83	Ф 108 x 62
LSTK01R006XB	6 W	BLUE	Φ83	Ф 108 x 62
LSTK01R006XP	6 W	PINK	Φ83	Ф 108 x 62
LSTK01R006XV	6 W	VIOLET / PURPLE	Φ83	Ф 108 х 62







Beam angle >120°

Technical & Commercial Data: Input voltage range: 100 V - 300 V AC Luminous efficacy: >90 Lm / W Power factor: >0.95 Housing material: Thermally conductive polycarbonate Lot size: 20 pcs

### Strella

Product Code	Power (W)	ССТ	Cutout (MM)	Dimension (MM)
LSTA4KVR05XC	5 W	CW	Φ75	Ф 80 х 35
LSTA4KVR05XN	5 W	NW	Φ75	Ф 80 х 35
LSTA4KVR05XW	5 W	WW	Φ75	Ф 80 х 35
LSTA01S008XC	8 W	CW	105 x 105	116 x 116 x 35
LSTA01S008XN	8 W	NW	105 x 105	116 x 116 x 35
LSTA01S008XW	8 W	WW	105 x 105	116 x 116 x 35
LSTA01R008XC	8 W	CW	Φ 105	Ф 116 х 35
LSTA01R008XN	8 W	NW	Φ 105	Ф 116 х 35
LSTA01R008XW	8 W	WW	Φ 105	Ф 116 х 35
LSTA4KVR12XC	12 W	CW	Φ 155	Ф 165 х 35
LSTA4KVR12XN	12 W	NW	Φ 155	Ф 165 х 35
LSTA4KVR12XW	12 W	WW	Φ 155	Ф 165 х 35
LSTA01S015XC	15 W	CW	155 x 155	165 x 165 x 35
LSTA01S015XN	15 W	NW	155 x 155	165 x 165 x 35
LSTA01S015XW	15 W	WW	155 x 155	165 x 165 x 35
LSTA01R015XC	15 W	CW	Φ 155	Ф 165 х 35
LSTA01R015XN	15 W	NW	Φ 155	Ф 165 х 35
LSTA01R015XW	15 W	WW	Φ 155	Ф 165 х 35
LSTA01S022XC	22 W	CW	205 x 205	220 x 220 x 35
LSTA01S022XN	22 W	NW	205 x 205	220 x 220 x 35
LSTA01S022XW	22 W	WW	205 x 205	220 x 220 x 35
LSTA01R022XC	22 W	CW	Φ 205	Ф 220 х 35
LSTA01R022XN	22 W	NW	Φ 205	Ф 220 х 35
LSTA01R022XW	22 W	WW	Φ 205	Ф 220 х 35






#### Technical & Commercial Data:

Input voltage range: 100 V - 300 V AC Luminous efficacy: >75 Lm / W Power factor: >0.95 Housing material: Die cast aluminium Lot size: 3 W - 6 W- 20 pcs 12 W - 22 W- 10 pcs

### Lumax Plus

Product Code	Power (W)	ССТ	Cutout (MM)	Dimension (MM)
LLMP01S003XC	3 W	CW	74 x 74	85 x 45 x 20
LLMP01S003XN	3 W	NW	74 x 74	85 x 45 x 20
LLMP01S003XW	3 W	WW	74 x 74	85 x 45 x 20
LLMP01R003XC	3 W	CW	Φ74	Φ 85 x 20
LLMP01R003XN	ЗW	NW	Φ74	Φ 85 x 20
LLMP01R003XW	ЗW	WW	Φ74	Φ 85 x 20
LLMP01S006XC	6 W	CW	105 x 105	121 x 121 x 20
LLMP01S006XN	6 W	NW	105 x 105	121 x 121 x 20
LLMP01S006XW	6 W	WW	105 x 105	121 x 121 x 20
LLMP01R006XC	6 W	CW	Φ 105	Φ 121 x 20
LLMP01R006XN	6 W	NW	Φ 105	Φ 121 x 20
LLMP01R006XW	6 W	WW	Φ 105	Φ 121 x 20
LLMP01S012XC	12 W	NW	155 x 155	171 x 171 x 20
LLMP01S012XN	12 W	WW	155 x 155	171 x 171 x 20
LLMP01S012XW	12 W	CW	155 x 155	171 x 171 x 20
LLMP01R012XC	12 W	NW	Φ 155	Φ 171 x 20
LLMP01R012XN	12 W	WW	Φ 155	Φ 171 x 20
LLMP01R012XW	12 W	CW	Φ 155	Ф 171 x 20
LLMP01S015XC	15 W	CW	155 x 155	171 x 171 x 20
LLMP01S015XN	15 W	NW	155 x 155	171 x 171 x 20
LLMP01S015XW	15 W	WW	155 x 155	171 x 171 x 20
LLMP01R015XC	15 W	CW	Φ 155	Ф 171 x 20
LLMP01R015XN	15 W	NW	Φ 155	Φ 171 x 20
LLMP01R015XW	15 W	WW	Φ 155	Ф 171 x 20
LLMP01S018XC	18 W	CW	175 x 175	190 x 190 x 20
LLMP01S018XN	18 W	NW	175 x 175	190 x 190 x 20
LLMP01S018XW	18 W	WW	175 x 175	190 x 190 x 20
LLMP01R018XC	18 W	CW	Φ 175	Φ 190 x 20
LLMP01R018XN	18 W	NW	Φ 175	Φ 190 x 20
LLMP01R018XW	18 W	WW	Φ 175	Φ 190 x 20
LLMP01S022XC	22 W	CW	206 x 206	225 x 225 x 20
LLMP01S022XN	22 W	NW	206 x 206	225 x 225 x 20
LLMP01S022XW	22 W	WW	206 x 206	225 x 225 x 20
LLMP01R022XC	22 W	CW	Φ 206	Ф 225 х 20
LLMP01R022XN	22 W	NW	Φ 206	Ф 225 х 20
LLMP01R022XW	22 W	WW	Φ 206	Ф 225 х 20





**Technical & Commercial Data:** Input voltage range: 100 V - 300 V AC Luminous efficacy: >105 Lm / W Power factor: >0.95 Housing material: CRCA Lot size: 5 pcs



### Skylite

Product Code	Power (W)	ССТ	Dimension (MM)
LSKL01S036XC	36 W	CW	595 x 595 x 36



Technical & Commercial Data: Input voltage range: 100 V - 300 V AC Luminous efficacy: >70 Lm / W Power factor: >0.95 Housing material: Sheet metal Lot size: 5 pcs



Turnoe			
Product Code	Power (W)	ССТ	Dimension (MM)
LZET03R015XC	15 W	CW	Ф 300 х 85



**Technical & Commercial Data:** Input voltage range: 100 V - 300 V AC Luminous efficacy: >90 Lm / W Power factor: >0.95 Housing material: Die cast aluminium Lot size: 10 pcs



### Gem Plus

Product Code	Power (W)	ССТ	Cutout (MM)	Dimension (MM)
LGMP01R005XC	5 W	CW	Φ70	Ф 85 х 55
LGMP01R005XN	5 W	NW	Φ70	Ф 85 х 55
LGMP01R005XW	5 W	WW	Φ70	Ф 85 х 55
LGMP01R010XC	10 W	CW	Φ70	Ф 85 х 70
LGMP01R010XN	10 W	NW	Φ70	Ф 85 х 70
LGMP01R010XW	10 W	WW	Φ70	Ф 85 х 70
LGMP01R015XC	15 W	CW	Φ90	Φ 110 x 85
LGMP01R015XN	15 W	NW	Φ90	Φ 110 x 85
LGMP01R015XW	15 W	WW	Φ90	Φ 110 x 85
LGMP01R020XC	20 W	CW	Φ110	Ф 140 х 95
LGMP01R020XN	20 W	NW	Φ110	Ф 140 х 95
LGMP01R020XW	20 W	WW	Φ110	Ф 140 х 95



### Street Lights

The idea of a safe city is actually incomplete without proper smart street light for which we need smart street lighting systems, because we step in and out from our home frequently during night. Jaquar Lighting street lights are made for high-performance and are engineered to withstand tough weather conditions. Available in a range of 20-30 watts, these street lights emit a warm, subtle light that makes the streets all the safer and happier with their beautiful, comfortable lighting

#### Street Lights



Technical & Commercial Data: Input voltage range: 100 V - 300 V AC Luminous efficacy: >100 Lm / W THD: <10% IP: 65 Housing material: Die cast aluminium Lot size: 10 pcs



### Hummer

Product Code	Power (W)	ССТ	Pole Mounting Dimensions (MM)	Dimension (MM)
LHMR01SL020C	20 W	CW	Φ40	320 x 75 x 60
LHMR01SL030C	30 W	CW	Φ40	320 x 75 x 60



Input voltage range: 100 V - 300 V AC Luminous efficacy: >100 Lm / W THD: <10% IP: 66 Housing material: Die cast aluminium Lot size: 10 pcs



### PCR

Product Code	Power (W)	ССТ	Pole Mounting Dimensions (MM)	Dimension (MM)
LPCRSRT25WXC	25 W	CW	Φ 42	330 x 117 x 67



Technical & Commercial Data: Input voltage range: 100 V - 300 V AC Luminous efficacy: >100 Lm / W THD: <10% IP: 65 Housing material: Die cast aluminium Lot size: 10 pcs



### Street Light

	$\cup$			
Product Code	Power (W)	ССТ	Pole Mounting Dimensions (MM)	Dimension (MM)
LSRT01F025C	28 W	CW	Φ 42	325 x 145 x 65





# Spot Lights

Jaquar LED spotlights are a beautiful addition to your decor and also help you in highlighting the essential things and driving attention towards the things that you want. Our energy- efficient spot lights come in different colour temperatures to give you decor a vibrant look

#### Spot Lights



Long life CRI >70 Beam angle >30°

Technical & Commercial Data: Input voltage range: 100 V - 300 V AC Luminous efficacy: >50 Lm / W

Luminous efficacy: >50 Lm / W Housing material: Thermally conductive polycarbonate Lot size: 50 pcs



### Jasper Neo

Power (W)	ССТ	Cutout (MM)	Dimension (MM)
2 W	CW	Φ 32	Ф 42 x 16
2 W	WW	Φ 32	Ф 42 х 16
2 W	RED	Φ 32	Ф 42 х 16
2 W	GREEN	Φ 32	Ф 42 х 16
2 W	BLUE	Φ 32	Ф 42 х 16
	(W) 2 W 2 W 2 W 2 W 2 W	(W)2 WCW2 WWW2 WRED2 WGREEN	(W)         (MM)           2 W         CW         \$\$\Phi\$ 32           2 W         WW         \$\$\$\Phi\$ 32           2 W         RED         \$\$\$\$\$32           2 W         GREEN         \$






**Technical & Commercial Data:** Input voltage range: 100 V - 300 V AC Luminous efficacy: >50 Lm / W CRI: >80 Beam angle: >30° Housing material: Aluminium Lot size: 50 pcs



### Jasper Plus

Product Code	Power (W)	ССТ	Cutout (MM)	Dimension (MM)
LJPP01S002XC	2 W	CW	Φ28	39 x 39 x 28
LJPP01S002XW	2 W	WW	Φ28	39 x 39 x 28
LJPP01R002XC	2 W	CW	Φ28	Ф 39 х 28
LJPP01R002XW	2 W	WW	Φ28	Ф 39 х 28
LJPP01R002XR	2 W	RED	Φ28	Ф 39 х 28
LJPP01R002XG	2 W	GREEN	Φ28	Ф 39 х 28
LJPP01R002XB	2 W	BLUE	Φ28	Ф 39 х 28
LJPP02R002XC	2 W	CW	Φ28	Ф 39 х 28
LJPP02R002XW	2 W	WW	Φ28	Ф 39 х 28
LJPP02R002XR	2 W	RED	Φ28	Ф 39 х 28
LJPP02R002XG	2 W	GREEN	Φ28	Ф 39 х 28
LJPP02R002XB	2 W	BLUE	Φ28	Ф 39 х 28





# Strip Lights

Be it festive lighting or the need to decorate any contour of your home, these flashy lighting effects highlight the beautiful parts of your house and look really pleasing. From blue LED strip lights to white LED strip lights, there is a wide range of options to choose from. They come in 5 meter roll with specific cut points which can bend into any shape



#### **Technical & Commercial Data:**

Input voltage range: 12 V DC (with adapter) Luminous efficacy: >90 Lm / W Roll: 5 meter with cut points No. of LEDs: 60 LEDs / meter Lot size: 5 pcs



### Janus

Product Code	Power (W)	ССТ	Dimension (MM)
LJNS02S012XC	24 W	CW	8 x 2.25
LJNS02S012XN	24 W	NW	8 x 2.25
LJNS02S012XW	24 W	VVVV	8 x 2.25
LJNS02S012XR	24 W	Red	8 x 2.25
LJNS02S012XG	24 W	Green	8 x 2.25
LJNS02S012XB	24 W	Blue	8 x 2.25
LJNS01S012XC	24 W	CW	8 x 2.25
LJNS01S012XW	24 W	VVVV	8 x 2.25



# Strip Driver

Product CodePower<br/>(V)LSTD02A012X12 DC

392 COMPLETE LED LIGHTING SOLUTIONS



#### **JAQUAR GROUP**

Global Headquarters, Plot No. 3, Sector-11, IMT Manesar, Gurugram-122050 India For more information: Visit any of our 21 Orientation Centres or log on to www.jaquarlighting.com, e-mail: ccare.lighting@jaquar.com For any query call: 18002126808 (Toll Free)

#### **ORIENTATION CENTRES:**

AHMEDABAD: Ground Floor, Commerce House-4, B/S Shell Petrol Pump, Near Anand Nagar Cross Roads, 100 Ft. Road, Prahlad Nagar, Satellite, Ahmedabad Ph.: 079-30452600 Email: ahmedabad@jaquar.com

**BANGALORE:** No. 10, V.N. Street, Next to Hotel Ramada, Shivaji Nagar, Tasker Town, Bangalore-560051 Email: bangalore@jaquar.com

**BHOPAL:** T- 7, 8, 3rd Floor, City Center, Above Lotus Electronics, 1 Press Complex, M. P. Nagar, Zone-1, Bhopal- 462011 Ph.: 0755-6550888 Email: bhopal@jaquar.com

BHUBANESWAR: Plot No. 853/1671, 2nd Floor, Jharpada, Cuttack Road, Bhubaneswar-751006 Ph.: 0674-2575501 Email: bhubaneswar@jaquar.com

CHANDIGARH: S.C.O. 52-53, Sector 17-A, Opp. Hotel Park Plaza, Adjacent to Fab India, Chandigarh-160017 Ph.: 0172-4071727 Email: chandigarhoc@jaquar.com

**CHENNAI:** Ground Floor, KGN Towers, #62, Ethiraj Salai, Egmore, Chennai- 600008 Phone: 044-42693001 Email: chennai@jaquar.com

**COCHIN:** No. 35/563, Opposite International Stadium, Palarivattom P.O., Cochin-682025 Email: cochin@jaquar.com **GUWAHATI:** "Swagota Envission" Ground Floor, G.S. Road, Sixmile, Khanapara (Opp. Directorate of Agriculture, Assam) Guwahati-781022 Email: guwahati@jaquar.com

**HYDERABAD:** Unit No. 202, Reliance Classic, Banjara Hills, Road No.1, Hyderabad-500034 Email: hyderabad@jaquar.co

JAIPUR: Neelkanth, 1 Bhawani Singh Road, Opp. Nehru Sehkar Bhawan, C-Scheme, Jaipur-302001 Ph.: 0141-5115609 Email: jaipur@jaquar.com

JAMMU: Bonny Square, NH Bypass, Near Vishal Mega Mart, Kunjwani, Jammu-180010 Ph.: 0191-2484876 Email: jammu@jaquar.com

KOLKATA: 2nd Floor, 55, Chowringhee Road, Kolkata-700071 Ph.: 033-40054891 Email: kolkata@jaquar.com

LUCKNOW: Asha Bhawan, 27/II A, Gokhle Marg, Lucknow Ph.: 0522-4001434 Email: lucknow@jaquar.com

LUDHIANA: 2nd Floor, Lodhi Complex, Mall Road, Ludhiana-141001 Ph.: 0161-5094974 Email: ludhiana@jaquar.com MUMBAI: 101,102,103, Kamla Spaces, Above Kohinoor Electronics, S.V. Road, Santacruz West, Mumbai-400054 Ph.: 022-26613279 Email: mumbai@jaquar.com

NAGPUR: Kala Bhavan, 103/A, South Ambazari Road, Shradhanand Peth Square, Laxmi Nagar, Nagpur-440022 Ph.: 0712-2223395 Email: nagpur@jaquar.com

NEW DELHI: D-56, Defence Colony, New Delhi-110024 Ph.: 011-24636807 Email: delhincr@jaquar.com

PUNE: DSK Gandharva Heights, 5th Floor, Office No. 501, Near Hotel Pride Executive, Ganeshkhind Road, Shivajinagar, Pune-411005 Email: pune@jaquar.com

RAIPUR: M K Planet, Ring Road No. 1, New Rajendra Nagar, Raipur-492001. Ph.: 0771-6556789 Email: raipur@jaguar.com

**SILIGURI:** 1st Floor, M-Square Building, Opp. Hotel Sachitra, 2 ½ Mile, Sevoke Road, Siliguri-734002 Email: siliguri@jaquar.com

**SURAT:** 23, Siddhi Shopping Centre, Near Agrasen Bhavan Char Rasta, City Light Road, Surat Email: suratcare@jaquar.com



CALL PURCHASE ASSISTANCE 1800-120-332222 (Toll Free)

And we'll make it easy!

Speak to our Lighting Experts, who will suggest the right product that you should go in for and where to buy it from

Jaquar