





























732 Camera	Model	Description	MRP
Turbo HD Analog Camera IP/ECO series			
 2MP	DS-2CE56D0T-IRP (2MP Dome)	2MP CMOS Sensor , 12pcs LEDs, 2.8mm LENS Upto 20m IR, 1080p@25fps, 0 lux with IR CR0.02lux/F1.2, 12VDC, Smart IR , DWDR SD Menu, DNR, DWDR , Indoor IR Turret	Rs. 2,478
 2MP	DS-2CE16D0T-IRP (2MP Bullet)	2MP CMOS Sensor , 12pcs LEDs, 3.6mm LENS Upto 20m IR, Outdoor IR Bullet ICR 0.02lux/F1.2, 12VDC, IP66, 1080p@25fps OSD Menu, 2D DNR, DWDR	Rs. 2,757
Value Series Turbo HD Analog Camera			
 2MP	2MP Dome DS-2CE76D0T-ITPFS	2MP CMOS Sensor , 2.8,3.6, 6mm Lens upto 20m IR, 1080p@30fps, 1920x1080 ICR 0.01lux/F1.2, 12VDC, Smart IR , DWDR OSD Menu, DNR , Indoor IR Turret	Rs. 3,287
 2MP	2MP Bullet DS-2CE16D0T-ITPFS	2MP CMOS Sensor , 2.8,3.6, 6mm Lens upto 25m IR, 1080p@30fps, 1920x1080 ICR 0.01lux/F1.2, 12VDC, Smart IR DWDR OSD Menu, DNR, Indoor IR Bullet	Rs. 3,433
2MP HD Straight Value Series			
 2MP	DS-2CE12D0T-PIRL (2MP Bullet)	2MP CMOS Sensor , 2.8/3.6 LENS, IP67 Upto 20m IR, Smart IR , Alarm light , ACGICR 0.01lux/F1.2, 12VDC, 1080p@25fps PIR Detection , Light Alarm , 20m PIR Range/light	Rs. 4,635
Turbo HD Vari-Focal Camera			
 2MP	DS-2CE16D0T-VFIR3F (2MP Varifocal)	2MP CMOS Sensor , 2.8-12mm LENS, BLC upto 40m IR, DNR, IP66, OSD menu, Day/Night ICR , color 0.01lux/F1.2, 12VDC, smart IR , 1080p@25fps Pan (0-360)°, Tilt (0-90)°, Rotate (0-360)°	Rs. 7,519








Turbo HD 5.0 FC-Series Color VU Camera			
  	<p>DS-2CE70DF0T-PF (2MP Bullet)</p>	<p>2MP CMOS Sensor, 2.8/3.6/6mm LENS, BLC, HLC, White-light upto 20m , 3D DNR, OSD ,menucolor, 0.001lux/F1.0, 12VDC, Full time color 1080p@25fps, True DWDR, smart light</p>	<p>Rs.4,220</p>
  	<p>DS- 2CE10DF0T-PF (2MP Bullet)</p>	<p>2MP CMOS Sensor, 2.8/3.6/6mm LENS, BLC White-light upto 20m , 3D DNR, IP67, OSD menu color 0.001lux/F1.0, 12VDC, Full time color, 1080p@25fps/30fps, True DWDR, smart light</p>	<p>Rs. 4,363</p>
  	<p>DS-2CE12DF0T-F (2MP Bullet)</p>	<p>1920×1080, 2 MP CMOS, Digital WDR, 3D DNR/2D DNR, 0.001 Lux @ F1.0, 2.8 mm, 3.6 mm, 6 mm Fixed Lens, DWDR, BLC, HLC, Global, IP67</p>	<p>Rs. 5,527</p>
5MP EXIR Camera			
 	<p>DS-2CE16H0T-ITPF (5MP Bullet)</p>	<p>5MP CMOS sensor, 2.8/3.6/6mm LENS, BLC,DWDR Upto 20m IR, EXIR 2.0, Smart IR, IP67 ICR 0.01lux/F1.2, 12VDC, OSD menu, 2D DNR 5 MP@20fps, 4 MP@25fps, 1080p@25fps, IR cutfilter</p>	<p>Rs. 4,483</p>
 	<p>DS-2CE76H0T-ITPF (5MP Dome)</p>	<p>5MP CMOS sensor, 2.4/2.8/3.6/6mm LENS, BLC,DWDR, Upto 20m IR, EXIR 2.0, Smart IR,IP67 ICR 0.01lux/F1.2, 12VDC, OSD menu, 2D 5M@20fps, 4M@30fps, 4M@25fps, 1080p@30fps, 1080p@25fps, IR cut filter</p>	<p>Rs. 4,483</p>









eDVR Series			
	DS-E04HGHI-B (4-ch 4MP Lite ID H.265 eSSD DVR)	H.265 Pro/H.265 video compression, 1-ch IP video input, Upto 6MP resolution, 12 VDC , eSSD technology, motion detection 2.0 , 4 MP Lite/1080p/720p/WD1/4CIF/QVGA/CIF	Rs. 14,026
	DS-E08HGHI-B (8-ich 1080p lite U H.265 eSSD DVR)	H.265 Pro/H.265 video compression, 1080p Lite/720p/WD1/4CIF/CIF, Up to 1080p Lite@30 fps encoding capability, motion detection 2.0 , 2-ch IP video input, Up to 5 MP resolution, 8-ch analog video input, 12 VDC	Rs. 16,033
	DS-E04HGQHI-B (4-ich 4MP lite 1U H.265 eSSD DVR)	H.265 Pro/H.265 video compression, 4 MP Lite/1080p/720p/WD1/4CIF/QVGA/CIF, , Motion Detection 2.0 , HDTVI/AHD/CVI/CVBS/IP video inputs, Up to 4 MP Lite@15 fps encoding, 1-ch IP Video input, 4-ich analog video input, 12 VDC	Rs. 16,599
HD DVR (7100-Series)			
	DS-7104HGHI-k1 (4-Channel Turbo HD DVR)	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 video compression video compression, 4-ch analog Video output, 1 SATA Interface upto 4 TB capacity for each disk, Support 1080p Lite of all channels	Rs. 7,272
	DS-7108HGHI-k1/N (8-Channel Turbo HD DVR)	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 video compression, 8-ch analog Video output, 1 SATA interface (up to 4 TB capacity, motion detection 2.0	Rs. 9,349
	DS-7116HGHI-K1 (16-Channel Turbo HD DVR)	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 video compression, 16-ch analog Video output, 1 SATA Interface upto 10 TB capacity, Hik-Connect & DDNS, Support 1080p Lite of all channels	Rs. 16,622
H.265+ Series HD DVRs (7100-Series)			
	DS-7104HQHI-K1(S) [4-Channel TURBO HD DVR (4MP Lite)]	H.265 Pro+/H.265 Pro/H.265 video compression, Up to 6 TB capacity per HDD, Support the 3rd party cloud storage, Hik-Connect & DDNS, 32 Kbps to 6 Mbps video bit rate	Rs.9,894









	DS-7108HQHI-K1(S) [8-Channel TURBO HD DVR (4MP Lite)]	H.265 Pro+/H.265 Pro/H.265 video compression, Max. 800 m for 1080p and 1200 m for 720p HDTV, Up to 6 TB capacity per HDD, Hik-Connect & DDNS	Rs. 15,502
	DS-7116HQHI-K1(S) [16-Channel DVRTURBO HD DVR (4MP Lite)]	H.265 Pro+/H.265 Pro/H.265 video compression, Up to 10 TB capacity per HDD, HDTV/AHD/CVI/CVBS/IP video input, Hik-Connect & DDNS 32 Kbps to 10 Mbps video bit rate	Rs. 26,055
H.265 AcuSense DVR			
	iDS-7204HUHI-M1/S (4-Channel)	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 video compression, Up to 8/16-ch IP camera inputs (up to 8 MP) , Up to 10 TB capacity per HDD, Recording at up to 8 MP resolution, 32 Kbps to 10 Mbps video bitrate	Rs. 16,337
	iDS-7208HQHI-M2/S (8-Channel)	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 video compression, Up to 12/24-ch IP camera inputs (up to 6 MP), Up to 10 TB capacity per HDD, Two SATA interfaces, HDTV/AHD/CVI/CVBS/IP video inputs	Rs. 19,435
	iDS-7208HUHI-M1/S (4-Channel)	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 video compression, HDTV/AHD/CVI/CVBS/IP video inputs, Hik-Connect & DDNS, Up to 8/16-ch IP camera inputs (up to 8 MP), Up to 10 TB capacity per HDD, 32 Kbps to 10 Mbps video bitrate	Rs. 27,604









IP Cameras			
 2MP	DS-2CD1323G0E-I (2MP Dome)	1/2.8" CMOS Sensor, H.265+, 3D DNR, IP67 Upto 30m IR, BLC, AGC, HLC, DWDR, Day/Night ICR F/1.2 aperture, 12VDC, ONVIF, Smart IR cut Filter 1920x1080@25fps(P)/30fps(N), 2.8mm Lens	Rs. 6,461
 2MP	DS-2CD1123G0E-I (2MP Dome)	1/2.7" Progressive CMOS, H.265, 2.8/4mm LENS Upto 30m IR, Fixed IR Dome, Smart IR, IP67, ICR 0.01lux/F2.0, 12VDC, 3DNR, BLC, ONVIF 1920x1080:25fps(P)/30fps(N), IK10, Vandal Proof	Rs. 7,167
	DS-2CD1T23G0-I (2 MP Fixed Bullet)	High quality imaging with 2 MP resolution Clear imaging against strong back light due to DWDR technology Efficient H.265+ compression technology Water and dust resistant (IP67), 1/2.8" Progressive Scan CMOS	Rs. 6,461
	DS-2CD1323G0-IU (2MP Dome)	1/2.8" CMOS Sensor, H.265+/H.265/H.264+/H.264, 3D DNR, IP66 Up to 30m IR, BLC, AGC, HLC, DWDR, Day/Night ICR F/2.0 aperture, 12VDC, ONVIF, Built In MIC	Rs. 7,935
	DS-2CD1023G0E-I (2MP Bullet)	1/2.8" Progressive CMOS, H.265, 2.8/ 4mm LENS Upto 30m IR, Fixed IR Bullet, Smart IR, IP67 ICR 0.01lux/F2.0, 12 VDC, 3DNR, BLC, ONVIF, 1920x1080:25fps(P)/30fps(N) resolution	Rs. 6,461
	DS-2CD1023G0-IU (2MP Bullet)	2 MP resolution, H.265+ compression technology, 0.028 Lux @ (F2.0, AGC ON), Up to 30m IR range, Clear imaging even with strong back, lighting due to DWDR technology Water and dust resistant (IP67) G.711/G.722.1/G.726/MP2L2/PCM (audio compression)	Rs. 7,935







 <p>4MP</p>	<p>DS-2CD1043G0E-I (4MP Bullet)</p>	<p>1/3" Progressive CMOS, H.265+, 2.8-4mm LENS Upto 30m IR, Outdoor IR Bullet, 3D DNR, IP67 0.028lux/F2.0, 12VDC, HLC, BLC, ROI, DWDR 4MP/2560x1440@20fps(P)/(N)</p>	<p>Rs. 9,864</p>
 <p>4MP</p>	<p>DS-2CD1343G0E-I (4MP Dome)</p>	<p>1/3" CMOS Sensor, H.265, H.265+, H.264, H.264+, 2560 × 1440@20fps 3D DNR, IP67 Up to 30m IR, BLC, HLC, DWDR, Day/Night ICR F/2.0 aperture, 12VDC, ONVIF, 3-axis adjustment, 2.8/4 mm fixed lens</p>	<p>Rs. 9,864</p>
 <p>5MP</p>	<p>DS-2CD1053G0-I (5MP Bullet)</p>	<p>1/2.7" CMOS Sensor, H.265+, 3D DNR, IP67, Upto 30m IR, BLC, Day/Night ICR, WDR 120dB F/2.0 aperture, 12VDC, ONVIF, 32kbps to 16Mbps video bit rate, 2560x1920@20fps(P)/30fps(N)</p>	<p>Rs. 13,129</p>
Color VU Lite Network Camera			
 <p>2MP</p>	<p>DS-2CD1327G0-L (2MP Dome)</p>	<p>1/2.8" Progressive CMOS, H.265+, 2.8mm/ 4 mm fixed LENS White-light upto 30m , 3D DNR, Digital WDR , IP67,ONVIF color 0.001lux/F1.0, 12VDC, 24x7 Main Stream: 50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720)</p>	<p>Rs. 9,810</p>
 <p>2MP</p>	<p>DS-2CD1027G0-L (2MP Bullet)</p>	<p>1/2.8" Progressive CMOS, H.265+, 2.8/4mm LENS White-light upto 30m , 3D DNR, IP67,ONVIF color 0.001lux/F1.0, 12VDC, 24x7, Digital WDR Main Stream: 50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720)</p>	<p>Rs. 9,810</p>
 <p>4MP</p>	<p>DS-2CD1347G0-L (4MP Dome)</p>	<p>1/2.7" CMOS Sensor, 2.8/4mm LENS, BLC White-light up to 30m , 3D DNR, IP67, ONVIF color 0.001lux/F1.0, 12VDC, 24x7 Color image 1080p@25fps, 120dB TrueWDR, smart light</p>	<p>Rs. 13,749</p>









 <p>4MP</p>	<p>DS-2CD1047G0-L (4MP Bullet)</p>	<p>1/2.7" CMOS Sensor, 2.8/4mm LENS, BLC White-light upto 30m , 3D DNR, IP67, ONVIF color 0.001lux/F1.0, 12VDC, 24x7 Main Stream: 50Hz: 20 fps (2560 × 1440) 25 fps (2304 × 1296, 1920 × 1080, 1280 × 720) 60Hz: 20 fps (2560 × 1440) 30 fps (2304 × 1296, 1920 × 1080, 1280 × 720)</p>	<p>Rs. 13,749</p>
ColorVu Network Cameras			
Camera	Model	Description	MRP
 <p>2MP</p>	<p>DS-2CD2123G2-IU (2 MP Vandal Fixed Dome)</p>	<p>Image Sensor1/2.8" Progressive Scan CMOS, Max. Resolution 1920 × 1080, LensType Fixed focal lens, 2.8 and 4 mm optional, Video Compression Mainstream: H.265/H.264/H.264+/H.265</p>	<p>Rs. 12,916</p>
 <p>2MP</p>	<p>DS-2CD2027G2-L(U) (2MP ColovVu Fixed mini bullet)</p>	<p>1/2.8" Progressive Scan CMOS, H.265+ compression, 24/7 colorful imaging, Water and dust resistant (IP67), WDR: 120dB, 2.8, 4, and 6 mm optional fixed lens, BLC, HLC, 3D DNR, Day/Night Switch, Face capture</p>	<p>Rs. 16,350</p>
 <p>4 MP COLORVU BULLET</p>	<p>DS- 2CD2047G2-LU (4 MP COLORVU BULLET)</p>	<p>1/1.8" Progressive Scan CMOS, H.265+ compression, 24/7 colorful imaging, 2.8,/4/6 mm optional fixed focal lens, 32 Kbps to 8 Mbps video bit rate, BLC, HLC, 3D DNR, Water and dust resistant (IP67) Main Stream: 50 Hz: 25 fps (2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720)</p>	<p>Rs. 18,431</p>
 <p>4 MP ColorVu Fixed Bullet</p>	<p>DS-2CD2T47G2-L (4 MP ColorVu Fixed Bullet)</p>	<p>1/1.8" Progressive Scan CMOS, 2688 x 1520 max resolution ,60m WLR, BLC, HLC, 3D DNR: 130 db WDR, in built storage up to 256 GB Main Stream: 50 Hz: 25 fps (2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720)</p>	<p>Rs. 21,701</p>
 <p>8MP Color Vu</p>	<p>DS-2CD2087G2-L (8MP Color Vu)</p>	<p>1/1.2" Progressive Scan CMOS, Color: 0.0005 Lux @ (F1.0, AGC ON), 3840 × 2160 max resolution, WDR: 130 dB, 2.8/4/6mm lens, 40m WLR, audio Main stream: 50 Hz: 25 fps (3840 × 2160, 3200 × 1800 , 2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 24 fps (3840 × 2160) 30 fps (3200 x 1800 , 2688 × 1520, 1920 × 1080, 1280 × 720)</p>	<p>Rs. 29,831</p>








PTZ Network Cameras

 <p>2MP</p> 	<p>DS-2DE4215IW-DE (2MP PTZ)</p>	<p>H.265+/H.265 video compression, 5- 75mm LENS, Upto 100m IR, optical zoom 15x, digital zoom 16x, Color 0.02lux/F1.5, DWDR,3D DNR, IP66, 2688x1520:25fps(P)/30fps(N) Main Stream: 50 Hz: 25 fps (1920 × 1080, 1280 × 960, 1280 × 720) 60 Hz: 30 fps (1920 × 1080, 1280 × 960, 1280 × 720)</p>	<p>Rs. 42,440</p>
 <p>4MP</p> 	<p>DS-2DE4425IWDE (4MP PTZ)</p>	<p>1/2.8" Progressive CMOS, H.265+/H.265 video compression, 3 Streams Upto 100m IR, optical zoom 25x, digital zoom 16x, Color: 0.005Lux @ (F1.6, AGC ON); B/W: 0.001Lux @ (F1.6, AGC ON), Auto-tracking, WDR, HLC 3D DNR, 2560x1440 max resolution:25fps(P)/30fps(N)</p>	<p>Rs. 59,236</p>




4K 8MP FIXED IR Bullet/Turret Network Camera			
 4K 8MP 	<p>DS-2CD2183G0-IU (8MP Turret)</p>	<p>1/2.5" Progressive CMOS H.265, H.265+, H.264, H.264+, 120db WDR, IP66, IK10 Upto 30m IR, 3840x2160@15fps, Color: 0.028 Lux/F2.0, 3D DNR, BLC, ROI, HLC 4-VCA, 3-Stream, ONVIF, on board storage</p>	<p>Rs. 19,172</p>
 4K 8MP 	<p>DS-2CD2T85G1-I5 (8MP Turret)</p>	<p>1/2" Progressive CMOS, H.265+, 120db WDR, 4K Upto 50m IR, 3840x2160@20fps, Smart IR, IP67 Color:0.008 Lux /F1.6 ,3DDNR, BLC, ROI, HLC 6mm Lens,5VCA, ONVIF,3-Stream, on board storage</p>	<p>Rs. 26,041</p>
4MP AcuSense IR Fixed Bullet Turret Network Camera			
 4MP 	<p>DS-2CD2346G1-I (4MP Turret)</p>	<p>1/2.7" Progressive CMOS, H.265+, H.264+, H.265, H.264 , 2.8 mm/4 mm/6 mm fixed lens , 120db WDR, 2K Upto 50m IR, Max. 2688x1520@30fps, smart IR, IP67 color 0.007lux/F1.6, 3D DNR, BLC, ROI, ONVIF, false alarm filter, on board storage</p>	<p>Rs. 16,165</p>













Vari-Focal Network Bullet Camera			
 <p>2MP</p>	<p>(2MP VF Bullet Camera) DS-2CD1623G0-I(Z)</p>	<p>1/2.7" CMOS Sensor, H.265+, 3D DNR, IP67 Upto 50m IR, BLC, 3D DNR, ROI, DWDR, IR cut Filter, HLC ICR, Color: 0.005 Lux @(F1.6, AGC ON), 12VDC, M16 Lens, Up to 256 GB SD card slot for storage 1920x1080@25fps/30fps, 2.8-8mm motorized varifocal lens</p>	<p>Rs. 16,650</p>
 <p>2MP</p>	<p>DS-2CD1723G0-IZ (2MP DOME)</p>	<p>1/2.7" Progressive Scan CMOS, 1920 × 1080, Main stream: H.265+/H.265/H.264+/H.264 , 32 Kbps to 8 Mbps video bit rate, BLC, 3D DNR, Auto Schedule, Day-Night, Motion detection, video tampering alarm</p>	<p>Rs. 16,650</p>
Pro-Series Darkfighter Varifocal Camera			
 <p>8MP</p>	<p>DS-2CD2685G0-IZS (8MP VF Bullet)</p>	<p>1/2" CMOS Sensor, H.265+, 3D DNR, IP66, IK10, Up to 50m IR, BLC, ROI, DWDR, IR cut Filter, HLC SD support, Alarm, Audio, behavior analysis 3840x2160(4K)@20fps, 2.8-12mm motorized Lens</p>	<p>Rs. 41,675</p>
Motorize Varifocal Bullet			
 <p>2MP</p>	<p>DS-2CD1A23G0-IZU (2MP Varifocal PT Bullet)</p>	<p>1/2.7" Progressive Scan CMOS, H.265+ compression technology, 1920 × 1080 max resolution, Day & Night IR Cut Filter, Water and dust resistant (IP66), EXIR 2.0, Pan, tilt and zoom ability Main Stream: 50 Hz: 25 fps (1920 × 1080, 1280 × 720) 60 Hz: 30 fps (1920 × 1080, 1280 × 720)</p>	<p>Rs. 16,650</p>
 <p>4MP</p>	<p>DS-2CD1643G0-IZ (4MP Bullet)</p>	<p>1/3" Progressive Scan CMOS, H.265+, 3D DNR, IP67, upto 50m, BLC, ROI, IR cut filter, WDR, 3D DNR 2.8-12mm, 0.005 Lux @(F1.6, AGC ON), 2560x1440 max resolution @20fps/25fps</p>	<p>Rs. 20,407</p>










	<p>DS-2CD2683G2-IZS (8MP AcuSense Motorized VF Bullet)</p>	<p>1/2.8" Progressive Scan CMOS Min. Illumination Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR Shutter Speed 1/3 s to 1/100,000s, Slow Shutter P/N P/N Wide Dynamic Range: 120 dB, Day & Night IR cut filter, Angle Adjustment: Pan: 0° to 355°, tilt: 0° to 90°, rotate: 0° to 360°</p>	<p>Rs. 33,095</p>
--	--	---	--------------------------






NVR			
	DS-7104NI-Q1/M (4-Port)	H.265+/H.265/H.264+/H.264 video compression, up to 40/60 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth. 2-ch@4MP or 4-ch@1080p playback resolution, 1 SATA interface (up to 6 TB capacity per HDD)	Rs. 9,020
	DS-7104NI-Q1/4P (4-Port/PoE Built)	H.265+/H.265/H.264+/H.264 video compression, 2-ch@4 MP or 4-ch@1080p playback resolution, 1 SATA interface (up to 6 TB capacity per HDD), 1 self-adaptive 10/100 Mbps Ethernet interface	Rs. 15,033
	DS-7108Ni-Q1/M (8-Port)	H.265+/H.265/H.264+/H.264 video compression, 1 SATA interface (up to 6 TB capacity per HDD), Up to 40/60Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth, 2-ch@4 MP or 4-ch@1080p playback resolution	Rs. 11,023
	DS-7604NI-Q1 (4-Port)	Up to 4-ch IP camera inputs, H.265+/H.265/H.264+/H.264 video formats, Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity, 1 SATA interface for HDD connection (up to 8 TB capacity per HDD), 1-ch Motion Detection 2.0, 12 VDC	Rs. 13,029
	DS-7608NI-Q1 (8-Port)	Up to 8-ch IP camera inputs, H.265+/H.265/H.264+/H.264 video formats, Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity, 1 SATA interface for HDD connection (up to 8 TB capacity per HDD), 4-ch Motion Detection 2.0, 12 VDC	Rs. 14,364
	DS-7608NI-Q2 (8-Port)	Up to 8-ch IP camera inputs, H.265+/H.265/H.264+/H.264 video formats, Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity, 4-ch Motion Detection 2.0, 2 SATA interfaces for HDD connection (up to 8 TB capacity per HDD)	Rs. 17,704
	DS-7608NI-I2 (8-Port)	H.265+/H.265/H.264+/H.264 video formats, Up to 8/16/32-ch IP camera inputs, Up to 2 SATA interfaces for HDD connection, 8/16-ch synchronous playback, Dual stream recording, 12 VDC	Rs. 40,430
	DS-7616NI-Q2 (16-Port)	Up to 16-ch IP camera inputs, H.265+/H.265/H.264+/H.264 video formats, Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity, 2 SATA interfaces for HDD connection (up to 8 TB capacity per HDD), 4-ch Motion Detection 2.0	Rs. 20,041
	DS-7616NI-Q1 (16-Port)	Up to 16-ch IP camera inputs, H.265+/H.265/H.264+/H.264 video formats, Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity, 1 SATA interface for HDD connection (up to 8 TB capacity per HDD), 4-ch Motion Detection 2.0, 12 VDC	Rs. 16,702
	DS-7616NI-K2 (16-Port)	H.265+/H.265/H.264+/H.264 video format, Up to 2-ch@8 MP or 4-ch@4 MP or 8-ch@1080p decoding capacity, 2 SATA interfaces for HDD connection, 12 VDC	Rs. 28,060












	DS-7616NXI-12/4S (16-Port)	H.265+ video compression, H.265/H.265+/H.264/H.264+/MPEG4 video/audio decoding format, 2 SATA interfaces for two 3.5-inch HDDs, Recording at up to 12 MP resolution	Rs. 39,836
	DS-7632NI-K2 (32-Port)	H.265+/H.265/H.264+/H.264 video formats, Up to 32-ch IP camera inputs , Up to 2-ch@8 MP or 4-ch@4 MP or 8-ch@1080p decoding capacity, 2 SATA interfaces for HDD connection	Rs. 38,850
	DS-7716NI-K4 (16-Port)	Up to 16-ch IP camera inputs , H.265+/H.265/H.264+/H.264 video formats, Up to 2-ch@8 MP/4-ch@4 MP/8-ch@1080p decoding capacity, 4 SATA interfaces for HDD connection (up to 10 TB capacity per HDD), 16-ch synchronous playback	Rs. 50,774
	DS-7732NI-K4 (32-Port)	Up to 32-ch IP camera inputs , H.265+/H.265/H.264+/H.264 video formats, Up to 2-ch@8 MP/4-ch@4 MP/8-ch@1080p decoding capacity, 4 SATA interfaces for HDD connection (up to 10 TB capacity per HDD), 16-ch synchronous playback	Rs. 65,138
	DS-8616NI-K8 (16 Port)	H.265+/H.265/H.264+/H.264 video formats, Up to 8/16/32-ch IP camera inputs , Up to 8-ch@1080p decoding capacity, 8 SATA interfaces (up to 8 TB capacity for each HDD), 8/16-ch synchronous playback	Rs. 89,857
	DS-8632NI-K8 (32 Port)	H.265+/H.265/H.264+/H.264 video formats, Up to 8/16/32-ch IP camera inputs , Up to 8-ch@1080p decoding capacity, 8 SATA interfaces (up to 8 TB capacity for each HDD), 8/16-ch synchronous playback	Rs. 1,03,219
	DS-8664NI-I8 (64 Port)	H.265+/H.265/H.264/H.264+ video compression, 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p, 64-ch video output @ 4KUHD & 2-ch Audio , 8 SATA interfaces for 8HDDs upto 10 TB, 1 eSATA interface , 320/256 Mbps bitrate, Hik Cloud P2P & HiDDNS	Rs. 1,79,541



SMART Cameras

 <p>2MP</p>	<p>DS-2PT3326IZ-DE3 (2MP PanoVU PTZ)</p>	<p>3-ch (1/2.8" CMOS Sensor),H.265+/H.265 10m IR, optical zoom 4x, digital zoom 16x color 0.05lux/F2.0, Focus 2.8-12mm 1920x1080:25fps(P)/30fps(N)</p>	<p>Rs. 16,165</p>
 <p>2MP</p>	<p>IDS-2CD8626G0/P-IZS (2MP VF ANPR)</p>	<p>1/1.8" Progressive CMOS, H.264, 2.8-12mm LENS 120m IR, IP66, Vehicle Detection, NEMA4X, IP67 ICR 0.002lux/F1.2, 5 streams, smart intelligence 1920x1080:60fps, 120dB WDR, MicroSD storage</p>	<p>Rs. 2,23,175</p>
 <p>2MP</p>	<p>IDS-2CD8426G0/F-I (2MP Deep inview)</p>	<p>1/2.8" Progressive CMOS, H.264, 2-ch(4mmLENS) 10m IR, smart defog, 120dBWDR color 0.005lux/F1.5, 3D DNR, BLC, HLC, 1920x1080p:25fps(P)/30fps(N)</p>	<p>Rs. 2,29,813</p>



USB Camera			
 2MP 	DS-U02 (2 MP)	2 MP CMOS, 1920 × 1080 resolution, Min. illumination: 0.1 Lux @ (F1.2, AGC ON), Built-in microphone, 3.6 mm fixed focal lens, 24/7 Color Imaging	Rs. 4,382
Dashboard Camera			
  	AE-DC2015-B1 (Dash Camera)	Up to 1080p resolution, with 115°FOV, supports TF card storage (Max.128GB), G-sensor, built-in loudspeaker, 5 VDC, 1080p@25fps (Default); 720p@25fps	Rs. 7,590
   	AE-DN2312-C4 (Dash Camera)	Up to 1080p full HD camera, built-in wifi module, IPS full view touch panel, 1080p(1920*1080) resolution, built-in G-sensor, built-in mic and speaker, SD card for video recording up to (129GB), low power consumption and high performance	Rs. 16,420

Note:

- VAT is included in all prices.
- Cameras do not include power adapters and brackets.
- Devices with burnt board, physical damage and water rusting are not valid for warranty.
- Devices are under 2-year replacement warranty.
- HDD are under 1 year replacement warranty.
- Feel free to contact us in case of any queries.












Value Series			
	5 Port Fast Ethernet Switch (DS-3E0105D-E)	Support ADI/ADIX, 10/100 Mbps adaptive Ethernet ports, 5 V DC, 0.6 A, 1 Gbps switching capacity	Rs. 985
	8 Port Fast Ethernet Switch (DS-3E0108D-E)	10/100 Mbps adaptive Ethernet ports, Support ADI/ADIX, 5 V DC, 0.6 A, Support desktop and wall-mounting, Plug & play, and easy to use	Rs. 1264
Hikvision Unmanaged Gigabit Switch			
Switch	Model	Description	MRP
	DS-3E0505D-E (5-Port Gigabit Switch)	Unmanaged Gigabit Switch , 5 Ports x1000Mbps IEEE802.3, IEEE802.3ustandard,2kMACSupport 5 VDC, Plug and play, Store-and-forward switching , 0.6A,10GbpsBackplanebandwidth	Rs. 1686
	DS-3E0508D-E (8-Port Gigabit Switch)	Unmanaged Gigabit Switch , 8 Ports x1000Mbps IEEE802.3, IEEE802.3ustandard,4kMACSupport 9VDC,1 A,16GbpsBackplanebandwidth	Rs. 3233
	DS-3E0508-E(B) (8 Port Gigabit Unmanaged Switch)	8 x 1000M Ethernet ports, Supports IEEE 802.3, IEEE 802.3u and IEEE 802.3x., 1000M network access, Wire-speed forwarding and non-blocking design	Rs.4217
	DS-3T0306HP-E/HS (4 Port Fast Ethernet Unmanaged Harsh POE Switch)	3 x 10/100 Mbps PoE ports, 6 KV surge protection for PoE ports , Up to 300 m long-range transmission, Wire-speed forwarding, Reliable fan-free design, Solid high-strength metal shell.	Rs.9837
Gigabit Switch			
	DS-3E0516-E(B) (16 port Gigabit switch)	32Gbps Exchange Capacity , 16 Ports, 16x 1000Mbps 220VAC,0.3A, 23.808Mbpspacketforwardrate IEEE802.3u/xstandard,4.1Mbitsinternalcache	Rs.9272
	DS-3E0524-E(B) (24 port Gigabit switch)	48Gbps Exchange Capacity , 24 Ports, 24x 1000Mbps 220VAC,0.7A, 35.712Mbpspacketforwardrate IEEE802.3u/xstandard,4.1Mbitsinternalcache	Rs. 12649
	DS-3T0506HP-E/HS (4 port gigabit unmanaged harsh poe switch)	3 x gigabit PoE ports, 1 x gigabit Hi-PoE port, 2 x gigabit SFP fiber optical ports , 6 KV surge protection, Up to 300 m long-range transmission, 12 Gbps switching capacity, RJ45 port , full duplex, MDI/MDI-X adaptive	Rs. 12,650







	HK-SFP-1.25G-20-1310 / HK-SFP-1.25G-20-1550	Single Power Supply 3.3V, Support 1.25G Ethernet, 1250 Mbps data rate, 0~20km distance, 1 connector quality, -9~-1dBm tx power Note: HK-SFP-1.25G-20-1310 has to work with HK-SFP-1.25G-20-1550 as a pair.	Rs. 6,975
	0 (SFP Modules)		
Hikvision Smart Managed Switch			
	<u>DS-3E1105P-EI</u> (Smart Managed)	1Gbps Switching Capacity, 5 Ports, 4x 100Mbps 48VDC, 1.35 A, 300m when extend IEEE802.3at/af standard, 6KV Surge Protection	Rs. 6466
	DS-3E1326P-E (Smart POE)	PoE Standard Ports 1 to 24: IEEE 802.3af, IEEE 802.3at, Switching Capacity 8.8 Gbps, Max. Power Consumption : 400 W , Operating Temperature-10°C to 55°C(14°F to 131°F)	Rs. 59030
Hikvision Web POE Switch			
	DS-3E1318P-E (L2 Web POE Switch)	Layer 2 network switch designed for video data transmission, Web management: supports intelligent management such as VLAN, link aggregation, QoS, loop guard via STP, SNMP, etc. to reduce project difficulty and time, IEEE 802.3 af & at high POE power supply, Maximum 250 m long distance PoE	Rs. 44,692
Hikvision POE Switch			
	DS-3E0105P-E/M (4-Port PoE Switch)	L2,Unmanaged,5Ports,4x100m 48VDC,0.8A, 250mwhen extend IEEE802.3, IEEE802.3u standard	Rs. 4492
	DS-3E0109P-E/M (8-Port PoE Switch)	L2, Unmanaged, 9 Ports IE51 VDC, 1.25 A, 250mwhenextendIEEE802.3af, 8x100mstandard	Rs. 8512
	DS-3E0318P-E/M (16-Port PoE Switch)	L2,Unmanaged,16Ports,100m(N) 100~240VAC, 50/60Hz IEEE802.3at standard, 250mwhen extend	Rs. 23,892
	DS-3E0326P-E/M (24-Port PoE Switch)	L2,Unmanaged,24Ports IEEE802.3af,24x100m, 250mwhenextend 100~240 VAC, 50/60Hz	Rs. 32,326
Hikvision Dual Uplink POE Switch			
	DS-3E0106P-E/M (4 port Dual Up Link)	Unmanaged, 1.6 Gbps Switching Capacity , 4 Ports, IEEE 802.3,IEEE802.3u,IEEE802.3x,48VDC,0.8A, 300 m long-range transmission.	Rs. 5340



	DS-3E0310P-E/M (8 Port Fast Ethernet Unmanaged POE Switch)	8 × 10/100Mbps PoE ports, and and 2 × Gigabit RJ45 port, 6 KV surge protection for PoE ports, Up to 300 m long-range transmission, Wire-speed forwarding.	Rs.9837
Gigabit Unmanaged POE			
	DS-3E0505P-E/M (4 PORT POE GIGA SWITCH)	Unmanaged, IEEE802.3,IEEE802.3u,IEEE802.3x, IEEE 802.3ab, and IEEE 802.3z standard, SwitchingCapacity 10 Gbps, PowerSupply48VDC,0.8A	Rs. 5903
	DS-3E0510P-E/M (8 PORT POE GIGA SWITCH)	Unmanaged, Standard IEEE 802.3, IEEE 802.3u,IEEE 802.3x, IEEE 802.3ab, IEEE 802.3z , Switching capacity 20 Gbps, Power supply 48VDC, 1.35 A	Rs. 10963
	DS-3E0520HP-E	12 × gigabit PoE ports, 4 × gigabit Hi-PoE ports, 2 × gigabit RJ45 ports, and 2 × gigabit fiber optical ports.	Rs. 39296
	DS-3E0518P-E/M (16 port POE switch)	16 × Gigabit PoE ports, 2 × Gigabit SFP fiber optical ports,IEEE 802.3at/af standard, IEEE 802.3, IEEE 802.3u, and IEEE 802.3x standard, 6 KV surge, protection for PoE ports, PoE power management, Gigabit network access	Rs.30,921
	DS-3E0526P-E/M (24 Port POE switch)	24 × Gigabit PoE ports, 2 × Gigabit SFP fiber optical ports.,IEEE 802.3at/af standard, IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z standard, 6 KV surge protection for PoE ports PoE power management	Rs.42,164
Industrial and WebManaged POE Switch			
	DS-3T0306P (Industrial Switch)	4-port unmanaged, supports 802.at/af, IP40 IEEE802.3x Full Duplex, Backpressure Flow Control	Rs.42,164
	DS-3E1310P-E (Industrial Switch)	Managed, 8 Ports, 100~240 V AC, 50/60Hz IEEE802.3af, IEEE802.3at, 5.4Gbps, 4/6KV protections	Rs.21381
Hikvision Full Managed POE Switch			
	DS-3E2528P (24 port Full managed POE)	24 Gigabit Poe electrical ports and 4 Gigabit combo ports, support static routing, policy routing, rip, OSPF and other three-layer routing protocols, GMP snooping and GRMP for filtering multicast traffic, Port-based VLAN, IEEE 802.1Q VLAN, and GVRP to ease network planning, Easy network management by web browser, Console, Telnet, SSH.	Rs. 99,363






Hikvision Router			
	DS-3WR3N	2.4 GHz: 300 Mbps, IEEE 802.11b/g/n @2.4 GHz, 5-dBi external antennas, Dual antennas for maximum coverage, Supports IPTV, 4 × RJ45, 10/100 Mbps auto-negotiation, ≤ 5.4 W max power consumption, 134 g (0.295 lb) weight, Wireless Router × 1, Ethernet cable × 1, Quick installation guide × 1	Rs. 2330
Switching Power Supply			
	DS-2FA1205-DW-IN (5 Ampere)	Input: 200-240 VAC, 50-60Hz, 2A Max Output: 12VDC, 5A Max, Metal Housing	Rs. 1353
	DS-2FA120A-DW-IN (10 Ampere)	Input: 200-240 VAC, 50-60Hz, 2A Max Output: 12VDC, 10A, Metal Housing	Rs. 1892
	DS-2FA120K-DW-IN (20 Ampere)	Input: 200-240 VAC, 50-60Hz, 3.5A Max Output: 12VDC, 20A, Metal Housing	Rs. 2971

Note:

- VAT is included in all prices.
- Devices with burnt board, physical damage and water rusting are not valid for warranty.
- Devices are under 2-year replacement warranty.
- HDD are under 1 year replacement warranty.
- Feel free to contact us in case of any queries.







Camera	Model	Description	MRP
Hikvision Logo WD Purple HDD			
	1 TB HDD (WD-10PURX-78)	Supported cameras: up to 64, Standby consumption: 0,4W, Dimensions: 101,6 x 26,1 x 147 mm, Weight: 450 g , Working temperature: 0°C ~ +65°C.	Rs. 8938
	<u>WD PURPLE (With Hikvision Certified)</u> (2TB)	BufferAmount-64MB,RoHScompatible Transfer Rate-145MB/s 64MB Cache, SATA 6Gb/s 23dBA, 300,000 unload cycles, 5400RPM	Rs.12100
	<u>WD PURPLE(With Hikvision Certified)</u> (4TB)	BufferAmount-64MB,RoHScompatible Transfer Rate-145MB/s 64MB Cache, SATA 6Gb/s 23dBA, 300,000 unload cycles, 5400RPM	Rs.18565
	<u>WD PURPLE (With Hikvision Certified)</u> (6TB)	BufferAmount-64MB,RoHScompatibleTransfer Rate- 145MB/s 64MB Cache, SATA 6Gb/s 23dBA, 300,000 unload cycles, 5400RPM	Rs. 32313
	<u>WD PURPLE(With Hikvision Certified)</u> (8TB)	BufferAmount-64MB,RoHScompatible Transfer Rate-145MB/s 64MB Cache, SATA 6Gb/s 23dBA, 300,000 unload cycles, 5400RPM	Rs.42625
Cable	Model	Description	MRP
Hikvision Analog and Network Cable			
	<u>DS- 1LH1SCA3C- 090B</u> (3+1 Coaxial Cable)	90m, RG59, Oxygen Free Copper Copper-clad Aluminum braided VW-1 Flameretardantrated Anti-interference/Aging performance	Rs. 4792
	<u>DS-1LN6U-W/CCA</u> (UTP CAT6 CCA)	CAT. 6 CCAU/UTP 4x2x23AWG 1 PVC, ISO/IEC11801, HDPE 305m CCA, Coppercontent:27% Material-Solid-Bare Copper	Rs. 12013
	<u>DS-1LN6U-G</u> (UTP CAT6)	U/UTP CAT6-6P- PVC-CMX category ISO/IEC11801, ANSI/TIA-568-C.2,RoHS2.0TIA-568-C.2 YD/T1019 Standard Material-Solid-Bare Copper	Rs. 23238






Note:

- VAT is included in all prices.
- Cameras do not include power adapters and brackets.
- Devices with burnt board, physical damage and water rusting are not valid for warranty.
- Devices are under 2-year replacement warranty.
- HDD are under 1 year replacement warranty.
- Feel free to contact us in case of any queries.





U RACK			MRP
	SMK54044U RACK	front door with white tempered glass door and smallround lock, side door with two plastic buckles, 2 side doors, top cover has a metal inlet cover, 2 fan inlet holes, front door and the bottom plate are each welded with a grounding stud, 4 brackets (U standard uses silk screen), a pair of L-shaped spacers (1.2mm), beam adopts the OB hole method, fixing bracket adopts M6 floating screws and flange nuts, top, and bottom, the back plate and the cross beam are designed as a whole, Dimension: 540*450*260	Rs.7500
	SMK54066U RACK	front door with white tempered glass door and smallround lock, side door with two plastic buckles, 2 side doors, top cover has a metal inlet cover, 2 fan inlet holes, front door and the bottom plate are each welded with a grounding stud, 4 brackets (U standard uses silk screen), a pair of L-shaped spacers (1.2mm), beam adopts the OB hole method, fixing bracket adopts M6 floating screws and flange nuts, top, and bottom, the back plate and the cross beam are designed as a whole, Dimension: 540*450*350	Rs. 9000
	SMK54099U RACK	front door with white tempered glass door and smallround lock, side door with two plastic buckles, 2 side doors, top cover has a metal inlet cover, 2 fan inlet holes, front door and the bottom plate are each welded with a grounding stud, 4 brackets (U standard uses silk screen), a pair of L-shaped spacers (1.2mm), beam adopts the OB hole method, fixing bracket adopts M6 floating screws and flange nuts, top, and bottom, the back plate and the cross beam are designed as a whole, Dimension: 540*450*480	Rs. 13000
	SMK5412 12U RACK	front door with white tempered glass door and smallround lock, side door with two plastic buckles, 2 side doors, top cover has a metal inlet cover, 2 fan inlet holes, front door and the bottom plate are each welded with a grounding stud, 4 brackets (U standard uses silk screen), a pair of L-shaped spacers (1.2mm), beam adopts the OB hole method, fixing bracket adopts M6 floating screws and flange nuts, top, and bottom, the back plate and the cross beam are designed as a whole, Dimension: 540*450*615	Rs. 20000



	<p>SMA5418 18U RACK</p>	<p>front door with white tempered glass door and smallround lock, side door with two plastic buckles, 2 side doors, top cover has a metal inlet cover, 2 fan inlet holes, front door and the bottom plate are each welded with a grounding stud, 4 brackets (U standard uses silk screen), a pair of L-shaped spacers (1.2mm), beam adopts the OB hole method, fixing bracket adopts M6 floating screws and flange nuts, top, and bottom, the back plate and the cross beam are designed as a whole, Dimension: 540*450*902</p>	<p>-</p>
	<p>SMB6622 22U RACK</p>	<p>front door with white tempered glass door and smallround lock, side door with two plastic buckles, 2 side doors, top cover has a metal inlet cover, 2 fan inlet holes, front door and the bottom plate are each welded with a grounding stud, 4 brackets (U standard uses silk screen), a pair of L-shaped spacers (1.2mm), beam adopts the OB hole method, fixing bracket adopts M6 floating screws and flange nuts, top, and bottom, the back plate and the cross beam are designed as a whole, Dimension: 600*600*1166</p>	<p>-</p>
	<p>SNB6632CD32U RACK</p>	<p>C type tempered glass door with advanced spring lock D type metal door with small round lock, 2pcs removable side panels, each with 2 small round lock, 4pcs mounting rails, two Galvanized of rails and ground bus and brush panel in the bottom panel as a standard equipment, 4 pcs leveling feet, can adjust height freely, high quality casters, 2 casters with break, one top panel, with cable entry cover, fan tray is optional: 600mm depth with 2fans, 800mm, 1000mm depth with 4 fans, bottom plate with cable entry, height $\leq 32U$, 20 sets of cage nuts, flat packing (assembled packing is also available), standard rack doesn't include fans, shelves, bottom panel, and any other 19" mounting accessories, loading Capacity up to 800kg, Dimension: 600*600*1610</p>	<p>Rs. 58000</p>



	<p>SNB6642CD 42U RACK</p>	<p>C type tempered glass door with advanced spring lockD type metal door with small round lock, 2pcs removable side panels, each with 2 small round lock, 4pcs mounting rails, two Galvanized of rails and ground bus and brush panel in the bottom panel as a standard equipment, 4 pcs leveling feet, can adjust height freely, high quality casters, 2 casters with break, one top panel, with cable entry cover, fan tray is optional:600mm depth with 2 fans, 800mm,1000mm depth with 4 fans, bottom plate with cable entry, height $\leq 42U$, 20 sets of cage nuts, flat packing (assembled packing is also available), standard rack doesn't include fans, shelves, bottom panel, and any other 19" mounting accessories, loading Capacity up to 800kg, Dimension: 600*600*2055</p>	<p>Rs. 105000</p>
Model		Description	DPP
Server Rack			
	<p>SSY8142 (19" SERVER RACK) 2020*820*370 (Dimension) Weight=132Kgs</p>	<p>19inch server rack</p> <ol style="list-style-type: none"> 1. Color: RAL9005(Black) 2. perforated front door with single lock 3. Split vented rear door with single lock 4. without side panels 5. 4pcs mounting profiles and 2pcs vertical cable rails (without cable management) 6. with leveling feet and castors 7. 40 sets of cage nuts 8. Flat packing 9. The loading capacity is 1000KGS <p>This price not include fans, shelves, bottom panel, and any other accessories</p>	<p>Rs. 1,31,000</p>
<p>SSY8132 (19" SERVER RACK) 1575*820*370 (Dimension) Top-72.5 Kgs Base-37Kgs Weight=109.5Kgs</p>	<p>Rs. 1,03,000</p>		
<p>SSY8127 (19" SERVER RACK) 1355*820*370 (Dimension) Weight=99Kgs</p>	<p>Rs. 96,500</p>		



U-Rack			MRP
	Safe Cash Box	Safe BGY-D Series-Small D-30	Rs. 27000
	Safe Cash Box	Safe BGY-D Series-Big D-50	Rs. 48000
COOLING FAN			MRP
	SWWMFA NTRAY2 COOLING FAN - Y2	for wall mount cabinet, fan tray with 2fans, 1.2m wire and UK plug , no switch, with metal tray, rated voltage:220V-240V, material: SPCC, color: RAL9005, Dimension: 260*140*40	Rs.3700
	SWSNBFA NTRAY2 COOLING FAN- Y2- 600	Color: RAL9005(Black), top fan tray with 2 fans for 600mm depth SNB network rack, Dimension: 346*412*40	Rs.3700
	SWMCABLEDUCT 1U	1U METAL CABLE MANAGER	-
POWER CORD			MRP
	SW- UTPCAT6P P24 POWER CORD	Color: RAL9005, Material: Aluminum, Size: 1U height, 19 inches in length, horizontal, Jack: 6-bit British standard jack, Function module: with zero fire double break switch , Plug: British standard plug with protective sleeve , Cable: three cores , 1.5 square meters, 2 meters, Voltage: 220V, Current: 1.5 square 10A, Label: Silver RoHS & CE label	Rs.2550
	SW-1U-6V-MS	Universal Power Cord	-
	CAT6 UTP PLUG	CAT6 UTP PLUG Copper	Rs. 10
	PATCH PANEL 24 PORT 19INCH IU	CAT6 UTP 24 port Patch Panel, 19inch 1U	Rs.4125



	SW-CAT6-2748	Patch Panel 48 Port	-
	BNC 20CM WIRE PURE COPPER	BNC 20CM WIRE, Pure Copper	Rs. 27
	DC 25CM WIRE PURE COPPER	DC 25CM WIRE, Pure Copper	Rs. 16
	Cabinet Tray	Fixed Shelf for 450mm Wall-mount Cabinet Material: SPCC Loading Capacity:20KGColor: RAL9005(Black)	Rs. 2000
	Cabinet Tray	Fixed Shelf for 600mm SNB network rack Material: SPCC Loading Capacity:90KGColor: RAL9005(Black)	Rs. 3250
	Media Converter Normal	100M MC single fiber, single mode 1310nm / 1490nm20km SC; must work in pairs	Rs. 4000
	Media Converter Giga	1000M MC single fiber, single mode 1310nm / 1490nm20km SC; must work in pairs	Rs. 6500
	Fiber Pole Junction Box	2port in 16port out 16 cores outdoor FTTH terminal box for splice or install 1 :16 PLC minit type splitter	Rs. 4250
	Tiffin box	1 port ftth socket, fit 1pcs SC simplex adaptor , with one metal part	Rs. 450
	14 Way Media Converter Power Junction	14 slots MC rack, single power AC220V input 4 fans	Rs. 21000
	Cable Clamp	ACC Cable clamp 2x6 PA	Rs. 250



	Cleaningpen	Cleaning pen for SC/FC/E2000 more than 800times	Rs. 4750
	Fiber PatchCord LC	MM OM3 50/125um 0,9mm /Red	Rs. 400
	Fiber PatchCord LC	MM OM2 50/125um 0,9mm /Yellow	Rs. 300
	FC/PC Simplex adapter	FC/PC Simplex adapter,separated	Rs. 150
	FC/PC Simplex adapterZINC	FC/PC Simplex adapter,integrated, ZINC	Rs. 150
	FC/PC Simplex adapter BIG	FC/PC Simplex adapter,Singlemode BIG	Rs. 150
	FBT Coupler	FBT Coupler 1*2 SC-SC	Rs. 2250
	Splitter	PLC Splitter 1*4SC	Rs. 1500
	Splitter	PLC Splitter 1*8SC	Rs. 2250



Note:

- VAT is included in all prices. Devices are under 2-year replacement warranty
- HDD are under 1-year replacement warranty
- Wire accessories are not under warranty
- HDD are under 1 year replacement warranty
- Feel free to contact us in case of any queries
- Devices with physical damage and water rusting are not valid for warranty.